

### Annex B2 - Product environmental attributes Servers/Data Storage Products

The declaration may be published only when all rows and/or fields marked with \* are filled-in (N/A for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo		
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs		Lenovo	
e-mail address	Alvin L Carter			
	alcarter@lenovo.com			
Internet site *	https://www.lenovo.com/us/en/about/sustainability			
Additional information	The latest version of this document can be found at:			
	http://www.lenovo.com/ecodeclaration			

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
conforms to the stateme	ents given in this declaration.				
Type of product *	Type of product * SERVER				
Commercial name *	Lenovo ThinkSystem SR850P				
Model number *	7D2F, 7D2G, 7D2H				
Issue date *	Feb. 6, 2020				
Intended market *	🔀 Global 🗌 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

Model n	umber *	7D2F, 7D2G, 7D2H	Logo			
Issue date *		* Feb. 6, 2020		Lend		Этн
Produc	t environ	mental attributes - Legal requirements		Require	ment	t met
ltem				Yes	No	N/A
P1	Hazardo	ous substances and preparations				
P1.1*	Product	s do comply with current European RoHS Directive. (See legal reference and NOTE	B1)	$\boxtimes$		
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.				
P1.3*	Products hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), omofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach ethane, methyl bromide (see legal reference). Comment: Legal reference has no m ration values.				
P1.4*		s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polych /l (PCT) in preparations (see legal reference).	lorinated	$\boxtimes$		
P1.5*	chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 cart ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).				
P1.6*	(see leg	th direct and prolonged skin contact do not release nickel in concentrations above 0 al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.	,5 μg/cm²/wee	k 🔀		
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail oww.lenovo.com/us/en/sustainability-resources	contact):	$\boxtimes$		
P2	Batterie	S				
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with t Information on proper disposal is provided in user manual. (See legal reference)	he disposal	$\boxtimes$		
P2.2*		s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadm	nium. (See lega	ıl 🔀		
P2.3*	Batterie	s and accumulators are readily removable. (See legal reference)		$\boxtimes$		
P2.4*	Docume	ntation includes the number of cycles the (secondary) battery can withstand. (See le	egal reference)			
P2.5*	When internal batteries of a notebook computer cannot be "accessed and replaced by a nonprofessional user", the related text is present and legible on the external packaging (see legal reference)					
P3		nity verification & Eco design (ErP)				
P3.1*	The pro	duct is CE-marked to show conformance with applicable legal requirements (see legularation of Conformity can be requested at: <a href="https://www.lenovo.com/us/en/complian">https://www.lenovo.com/us/en/complian</a>		$\boxtimes$		
P3.2*	The pro	duct complies with the Eco design requirements for energy-related products, al reference).		$\boxtimes$		
	Require	d information is; given in item P15 or added to this document, available at: https://www.lenovo.com/us/en/compliance/e	eco-declaration	$\boxtimes$		
P5	Product	packaging				
P5.1*	Packagi	ng and packaging components do not contain more than 0,01% lead, mercury ent chromium by weight of these together.	/, cadmium ar	nd 🔀		
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of the legal reference).	of the material(	s) 🔀		
P5.3*	The prod (see leg	duct packaging material is free from ozone depleting substances as specified in the N al reference). nt: Legal reference has no maximum concentration values.	Iontreal Protoc	ol 🔀		
P6		nt information				
P6.1*		on for recyclers/treatment facilities is available (see legal reference).				

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model nu	mber *	7D2F, 7D2G, 7D2H	Logo			
Issue dat	:e *	Feb. 6, 2020		Len	OVC	<b>D</b> <sub>TH</sub>
Product		mental attributes - Market requirements (See General NOTE GN b	pelow)			
		onmental conscious design		Require		
Item P7		tory to fill in. Additional information regarding each item may be found under P14. Disassembly, recycling		Yes	No	N/A
P7.1*		thave to be treated separately are easily separable				
P7.2*		naterials in covers/housing have no surface coating.			╞	╞
P7.3*		arts > 100 g consist of one material or of easily separable materials.			⊢⊢	┢
P7.4*		arts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.			╞	⊢⊢
P7.5		arts are free from metal inlays or have inlays that can be removed with commonly av	vailable tools		╞	╞
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).			╞	╞
	Product					
P7.7*		ing can be done e.g. with processor, memory, cards or drives				
P7.8*		ig can be done using commonly available tools			H	⊢⊢
P7.9	10	arts are available after end of production for: years				-#-
P7.10		s available after end of production for: years				╞
11.10		and substance requirements				
P7.11*		cover/housing material type (e.g. plastics, metal, aluminum):				
		type: Metal Material type: Plastic Material	l type:			
P7.12	Insulation	n materials of external electrical cables are PVC free.				
P7.13		n materials of internal electrical cables are PVC free.				
P7.14	weight (1 polyvinyl	plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bro 1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in in 25% post-consumer recycled content.	retardants, ar	nd		
P7.15	Printed c	ircuit boards, PCBs (without components) are low halogen: all $\square$ PCBs > 25 g $\square$ ed in IEC 61249-2-21. (See <sup>5</sup> NOTE B2)	are low haloge	en 🗌		
P7.16	Flame re Marking:	tarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4:				
P7.17		nemical specifications of flame retardants in printed circuit boards > 25 g (without co additive) , TBBPA (reactive) (See NOTE B3), Other: chemical name: ,	mponents): CAS #:			
		nemical specifications of flame retardants in printed circuit boards (without compone g ISO 1043-4:	nts) > 25 g			
P7.18	concentra 1. Chemi 2. Chemi	ame retarded plastic parts > 25 g contain the following flame retardant substances ations above 0,1%: ical name: , CAS #: (See NOTE B4) ical name: , CAS #: " ical name: , CAS #: "	s/preparations	in		
		nemical specifications of flame retardants in plastic parts > 25 g according ISO 1043				
P7.19	assigned	parts > 25 g, flame retardant substances/preparations above 0,1% are used which the following Risk phrases; and Hazard statements:				
P7.20*		rce(s) for these classifications is/are found at (add URL(s)): , (Se sumer recycled plastic material content is used in the product (See Note B6):	ee note B5)			
	a) Of t a pe or	t least one of the two alternatives below shall be answered; otal plastic parts' weight > 25 g, the postconsumer recycled plastic material content ercentage of total plastic by weight) is %.	(calculated as	i -		

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <u>http://www.ecma-international.org/publications/standards/Ecma-370.htm</u>.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	7D2F, 7D2G, 7D2H	Logo	
Issue date *	Feb. 6, 2020		Lenovo
Product environment	nental attributes - Market requirements (continued)		Requirement met

Requirement metYesNoN/A

			, ,, n			_		
P7.21*		bstance requirements ( material content is used		DTE B7):				
	•	ne of the two alternative		,				
	,	tic parts' weight > 25 g,		,	ted as a percentage of			
	total plastic	by weight) is %.	•	, ,	1 5			
	or b) The weight	of the highered plactic r	actorial in a					
P7.22*	.,	of the biobased plastic n e free from mercury, i.e.	<b>v</b>			$\square$		
1 1.22	0	d specify: Number of lan	, 0 1	im mercury content pe	r lamp: mg			
P7.23*	If product include	es an integral display, the	e total mercury content i	in the integrated displa	ay: mg			$\boxtimes$
P8	Batteries							
P8.1*	Battery chemical composition: Lithium Manganese Dioxide							
P9	Energy consumption (See NOTE B8)							
P9.1		he following power level			1			
Energy mod	de *	Power level at <b>100</b> V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard modes and test meth		hergy	$\bowtie$
Peak (On-r	nax)	W	W		Full load	Ju		
Category								
EPS No-loa	ad ower supply /	W	W	W				
	gged in the wall							
	isconnected from							
the product	.)							
PTEC *		W	W	W				$\boxtimes$
	ergy Consumption							
ETEC *	and Consumption	kWh/year	kWh/year	kWh/year				$\boxtimes$
	ergy Consumption	ency Level (International	Efficiency Marking Prot	tocol) * ·				
Display res		negapixels						
1 2	e to enter energy	<b>8</b> ·	29					
P9.2*	0,	t the energy save function		product		$\square$		<u> </u>
P9.3		class (monitors only):						
P10	Emissions							
FIU		- Declared according to	ISO 9296 (See NOTE	B9)				
P10.1	Mode	Mode description	<b>,</b>	Statistical upper limit	t A-weighted sound pov	ver leve	I, <i>Lw</i> A,c	(B)
	Idle	* Idle		* 5.5				
	Operation	* Operating		* 6.3				
	Other mode         Declared A-weighted sound pressure level (dB) $L_{pAm}$ (operator position desktop – idle)							
	Other mode Declared A-weighted sound pressure level (dB) $L_{pAm}$ (operator position desktop – operating)							
	Measured accord	ding to: 🔀 ISO 7779 🗌	ECMA-74					
		Other	(only if not covered by	ECMA-74)				
	Electromagneti							
P10.4	Computer displa program(s):	y meets the requirement	for low frequency elect	romagnetic fields of th	e following voluntary			

Item

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available;

see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Model nu	mber *	7D2F, 7D2G, 7D	2H			Logo			
Issue date *		Feb. 6, 2020					Leno	VO	н
Product	environr	nental attribute	es - Market requirement	ts (continued)			Require	ment	met
Item							Yes	No	N/A
P12		mics for computi	01						
P12.1*	The disp	lay meets the erg	onomic requirements of ISC	D 9241-307 for visual d	isplay technolo	gies.			$\boxtimes$
P12.2*	The phy	sical input device	meets the requirements of I	ISO 9995 and ISO 924	1-410.				$\boxtimes$
P13	Packaging and documentation								
P13.1*	Product	packaging materia	al type(s): <i>Corrugated boa</i> al type(s): <i>EPE</i> we al type(s): <i>Plastic LDPE</i> we	eight (kg): 1.114	756				
P13.2*			ckaging is free from PVC.				$\square$		
P13.3*		duct primary corru er recovered fiber	igated fiberboard packagin content: 35 %	ng, specify the contain	ed percentage	of minimum p	post-	_	
P13.4*		media for user and ronic, 🔀 Paper, 🚺	d product documentation (tig Other	ck box):					
P13.5	Úser and		item if paper documentation tration on paper media is c						
		hlorine-free al chlorine-free							
	Process	ed chlorine-free					H		
P14	Volunta	ry programs							
P14.1	The proc	Juct meets the rec	uirements of the following	voluntary program(s):					
	ENERG` Eco-labe Eco-labe		Criteria version: Criteria version: Criteria version:	Date: Date: Date:	Product Product Product	0,			
P15	Addition	nal information (S	See NOTE B10)						
P9			computer products; desc						
	the info supplie informa	rmation containe r's knowledge av tion. The informa	o representations, guara d in this document. All in ailable at the time of com tion provided here is app for more information.	formation provided b pletion, and supplier	y supplier in t shall have no	his document obligation to t	is provided l update such	based	lon
P9	See Ene	ergy Star Qualifie	d Enterprise Servers for t gov/products/data_center						

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

## Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive)* * Specific exemptions apply for certain products and applications.	P1.1, P3.1
Regulation (EC) 1907/2006 (REACH Regulation), annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2006/66/EC (Battery and accumulators Directive), as amended.* * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2014/35/EU (Low Voltage Directive)	P3.1
Directive 2014/30/EU (EMC Directive)	P3.1
Directive 2014/53/EU (RE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies	P3.1, P3.2, P9.1
COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers	P2.4, P2.5, P3.1, P3.2, P7.23, P9.1
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1
Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.	
Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State.	

# Lenovo ErP Lot9 Information Sheet - Servers & Storage Products-

As required by COMMISSION REGULATION (EU) 2019/424 of 15 March 2019 laying down ecodesign requirements for servers and data storage products pursuant to Directive 2009/125/EC of the European Parliament and of the Council and amending Commission Regulation (EU) No 617/2013. (ErP Lot9)

#### Products scope of this sheet: Servers & storage products

This document is only valid in connection with the IT Eco Declaration of the specific Product.

#### SERVERS

### General information

Commercial name (3.1 (b) )	Lenovo ThinkSystem SR850P	Logo	
Contact Address (3.1 (b))	7001 Development Dr. Building 7		
	Morrisville, NC 27560		
	United States		Lenovo
Model Number (3.1 (c))	7D2F, 7D2G, 7D2H		
Issue Date	Feb. 6, 2020		
Additional information			

Product e	environmental attributes (EU) 2019/424 – Annex II points 3.1 and 3.3
1.a	Is the product consider to be in scope of ErP Lot 9 🛛 🔀 in scope 🗌 out of scope, product is out of scope as:
1.b	Server type 🛛 🔀 Rack Server 🔄 High Performance Computing (HPC)
(3.1 (a))	Tower Server Multi Node Server
	Blade Server Data Storage product (Please go to "DATA STORAGE PRODUCTS" section
1.c (3.1 (d))	Year of manufacture: 2020
1.d	Product model part of a server product family?
(3.1 (p))	List of all model configurations that are represented by the model:
	https://lenovopress.com/lp1237-lenovo-thinksystem-sr850p-server
1.e (3.1 (n))	Information on the secure data deletion functionality
(3.1 (1))	(a) instructions on how to use the functionality:
	2 methods are provided to use the functionality.
	1) Use a command line tool to do the secure data deletion on the remote target system via boot up a customized
	Linux OS on it. Eg: OneCli.exe serase -bmc USERID:PASSWORD@xx.xx.xx.xxsftp root:password@xx.xxx.xx.xx:/home -log 5
	2) Use BoMC to create a full functions bootable media, start the media and choose secure erase from the text menu.
	(b) techniques used:
	OS tools under Linux -> Standard Linux Open Source tool
	(c) supported secure data deletion standard (if any): Secure Erase/block Erase/Crypto Erase, Sanitize
	<b>OR -</b> Reference to other information: Hdparm: <u>https://en.wikipedia.org/wiki/Hdparm</u>
	Nvme-format: https://www.mankier.com/1/nvme-format
	sg_sanitize: https://www.systutorials.com/docs/linux/man/8-sg_sanitize/
	scrub: https://www.systutorials.com/docs/linux/man/1-scrub/
	storcli: https://docs.broadcom.com/docs-and-downloads/raid-controllers/raid-controllers-common-iles/StorCLI_RefMan_revf.pdf
1.f	Blade servers? 🛛 🖾 No 🔄 Yes
(3.1 (o))	list of recommended combinations with compatible chassis:
Recycling	
2.a (3.3 (a))	Indicative weight range at component level, of the following critical raw materials:
( (-//	
	between 5 g and 25 g
0.5	above 25 g
2.b (3.3 (b))	Instructions on the disassembly operations (a) the type of operation;
	(b) the type and number of fastening technique(s) to be unlocked;
	(c) the tool(s) required.
	OR - Reference to other information: https://thinksystem.lenovofiles.com/help/topic/7D2F/SR850P_maintenance_manual.pdf
2.c	Firmware
	Reference to information on last available firmware:
	https://datacentersupport.lenovo.com/cn/en/products/servers/thinksystem/sr850p/7d2f/downloads/driver-list/

## Server family specific information Family 1

Family r	io. / name	🛛 1 - Lenovo Thin	kSystem SR850P	
	umber(s) / Description	Standard or low-en	d performance configuration:	
(3.1 (c) )			Gold 5222 4C 3.8GHz CPUs	
			GB 1Rx8 PC4-2933Y TruDDR4 RDIMM	
			2 32GB SATA 6Gbps Non-Hot Swap S 0GB 10Krpm 12Gb SAS HDDs	SD
		1x ThinkSystem 1G	•	
			ID 930-16i 4GB Flash PCle 12Gb Adap	oter
		2x 750W Platinum F		
		High-end performar		
			Platinum 8280L 28C 2.7GHz CPUs 4GB 2Rx4 PC4-2933Y TruDDR4 RDIMN	As a second s
			2 32GB SATA 6Gbps Non-Hot Swap S	
			tel S4600 Series 960GB 6Gb/s 2.5" SA	
		1x ThinkSystem 1G		
		· · · · · · · · · · · · · · · · · · ·	ID 930-16i 4GB Flash PCle 12Gb Adap	oter
			al Port 10GBase-T Adapter ctX-4 Lx 1x40GbE QSFP+ Adapter	
		2x 2000W Platinum		
Addition	nal information	You can refer to	adsolutions com/80PlusPowerSupplie	sDetail.aspx?id=49&type=1 along with
				Op-server for the PSU efficiency details.
Produc	t environmental attri		- Annex II points 3.1 and 3.3	
F1.a	PSU efficiency at 10	% (if applicable), 20 %	6, 50 % and 100 % of rated output power	
(3.1 (e))	(expressed in % and	I rounded to the first de	ecimal place): 🗌 Multi-output 🛛 🛛 Sing	le-output
	700-014188-1500 (A	rtesvn 750W/		
		% 93.5% 50% 94.8%	6 100% 93.5% Average 93.9%	
	FSF055 (AcBel 750			
	10% <b>91.4%</b> 20	% 93.3% 50% 94.8%	6 100% 93.3% Average 93.8%	
	Lligh and norferman	as configuration(a)		
	High-end performan 700-014265-1500 (A			
	100-01-203-1300 (F			
	10% 92.5% 20	•	6 100% 93.4% Average 94.4%	
	10% 92.5% 20 DPS-2000HB A (De	% <b>94.8%</b> 50% <b>95.3%</b>	6 100% 93.4% Average 94.4%	
	DPS-2000HB A (De	% <b>94.8%</b> 50% <b>95.3%</b>	C C	
	DPS-2000HB A (De	% <mark>94.8%</mark> 50% <mark>95.3%</mark> Ita 2000W)	, i i i i i i i i i i i i i i i i i i i	
F1.b	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 %	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         6 of the rated load leve       %	6 100% 92.6% Average 93.5%	
(3.1 (f))	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de	%         94.8%         50%         95.3%           Ita 2000W)         %         93.4%         50%         94.5%           %         93.4%         50%         94.5%           %         of the rated load leve         %           %         scimal places)         %	<ul> <li>100% 92.6% Average 93.5%</li> <li>I standard or low-end performation: 1.000</li> </ul>	configuration: 1.000
	DPS-2000HB A (De         10%       91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out	%         94.8%         50%         95.3%           Ita 2000W)         %         93.4%         50%         94.5%           %         93.4%         50%         94.5%           %         of the rated load leve         %           %         scimal places)         *	<ul> <li>100% 92.6% Average 93.5%</li> <li>I standard or low-end performa configuration: 1.000 standard or low-end performa</li> </ul>	configuration: 1.000 ance high-end performance
(3.1 (f)) F1.c	DPS-2000HB A (De         10%       91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power ou         (in Watts rounded to to)	%         94.8%         50%         95.3%           Ita 2000W)         %         93.4%         50%         94.5%           %         93.4%         50%         94.5%           %         of the rated load leve         %           %         scimal places)         *	<ul> <li>100% 92.6% Average 93.5%</li> <li>I standard or low-end performation: 1.000</li> </ul>	configuration: 1.000
(3.1 (f)) F1.c	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power ou         (in Watts rounded to         internal note:         If a product model is part of a set	%         94.8%         50%         95.3%           Ita 2000W)         %         93.4%         50%         94.5%           %         93.4%         50%         94.5%           %         of the rated load leve         scimal places)         scimal places)           tput         the nearest integer)         scimal places)         scimal places)	6 100% 92.6% Average 93.5% 1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750 in a server	configuration: 1.000 ance high-end performance
(3.1 (f)) F1.c	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power ou         (in Watts rounded to         internal note:         If a product model is part of a set	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       of the rated load leve       %         %       of the rated leve       %         %       of the rated leve       %         %       of the rated leve       %	6 100% 92.6% Average 93.5% 1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750 in a server	configuration: 1.000 ance high-end performance configuration: 2000
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported.         idle state power         (in Watts and rounded)	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       of the rated load leve cimal places)       %         tput       the nearest integer)         rver product family, all PSUs offered with the information specified in (e) are compared by the first decimal place)         ed to the first decimal place	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performation: 1.000 standard or low-end performation configuration: 750</li> <li>standard or low-end performation standard or low-end performation configuration: 131.1</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported.         idle state power         (in Watts and rounded)	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       of the rated load leve cimal places)       %         tput       the nearest integer)         rver product family, all PSUs offered with the information specified in (e) are compared by the first decimal place)         ed to the first decimal place	6 100% 92.6% Average 93.5% I standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750 in a server and (f) standard or low-end performa	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported.         idle state power         (in Watts and rounded)	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %         tput	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa blace) configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE –</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported.         idle state power         (in Watts and rounded)	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performation: 1.000 standard or low-end performation configuration: 750</li> <li>standard or low-end performation standard or low-end performation configuration: 131.1</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported.         idle state power         (in Watts and rounded)	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa blace) configuration: 131.1</li> <li>wwer allowances : NOT APPLICABLE – tandard or low-end performance</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounded List of all component	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput       .       .       %       %         rver product family, all PSUs offered with the information specified in (e) science does not be first decimal places of the first decimal places of th	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa blace) configuration: 131.1</li> <li>wwer allowances : NOT APPLICABLE – tandard or low-end performance onfiguration:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounde List of all componen	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput       .       .       %       %         rver product family, all PSUs offered with the information specified in (e) science does not be first decimal places of the first decimal places of th	100% 92.6% Average 93.5%      standard or low-end performation: 1.000     standard or low-end performation: 750      in a server     ind (f)         standard or low-end performation: 131.1     wer allowances : NOT APPLICABLE –      tandard or low-end performance     onfiguration:     1 Socket (10 × PerfCPU W)	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput       .       .       %       %         rver product family, all PSUs offered with the information specified in (e) science does not be first decimal places of the first decimal places of th	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>standard or low-end performa onfiguration: 131.1</li> <li>standard or low-end performance</li> <li>configuration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         (Yes / No)
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve scimal places)       %       %         tput       .       .       %       %         rver product family, all PSUs offered with the information specified in (e) science does not be first decimal places of the first decimal places of th	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:         <ul> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #: (Yes / No) #:</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li> </ul> </li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>standard or low-end performa blace) configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #: (Yes / No) #: (Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #: (Yes / No) #: (Yes / No) #: (Yes / No) #:</li> <li>(Yes / No) #: (Yes / No) #:</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1 wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration: 1 Socket (10 × PerfCPU W) 2 Socket (7 × PerfCPU W) (Yes / No) #: (Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         none
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1 wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration: 1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #: (Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         none         < 1 Gb/s: No Allowance
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>none</li> <li>&lt; 1 Gb/s: No Allowance</li> <li>= 1 Gb/s: 2,0 W/Active Port</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         none
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1 wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration: 1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #: (Yes / No) #:</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         none         < 1 Gb/s: No Allowance
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>none</li> <li>&lt; 1 Gb/s: No Allowance</li> <li>= 1 Gb/s: 2,0 W/Active Port</li> </ul>	configuration: 1.000         ance       high-end performance         configuration: 2000         ance       high-end performance         configuration: 353.1         Server is 4-Socket Only         high-end performance         configuration:         1 Socket         2 Socket         (Yes / No)         none         < 1 Gb/s: No Allowance
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>in a server allowances : NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:</li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         1 Gb/s and < 10 Gb/s: 4,0 W/Active Port
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i))	DPS-2000HB A (De         10% 91.6%       20         Power factor at 50 %         (rounded to three de         PSU rated power out         (in Watts rounded to         internal note:         If a product model is part of a se         product family shall be reported         idle state power         (in Watts and rounded         List of all component         CPU Performance         Additional PSU         HDD         SDD         Additional memory         Additional buffered DD	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       6 of the rated load leve ecimal places)       %         tput       •       •       •         the nearest integer)       •       •       •         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first decimal places o	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1 were allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li></li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         1 Gb/s and < 10 Gb/s: 4,0 W/Active Port
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (g)) F1.e (3.1 (i)) F1.e (3.1 (	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounde List of all componen CPU Performance Additional PSU HDD SDD Additional memory Additional buffered DDI Additional I/O devices	%       94.8%       50%       95.3%         Ita 2000W)       %       93.4%       50%       94.5%         %       93.4%       50%       94.5%         %       of the rated load leve scimal places)	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performa configuration: 1.000 standard or low-end performa configuration: 750</li> <li>in a server and (f) standard or low-end performa configuration: 131.1</li> <li>wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>(Yes</li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         = 1 Gb/s: 2,0 W/Active Port         > 10 Gb/s and < 20 Gb/s: 20,0 W/Active Port
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (g)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.f (3.1 (j))	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounde List of all componen CPU Performance Additional PSU HDD SDD Additional memory Additional buffered DDI Additional I/O devices	99.4.8%       50%       95.3%         Ita 2000W)       98.5%         % 93.4%       50%       94.5%         % of the rated load leve scimal places)       94.5%         tput       the nearest integer)         rver product family, all PSUs offered with the information specified in (e) and the first decimal points for additional idle points for additional idle points         R channel       Image: Comparison of the first decimal point of	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1</li> <li>wer allowances : NOT APPLICABLE –</li> <li>tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:&lt;</li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         1 Gb/s and < 10 Gb/s: 4,0 W/Active Port
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (g)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.e (3.1 (j)) F1.f (3.1 (j)) F1.g	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounde List of all componen CPU Performance Additional PSU HDD SDD Additional memory Additional buffered DDI Additional I/O devices maximum power (in Watts and rounde operating condition of	99.4.8%       50%       95.3%         Ita 2000W)       98.9%       50%       94.5%         % of the rated load leve scimal places)       94.5%         tput       the nearest integer)         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1 wer allowances: NOT APPLICABLE – tandard or low-end performance onfiguration: 1 Socket (10 × PerfCPU W) 2 Socket (7 × PerfCPU W) 2 Socket (7 × PerfCPU W) (Yes / No) #: (Yes / No</li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         1 Gb/s and < 10 Gb/s: 4,0 W/Active Port
(3.1 (f)) F1.c (3.1 (g)) F1.d (3.1 (h)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.e (3.1 (i)) F1.c (3.1 (g)) F1.c (3.1 (	DPS-2000HB A (De 10% 91.6% 20 Power factor at 50 % (rounded to three de PSU rated power ou (in Watts rounded to internal note: If a product model is part of a se product family shall be reported idle state power (in Watts and rounde List of all componen CPU Performance Additional PSU HDD SDD Additional memory Additional buffered DDI Additional I/O devices	99.4.8%       50%       95.3%         Ita 2000W)       98.9%       50%       94.5%         % of the rated load leve scimal places)       94.5%         tput       the nearest integer)         rver product family, all PSUs offered with the information specified in (e) and the first decimal places of the first	<ul> <li>100% 92.6% Average 93.5%</li> <li>1 standard or low-end performation: 1.000 standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 750</li> <li>in a server and (f) standard or low-end performation: 131.1</li> <li>wer allowances : NOT APPLICABLE –</li> <li>tandard or low-end performance onfiguration:</li> <li>1 Socket (10 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>2 Socket (7 × PerfCPU W)</li> <li>(Yes / No) #:</li> <li>(Yes / No) #:&lt;</li></ul>	configuration: 1.000         ance       high-end performance configuration: 2000         ance       high-end performance configuration: 353.1         Server is 4-Socket Only         high-end performance configuration:         1 Socket         2 Socket         (Yes / No)         1 Gb/s: No Allowance         1 Gb/s and < 10 Gb/s: 4,0 W/Active Port

		Exception comments <ul> <li>One power supplies installed</li> <li>NVMe drives installed</li> <li>PCIe flash storage adapters installed</li> <li>DCPMMs installed</li> </ul>	Exception comments <ul> <li>One power supplies installed</li> <li>NVMe drives installed</li> <li>PCIe flash storage adapters installed</li> <li>DCPMMs installed</li> </ul>
F1.h (3.1 (l))	idle state power at the higher boundary temperature of the declared operating condition class (in Watts)	standard or low-end performance configuration: <b>332.1</b>	high-end performance configuration: <b>554.1</b>
F1.i (3.1 (m))	the active state efficiency and the performance in active state of the server;	standard or low-end performance configuration: <b>13.7</b>	high-end performance configuration: <b>37.4</b>