



### Annex B2 - Product environmental attributes Servers/Data Storage Products

The declaration may be published only when all rows and/or fields marked with \* are filled-in (N/A for not applicable). Additional information regarding each item may be found under P15.

| Brand *                | Lenovo   | Logo |           |
|------------------------|--|------|-----------|
| Company name *         | Lenovo   |      | _         |
| Contact information *  | Lenovo Global Environmental Affairs                  |      | Lenovo    |
| e-mail address         | Alvin L Carter                                       |      | LCI IOVO, |
|                        | alcarter@lenovo.com                                  |      |           |
| Internet site *        | https://www.lenovo.com/us/en/about/sustainability    |      |           |
| Additional information | The latest version of this document can be found at: |      |           |
|                        | http://www.lenovo.com/ecodeclaration                 |      |           |

| The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration. |  |  |  |  |
|--|--|--|--|--|
| Type of product *  | SERVER   |  |  |  |
| Commercial name *  | Lenovo ThinkSystem ST550                           |  |  |  |
| Model number *   | 7X09, 7X10   |  |  |  |
| Issue date *   | 2020-01-31   |  |  |  |
| Intended market *  | Global Europe Asia, Pacific & Japan Americas Other |  |  |  |
| Additional information   |  |  |  |  |

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

#### About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products.

| Model number * |  | 7X09, 7X10   | Logo           | Long        |      |                        |
|----------------|--|--|----------------|-------------|------|------------------------|
| Issue date *   |  | 2020-1-31  |                | Lend        |      | <b>)</b> <sub>TM</sub> |
| Product        | environ  | mental attributes - Legal requirements   |                | Require     | ment | met                    |
| Item           |  |  |                | Yes         | No   | N/A                    |
| P1             | Hazardo  | us substances and preparations   |                |             |      |                        |
| P1.1*          | Products   | do comply with current European RoHS Directive. (See legal reference and NOTE  | B1)            |             |      |                        |
| P1.2*          |  | do not contain Asbestos (see legal reference).   |                | $\boxtimes$ |      |                        |
|                |  | nt: Legal reference has no maximum concentration value.  |                |             |      |                        |
| P1.3*          |  | do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),  |                |             |      |                        |
|                |  | mofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrach  |                |             |      |                        |
|                |  | ethane, methyl bromide (see legal reference). Comment: Legal reference has no m  | aximum         |             |      |                        |
|                |  | ation values.  |                |             |      |                        |
| P1.4*          |  | do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated  | orinated       |             |      |                        |
|                |  | l (PCT) in preparations (see legal reference).   |                |             |      |                        |
| P1.5*          | * Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in t |  |                | ne 🔀        |      |                        |
|                | chain co   | ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).  |                |             |      |                        |
| P1.6*          |  | h direct and prolonged skin contact do not release nickel in concentrations above 0 al reference).   | ,5 μg/cm²/wee  | k 🔀         |      |                        |
|                | Commer   | nt: Max limit in legal reference when tested according to EN1811:2011-5.   |                |             |      |                        |
| P1.7*          |  | Article 33 information about substances in articles is available at (add URL or mail of  | contact):      | $\boxtimes$ |      |                        |
|                | https://w  | ww.lenovo.com/us/en/sustainability-resources   |                |             |      |                        |
| P2             | Batterie   | S  |                |             |      |                        |
| P2.1*          | If the pro   | duct contains a battery or an accumulator, the battery/accumulator is labeled with t   | ne disposal    | $\boxtimes$ |      |                        |
|                | symbol.  | Information on proper disposal is provided in user manual. (See legal reference)   |                |             |      |                        |
| P2.2*          | Batteries  | or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadm  | ium. (See lega | al 🔀        |      |                        |
|                | reference  | e)   |                |             |      |                        |
| P2.3*          | Batteries  | and accumulators are readily removable. (See legal reference)  |                | $\boxtimes$ |      |                        |
| P2.4*          | Docume   | ntation includes the number of cycles the (secondary) battery can withstand. (See le   | gal reference  | )           |      | $\times$               |
| P2.5*          |  | ternal batteries of a notebook computer cannot be "accessed and replaced by a nor<br>e related text is present and legible on the external packaging (see legal reference) | professional   |             |      | $\boxtimes$            |
| P3             |  | nity verification & Eco design (ErP)   |                |             |      |                        |
| гэ             | Comorn   | ity verification & Eco design (EIP)  |                |             |      |                        |

The product is CE-marked to show conformance with applicable legal requirements (see legal reference). The Declaration of Conformity can be requested at: <a href="https://www.lenovo.com/us/en/compliance/eu-doc">https://www.lenovo.com/us/en/compliance/eu-doc</a>

given in item P15 or added to this document,

Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium and

The packaging materials are marked with abbreviations and numbers indicating the nature of the material(s)

The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol

available at: https://www.lenovo.com/us/en/compliance/eco-declaration

The product complies with the Eco design requirements for energy-related products,

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

P3.1\*

P3.2\*

**P5** P5.1\*

P5.2\*

P5.3\*

P6

P6.1\*

(see legal reference). Required information is;

Product packaging

(see legal reference).

Treatment information

used (see legal reference)

hexavalent chromium by weight of these together.

Comment: Legal reference has no maximum concentration values.

Information for recyclers/treatment facilities is available (see legal reference).

| Model number * | 7X09, 7X10 | Logo | Lonovo    |
|----------------|------------|------|-----------|
| Issue date *   | 2020-1-31  |      | LEI IOVO. |

| Product | t environmental attributes - Market requirements (See General NOTE GN below)  |                 |             |          |
|---------|---|-----------------|-------------|----------|
|         |   | Require         | ment        | met      |
| Item    | *=mandatory to fill in. Additional information regarding each item may be found under P14.  | Yes             | No          | N/A      |
| P7      | Design, Disassembly, recycling  |                 |             |          |
| P7.1*   | Parts that have to be treated separately are easily separable   |                 | <u> </u>    | <u> </u> |
| P7.2*   | Plastic materials in covers/housing have no surface coating.  |                 | Щ.          |          |
| P7.3*   | Plastic parts > 100 g consist of one material or of easily separable materials.   |                 | <u> </u>    |          |
| P7.4*   | Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.   |                 | <u> </u>    |          |
| P7.5    | Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.  | $\boxtimes$     |             |          |
| P7.6*   | Labels are easily separable. (This requirement does not apply to safety/regulatory labels).   | $\boxtimes$     |             |          |
|         | Product lifetime  |                 |             |          |
| P7.7*   | Upgrading can be done e.g. with processor, memory, cards or drives  |                 | <u> </u>    |          |
| P7.8*   | Upgrading can be done using commonly available tools  | $\boxtimes$     |             |          |
| P7.9    | Spare parts are available after end of production for: years  |                 |             |          |
| P7.10   | Service is available after end of production for: years   |                 |             |          |
|         | Material and substance requirements   |                 |             |          |
| P7.11*  | Product cover/housing material type (e.g. plastics, metal, aluminum):   |                 |             |          |
| P7.12   | Material type: Steel Material type: PC+ABS Material type:  Insulation materials of external electrical cables are PVC free.   |                 |             |          |
| P7.12   | Insulation materials of external electrical cables are PVC free.  | $\dashv$        |             | ╬        |
| P7.13   |   | <del>-  -</del> |             | -        |
| P7.14   | External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and |                 |             | Ш        |
|         | polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing  |                 |             |          |
|         | more than 25% post-consumer recycled content.   |                 |             |          |
| P7.15   | Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen  | Ш               |             |          |
| D7.40   | as defined in IEC 61249-2-21. (See <sup>5</sup> NOTE B2)  |                 |             |          |
| P7.16   | Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking:  |                 |             |          |
| P7.17   | Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):  |                 |             |          |
|         | TBBPA (additive) , TBBPA (reactive) (See NOTE B3), Other: chemical name: , CAS #:   |                 |             |          |
|         | Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g   |                 |             |          |
|         | according ISO 1043-4:   |                 |             |          |
| P7.18   | Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in  |                 |             |          |
| 1 7.10  | concentrations above 0,1%:  |                 |             |          |
|         | 1. Chemical name: , CAS #: (See NOTE B4)  |                 |             |          |
|         | 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: "   |                 |             |          |
|         |   | _               |             | _        |
|         | Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:   |                 | <u>Ц</u>    | Ц_       |
| P7.19   | In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been  |                 |             |          |
|         | assigned the following Risk phrases; and Hazard statements:   |                 |             |          |
| D7 00*  | The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)   |                 |             |          |
| P7.20*  | Postconsumer recycled plastic material content is used in the product (See Note B6):  | Ш               | $\boxtimes$ |          |
|         | If YES; at least one of the two alternatives below shall be answered;   |                 |             |          |
|         | a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as   |                 |             |          |
|         | a percentage of total plastic by weight) is %.  |                 |             |          |
| 1       | or b) The weight of recycled material is g.   |                 |             |          |
|         | b) The weight of recycled material is g.  |                 |             |          |

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>.

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

| Model number * | 7X09, 7X10 | Logo | Lanava   |
|----------------|------------|------|----------|
| Issue date *   | 2020-1-31  |      | Lei IOVO |

| Product environmental attributes - Market requirements (continued) |     |    | nt met |
|--|-----|----|--------|
| Item   | Yes | No | N/A    |

|             | Material and sub   | stance requirements                              | (continued)                           |   |                           |             |   |             |
|-------------|--|--|---------------------------------------|---|---------------------------|-------------|---|-------------|
| P7.21*      |  | material content is used                         | , ,                                   | OTE B7):  |                           |             |   |             |
|             | If YES; at least one of the two alternatives below shall be answered;  a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %.  or  b) The weight of the biobased plastic material is g. |  |                                       |   |                           |             |   |             |
| P7.22*      |  |  |                                       |   |                           |             |   |             |
| P1.22"      |  | free from mercury, i.e. I specify: Number of lan |                                       | ım mercury content pe                           | r lamp: mg                |             | Ш                                       | $\boxtimes$ |
| P7.23*      |  | s an integral display, the                       | e total mercury content               | in the integrated displa                        | ay: mg                    |             |   | $\square$   |
| P8          | Batteries  |  | <u> </u>                              |   | <u> </u>                  |             |   |             |
| P8.1*       | Battery chemical   | composition:                                     |                                       |   |                           |             |   |             |
| P9          |  | otion (See NOTE B8)                              |                                       |   |                           |             |   |             |
| P9.1        |  | ne following power level                         | s or energy consumptio                | ns are reported:                                |                           |             |   |             |
| Energy mo   | de *   | Power level at                                   | Power level at                        | Power level at                                  | Reference/Standard        | for en      | ergy                                    | $\square$   |
| 0,          |  | <b>100</b> V AC                                  | 115 V AC                              | 230 V AC  | modes and test meth       | od *        |   |             |
| Peak (On-   | max)   | W  | W                                     | W   | Full load                 |             |   |             |
| Categor     | y  |  |                                       |   |                           |             |   |             |
| EPS No-loa  |  | W  | W                                     | W   |                           |             |   |             |
|             | ower supply /  |  |                                       |   |                           |             |   |             |
|             | igged in the wall  |  |                                       |   |                           |             |   |             |
| the product | lisconnected from  |  |                                       |   |                           |             |   |             |
| PTEC *      | )  | W  | W                                     | W   |                           |             |   | $\square$   |
| _           | ergy Consumption   |  |                                       | •••   |                           |             |   |             |
| ETEC *      |  | kWh/year   | kWh/year                              | kWh/year  |                           |             | -                                       | $\boxtimes$ |
|             | ergy Consumption   |  | Efficient Markin Da                   | ( 1\ <del>*</del>                               |                           |             |   |             |
|             |  | ncy Level (International                         | Efficiency Marking Pro                | tocol) ^ :                                      |                           |             |   |             |
| Display res | solution * : n   | negapixels                                       |                                       |   |                           |             |   | $\boxtimes$ |
| Default tim | e to enter energy s  | ave mode: minut                                  | tes                                   |   |                           |             |   | $\boxtimes$ |
| P9.2*       | Information about  | the energy save function                         | on is provided with the p             | oroduct.  |                           | $\boxtimes$ |   |             |
| P9.3        | Energy efficiency  | class (monitors only):                           |                                       |   |                           |             |   | $\boxtimes$ |
| P10         | Emissions  | <ul> <li>Declared according to</li> </ul>        | JSO 9296 (See NOTE                    | RQ)   |                           |             |   |             |
| P10.1       |  | Mode description                                 | 7100 0200 (000 110 12                 |   | t A-weighted sound pov    | ver level   | I WA c                                  | (B)         |
|             | Idle   | * HDD idle                                       |                                       | * 5.3   | tri troigittoù ooutiù por |             | , _,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,, | <u>(=)</u>  |
|             | Operation  | * HDD Operating                                  |                                       | * 5.3   |                           |             |   | ╁           |
|             | Other mode   | Declared A-weighted sound                        | d pressure level (dB) $L_{p{\sf Am}}$ | $L_{pAm}$ 43 (operator position desktop – idle) |                           |             |   |             |
|             | Other mode   | Declared A-weighted sound                        | d pressure level (dB) $L_{pAm}$       | 43 (operator position desktop – operating)      |                           |             |   |             |
|             | Measured accord  | ing to: X ISO 7779                               | ECMA-74                               |   |                           |             |   |             |
|             |  | Other  | (only if not covered by               | ECMA-74)  |                           |             |   |             |
|             | Electromagnetic  | emissions  |                                       |   |                           |             |   |             |
| P10.4       |  | meets the requirement                            | for low frequency elect               | tromagnetic fields of th                        | e following voluntary     |             |   |             |
|             | program(s):  |  |                                       |   |                           |             |   |             |

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

NOTE B9 A Guidance document on Acoustic Noise is available;

see <a href="http://www.ecma-international.org/publications/standards/Ecma-370.htm">http://www.ecma-international.org/publications/standards/Ecma-370.htm</a>

| woder number |   | 7X09, 7X10   |  |  | Logo   |                              | one                  | MO    |             |
|--------------|---|--|--|--|--|------------------------------|----------------------|-------|-------------|
| Issue date * |   | 2020-1-31  |  |  |  | L                            | eno                  | VU    | тм          |
| Product      | environr  | nental attrib  | utes - Market requirem   | nents (continued)  |  | F                            | Require              | ment  | met         |
| Item         |   |  | -  |  |  |                              | Yes                  | No    | N/A         |
| P12          | Ergonoi   | nics for comp  | uting products   |  |  |                              |                      |       |             |
| P12.1*       | The disp  | lay meets the  | ergonomic requirements of  | f ISO 9241-307 for visual  | display technologies.  |                              |                      |       | $\boxtimes$ |
| P12.2*       | The phys  | sical input devi   | ce meets the requirements  | of ISO 9995 and ISO 92   | 241-410.   |                              |                      |       | $\boxtimes$ |
| P13          | Packagi   | ng and docun   | nentation  |  |  |                              |                      |       |             |
| P13.1*       | Product<br>Product  | packaging mat<br>packaging mat                                     |  | weight (kg): 0.07<br>weight (kg): 1.2<br>weight (kg):                  |  |                              |                      |       |             |
| P13.2*       | Product   | plastic primary  | packaging is free from PV  | C.   |  |                              | $\boxtimes$          |       |             |
| P13.3*       |   |  | orrugated fiberboard pack<br>per content: <b>55</b> %  | aging, specify the conta   | ined percentage of mi  | nimum post-                  |                      |       |             |
| P13.4*       |   | nedia for user<br>ronic, <mark>X</mark> Pape                       | and product documentation, Other   | n (tick box):  |  |                              |                      |       |             |
| P13.5        | Ùser and  |  | this item if paper documen<br>mentation on paper media   |  |  |                              |                      |       |             |
|              | Totally c   | hlorine-free   |  |  |  |                              |                      |       |             |
|              | Element   | al chlorine-free   |  |  |  |                              |                      |       |             |
|              | Process   | ed chlorine-free   | )  |  |  |                              |                      |       |             |
| P14          | Volunta   | ry programs  |  |  |  |                              |                      |       |             |
| P14.1        | The prod  | luct meets the   | requirements of the followi  | ing voluntary program(s):  |  |                              |                      |       |             |
|              | Eco-labe  | el:  | Criteria version:<br>Criteria version:<br>Criteria version:  | Date:<br>Date:<br>Date:  | Product catego<br>Product catego<br>Product catego                         | ory:                         |                      |       |             |
| P15          | Addition  | nal information  | n (See NOTE B10)   |  |  |                              |                      |       |             |
| P9           | Energy  | consumption  | of computer products; d  | escription of the tested   | product configuration  | n:                           |                      |       |             |
|              | the info<br>supplier<br>informa<br>Accoun   | rmation conta<br>'s knowledge<br>tion. The infor<br>t Representati | s no representations, guined in this document. A available at the time of comation provided here is the formation. | Il information provided completion, and supplie approximate and provid | by supplier in this do<br>or shall have no obliga<br>ded for informational | cument is pr<br>tion to upda | rovided i<br>te such | based | d on        |
| P9           | See Energy Star Qualified Enterprise Servers for the latest information: https://www.energystar.gov/products/data_center_equipment/enterprise_servers |  |  |  |  |                              |                      |       |             |

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

# Legal references Europe Annex B2

| Reference  | Declaration item                    |
|--|-------------------------------------|
| Directive 2011/65/EU (RoHS Directive)*  * Specific exemptions apply for certain products and applications.   | P1.1, P3.1                          |
| Regulation (EC) 1907/2006 (REACH Regulation), annex XVII   | P1.2, P1.4, P1.6, P1.7              |
| Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)  | P1.3, P5.3                          |
| Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002   | P1.5                                |
| Directive 2006/66/EC (Battery and accumulators Directive), as amended.*  * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.   | P2.1, P2.2, P2,3, P8.1              |
| Directive 2014/35/EU (Low Voltage Directive)   | P3.1                                |
| Directive 2014/30/EU (EMC Directive)   | P3.1                                |
| Directive 2014/53/EU (RE Directive)  | P3.1                                |
| Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions  | P3.1, P3.2                          |
| Commission Regulation (EC) No 278/2009 of 6 April 2009 implementing Directive 2005/32/EC of the European Parliament and of the Council with regard to ecodesign requirements for no-load condition electric power demand and average active efficiency of external power supplies  | P3.1, P3.2, P9.1                    |
| COMMISSION REGULATION (EU) No 617/2013 of 26<br>June 2013 implementing Directive 2009/125/EC of the<br>European Parliament and of the Council with regard to<br>ecodesign requirements for computers and computer<br>servers   | P2.4, P2.5, P3.1, P3.2, P7.23, P9.1 |
| Regulation (EC) No 1272/2008 (CLP Regulation)  | P7.19                               |
| Directive 2004/12/EC (Packaging Directive)   | P5.1                                |
| Decision 97/129/EC (Secondary packaging legislation)   | P5.2                                |
| Directive 2012/19/EU (WEEE directive)  | P6.1                                |
| Implementing Regulation (EU) 2019/290 establishing the format for registration and reporting of producers of electrical and electronic equipment to the register.  |                                     |
| Commission Implementing Regulation 2017/699 establishing a common methodology for the calculation of the weight of electrical and electronic equipment (EEE) placed on the national market in each Member State and a common methodology for the calculation of the quantity of waste electrical and electronic equipment (WEEE) generated by weight in each Member State. |                                     |

# **Lenovo ErP Lot9 Information Sheet**- Servers & Storage Products-

As required by COMMISSION REGULATION (EU) 2019/424 of 15 March 2019 laying down ecodesign requirements for servers and data storage products pursuant to Directive 2009/125/EC of the European Parliament and of the Council and amending Commission Regulation (EU) No 617/2013. (ErP Lot9)

#### Products scope of this sheet: Servers & storage products

This document is only valid in connection with the IT Eco Declaration of the specific Product.

#### **SERVERS**

| informa |
|---------|

| Commercial name (3.1 (b)) | Lenovo ThinkSystem ST550                                       | Logo |        |
|---------------------------|--|------|--------|
| Contact Address (3.1 (b)) | 7001 Development Dr. Building 7, Morrisville, NC 27560, United |      |        |
|                           | States   |      | Lonovo |
| Model Number (3.1 (c) )   | 7X09, 7X10   |      | Lenovo |
| Issue Date                | 2020-01-31   |      |        |
| Additional information    |  |      |        |

| Product 6        | environmental attributes (EU) 2019/424 – Annex II points 3.1 and 3.3  |  |  |  |  |  |  |
|------------------|---|--|--|--|--|--|--|
| 1.a              | Is the product consider to be in scope of ErP Lot 9 in scope out of scope, product is out of scope as:  |  |  |  |  |  |  |
| 1.b<br>(3.1 (a)) | Server type  Rack Server  High Performance Computing (HPC)  Tower Server  Blade Server  Data Storage product (Please go to "DATA STORAGE PRODUCTS" section  |  |  |  |  |  |  |
| 1.c<br>(3.1 (d)) | Year of manufacture: 2017   |  |  |  |  |  |  |
| 1.d<br>(3.1 (p)) | Product model part of a server product family? No Yes List of all model configurations that are represented by the model:  http://psref.lenovo.com/Product/ThinkSystem/ThinkSystem_ST550  |  |  |  |  |  |  |
| 1.e              | Information on the secure data deletion functionality   |  |  |  |  |  |  |
| (3.1 (n))        | <ul> <li>(a) instructions on how to use the functionality: 2 methods are provided to use the functionality. 1) Use a command line tool to do the secure data deletion on the remote target system via boot up a customized Linux OS on it. Eg: OneCli.exe serase -bmc USERID:PASSWORD@xx.xx.xx.xxsftp root:password@xx.xxx.xx.xx:/home -log 5 2) Use BoMC to create a full functions bootable media, start the media and choose secure erase from the text menu.</li> <li>(b) techniques used: OS tools under Linux -&gt; Standard Linux Open Source tool</li> <li>(c) supported secure data deletion standard (if any): Secure Erase/block Erase/Crypto Erase, Sanitize</li> </ul> |  |  |  |  |  |  |
|                  | OR - Reference to other information:  |  |  |  |  |  |  |
|                  | Hdparm: https://en.wikipedia.org/wiki/Hdparm  |  |  |  |  |  |  |
|                  | Nvme-format: https://www.mankier.com/1/nvme-format  |  |  |  |  |  |  |
|                  | sg_sanitize: <a href="https://www.systutorials.com/docs/linux/man/8-sg_sanitize/">https://www.systutorials.com/docs/linux/man/8-sg_sanitize/</a>  |  |  |  |  |  |  |
|                  | scrub: <a href="https://www.systutorials.com/docs/linux/man/1-scrub/">https://www.systutorials.com/docs/linux/man/1-scrub/</a>  |  |  |  |  |  |  |
|                  | $storcli: $$ \underline{https://docs.broadcom.com/docs-and-downloads/raid-controllers/raid-controllers-common-iles/StorCLI\_RefMan\_revf.pdf} $$$   |  |  |  |  |  |  |
| 1.f<br>(3.1 (o)) | Blade servers? No Yes   |  |  |  |  |  |  |
| , , ,            | list of recommended combinations with compatible chassis:   |  |  |  |  |  |  |
| Recycling<br>2.a | Indicative weight range at component level, of the (a) Cobalt in the batteries (b) Neodymium in the HDDs  |  |  |  |  |  |  |
| (3.3 (a))        | following critical raw materials:    A cobalt in the batteries   (b) Neodynium in the FIDDS   |  |  |  |  |  |  |
|                  | between 5 g and 25 g  |  |  |  |  |  |  |
|                  | above 25 q  |  |  |  |  |  |  |
| 2.b              | Instructions on the disassembly operations  |  |  |  |  |  |  |
| (3.3 (b))        | (a) the type of operation;  |  |  |  |  |  |  |
|                  | (b) the type and number of fastening technique(s) to be unlocked;   |  |  |  |  |  |  |
|                  | <ul> <li>(c) the tool(s) required.</li> <li>OR - Reference to other information: <a href="https://thinksystem.lenovofiles.com/help/index.jsp">https://thinksystem.lenovofiles.com/help/index.jsp</a></li> </ul>   |  |  |  |  |  |  |
| 2.c              | Firmware  |  |  |  |  |  |  |
|                  | Reference to information on last available firmware:  |  |  |  |  |  |  |
| A dditi = = -1   | https://datacentersupport.lenovo.com/cn/en/products/servers/thinksystem/st550/downloads/driver-list/  |  |  |  |  |  |  |
|                  |   |  |  |  |  |  |  |

# Server family specific information Family 1

| Family no. / name                                   |   | 1 - 1 CPU populated family  |                                       |   |  |
|---|---|---|---------------------------------------|---|--|
| Model number(s) / Description                       |   | Standard or low-end performance configuration:  |                                       |   |  |
| (3.1 (c))   |   | Processor(Minimum result of core count * frequency in family): Intel Xeon Silver 4109T, Storage:  |                                       |   |  |
|   |   | 1TB HDD * 2, Memory: 16GB(lowest capacity in family) * 3, PSU: 550W * 1   |                                       |   |  |
|   |   | High-end performance configuration:   |                                       |   |  |
|   |   | Processor(Maximum result of core count * frequency in family): Intel Xeon Gold 5220S, Storage: 480GB SSD * 2, Memory: 32GB * 6, PSU: 750W * 2 |                                       |   |  |
|   |   |   |                                       | sPowerSuppliesDetail.aspx?id=49&type=1      |  |
| Additio   | nal information                                     | along with http://psref lenovo.go   | om/Product/ThinkSystem/Think          | System ST550 for the PSU efficiency         |  |
| Additio   | iiai iiiioiiiiatioii                                | details.  | OHI/I TOUCE/THIRKS ystern/THIRK       | System 31330 for the 130 emoleticy          |  |
| Produc  | ct environmental attri                              | <b>butes</b> (EU) 2019/424 – Annex II   | I points 3.1 and 3.3                  |   |  |
| F1.a  |   | % (if applicable), 20 %, 50 % an  |                                       |   |  |
| (3.1 (e))   |   | rounded to the first decimal place  |                                       | e-output                                    |  |
|   | (expressed in 70 and                                | rounded to the mot desimal place  | oo). I maia oatpat S oingi            | o output                                    |  |
|   | Standard or low-end                                 | performance configuration(s):   |                                       |   |  |
|   |   | 93.81% 50% 95.09% 100% s  | 93.99% Average 94.30%                 |   |  |
|   |   |   | -                                     |   |  |
|   | High-end performand                                 |   |                                       |   |  |
|   |   | <b>93.25%</b> 50% <b>94.78%</b> 100% 9  |                                       |   |  |
| F1.b  |   | of the rated load level   | standard or low-end performa          |   |  |
| (3.1 (f))   | (rounded to three de                                | . ,   | configuration: 0.990                  | configuration: 1.000                        |  |
| F1.c<br>(3.1 (g))                                   | PSU rated power out<br>(in Watts rounded to         |   | standard or low-end performation: 550 | nce high-end performance configuration: 750 |  |
| (5.1 (9))   | ,   | the hearest integer)  | comgulation. 950                      | configuration. 750                          |  |
|   | internal note:  If a product model is part of a ser | ver product family, all PSUs offered in a server  |                                       |   |  |
|   |   | ver product family, all PSUs offered in a server with the information specified in (e) and (f)  |                                       |   |  |
| F1.d  | idle state power                                    | d to the first decised alone)   | standard or low-end performan         |   |  |
| (3.1 (h))   |   | ed to the first decimal place)  | configuration: 60.0                   | configuration: 88.1                         |  |
| F1.e<br>(3.1 (i))                                   | List of all component                               | ts for additional idle power allowa   | ances                                 |   |  |
| (0.1 (1))   |   | standard or   | low-end performance                   | high-end performance                        |  |
|   |   | configuration   |                                       | configuration:                              |  |
|   | CPU Performance                                     | X 1 Socke   | et (10 × PerfCPU W)                   | X 1 Socket                                  |  |
|   |   |   | et (7 × PerfCPU W)                    | 2 Socket                                    |  |
| ıts   | Additional PSU                                      | No(Yes / No)  | ,                                     | Yes(Yes / No) #: 1                          |  |
| idle power allowances adjustments<br>during testing | HDD   | <b>Yes</b> (Yes / No)   |                                       | No(Yes / No) #: 0                           |  |
| ustr  | SDD   | No(Yes / No)  | ,                                     | Yes(Yes / No) #: 2                          |  |
| adj<br>Ig   | Additional memory                                   | Yes(Yes / No  |                                       | <b>Yes</b> (Yes / No) #: <b>188GB</b>       |  |
| Ses   | Additional buffered DDF                             | R channel No(Yes / No)  | #: <mark>0</mark>                     | <b>No</b> (Yes / No) #: <b>0</b>            |  |
| anc<br>g te   | Additional I/O devices                              | none  |                                       | none  |  |
| <u>8</u> i.   |   |   | No Allowance                          | < 1 Gb/s: No Allowance                      |  |
| g g   |   | <u>=</u>  | 2,0 W/Active Port                     | = 1 Gb/s: 2,0 W/Active Port                 |  |
| ) We  |   |   |                                       |   |  |
| e<br>D  |   |   | and < 10 Gb/s: 4,0 W/Active Port      | > 1 Gb/s and < 10 Gb/s: 4,0 W/Active Port   |  |
| . <u>च</u>  |   |   | and < 25Gb/s: 15,0 W/Active Port      | ≥ 10 Gb/s and < 25Gb/s: 15,0 W/Active Port  |  |
|   |   |   | and < 50Gb/s: 20,0 W/Active Port      | ≥ 25 Gb/s and < 50Gb/s: 20,0 W/Active Port  |  |
|   |   | ≥ 50 Gb/s   | 26,0 W/Active Port                    | ≥ 50 Gb/s 26,0 W/Active Port                |  |
| F1.f  | maximum power                                       |   | standard or low-end performa          |   |  |
| (3.1 (j))   | ,   | ed to the first decimal place)  | configuration: 125                    | configuration: 241.6                        |  |
| F1.g  | operating condition of                              |   | standard or low-end performan         |   |  |
| (3.1 (k))   | (as defined in Table                                | o or ErP lot 9)   | configuration:                        | configuration:                              |  |
|   |   |   | A1                                    |   |  |
|   |   |   | Evention comments                     | Evention comments                           |  |
|   |   |   | Exception comments                    | Exception comments                          |  |
| F1.h  | idle state nower at th                              | ne higher boundary temperature  | standard or low-end performa          | nce high-end performance                    |  |
| (3.1 (l))   |   | ating condition class (in Watts)  | configuration: 81                     | configuration: 107                          |  |
| F1.i  |   | ency and the performance in   | standard or low-end performal         |   |  |
| (3.1 (m))   | active state of the se                              |   | configuration: 17.9                   | configuration: 31.1                         |  |

# Server family specific information Family 2

| Family no. / name  |   | 2 - 2 CPUs populated family  |                   |  |   |  |  |
|--|---|--|-------------------|--|---|--|--|
| Model number(s) / Description  |   | Standard or low-end performance configuration:   |                   |  |   |  |  |
| (3.1 (c))  |   |  |                   |  | mily): Intel Xeon Bronze 3104, Storage:       |  |  |
|  |   | 1TB HDD * 2, Memory: 16GB(lowest capacity in family) * 6, PSU: 550W  |                   |  |   |  |  |
|  |   | High-end performance configuration:  |                   |  |   |  |  |
|  |   | Processor(Maximum result of core count * frequency in family): Intel Xeon Gold 5220S, Storage: 480GB SSD * 2, Memory: 32GB * 12, PSU: 750W * 2 |                   |  |   |  |  |
|  |   | You can refer to h   | ttps://www.i      | plugloadsolutions.com/80Plus           | sPowerSuppliesDetail.aspx?id=49&type=1        |  |  |
| Addition   | nal information   |  |                   |  | System ST550 for the PSU efficiency           |  |  |
|  |   | details.   |                   |  |   |  |  |
|  | t environmental attri   | <b>butes</b> (EU) 2019/4   | 24 – Annex I      | I points 3.1 and 3.3                   |   |  |  |
| F2.a<br>(3.1 (e))  | See family 1  |  |                   |  |   |  |  |
| (3.1 (e))  | Of specific to this family.   |  |                   |  |   |  |  |
|  | PSU efficiency at 10 % (if applicable), 20 %, 50 % and 100 % of rated output power (expressed in % and rounded to the first decimal place) : Multi-output Single-output |  |                   |  |   |  |  |
|  | expressed in % and standard or low-end  |  |                   | ce):                                   | le-output                                     |  |  |
|  | 10% 20%   | 50%  | 100%              | Average                                |   |  |  |
|  | high-end performance  |  |                   |  |   |  |  |
|  | 10% 20%   | 50%  | 100%              | Average                                |   |  |  |
| F2.b   | Power factor at 50 %  |  | evel              | See family 1                           |   |  |  |
| (3.1 (f))  | (rounded to three de  | cimal places)  |                   | Or specific to this family:            |   |  |  |
|  |   |  |                   | standard or low-end performan          |   |  |  |
| F2.c   | DCI I reted newer our   | lmt  |                   | configuration:                         | configuration:                                |  |  |
| (3.1 (g))  | PSU rated power ou<br>(in Watts rounded to  |  | .)                | See family 1                           |   |  |  |
| ( (0))   | (iii vvalto rounaca to  | the nearest integer  | ,                 | Or specific to this family:            |   |  |  |
|  | internal note:  |  |                   | standard or low-end performa           | nce high-end performance                      |  |  |
|  | If a product model is part of a ser<br>product family shall be reported v   | vith the information specified in  | (e) and (f)       | configuration:                         | configuration:                                |  |  |
| F2.d   | idle state power  |  |                   | standard or low-end performan          |   |  |  |
| (3.1 (h))  | (in Watts and rounde  |  |                   | configuration: 73.1                    | configuration: 124.8                          |  |  |
| F2.e<br>(3.1 (i))  | List of all componen  | is for additional idle   |                   | r low-end performance                  | high-end performance                          |  |  |
| ( (-//   |   |  | configuration     |  | configuration:                                |  |  |
|  | CPU Performance   |  |                   | et (10 × PerfCPU W)                    | 1 Socket                                      |  |  |
|  |   |  |                   | et (7 × PerfCPU W)                     | 2 Socket                                      |  |  |
| nts  | Additional PSU  |  | No(Yes / No)      | ,                                      | Yes(Yes / No) #: 1                            |  |  |
| me   | HDD   |  | Yes(Yes / No      |  | <b>No</b> (Yes / No) #: <b>0</b>              |  |  |
| just   | SDD   |  | No(Yes / No) #: 0 |  | <b>Yes</b> (Yes / No) #: 2                    |  |  |
| s ac<br>ing  | Additional memory   |  | Yes(Yes / No      |  | <b>Yes</b> (Yes / No) #: <b>380</b>           |  |  |
| power allowances adjustments<br>during testing   | Additional buffered DDF   | R channel  | Yes (Yes / No     | ) #: <b>4</b>                          | <b>Yes</b> (Yes / No) #: <b>4</b>             |  |  |
| wai  | Additional I/O devices  |  | none              |  | none  |  |  |
| allo   |   |  |                   | No Allowance                           | < 1 Gb/s: No Allowance                        |  |  |
| wer  |   |  | = 1 Gb/s:         | 2,0 W/Active Port                      | = 1 Gb/s: 2,0 W/Active Port                   |  |  |
|  |   |  |                   | and < 10 Gb/s: 4,0 W/Active Port       | > 1 Gb/s and < 10 Gb/s: 4,0 W/Active Port     |  |  |
| idle   |   |  | ≥ 10 Gb/s         | and < 25Gb/s: 15,0 W/Active Port       | ≥ 10 Gb/s and < 25Gb/s: 15,0 W/Active Port    |  |  |
|  |   |  | ≥ 25 Gb/s         | and < 50Gb/s: 20,0 W/Active Port       | ≥ 25 Gb/s and < 50Gb/s: 20,0 W/Active Port    |  |  |
|  |   |  | ≥ 50 Gb/s         | 26,0 W/Active Port                     | ≥ 50 Gb/s 26,0 W/Active Port                  |  |  |
| F2.f   | Maximum power   |  |                   | standard or low-end performan          | •   |  |  |
| (3.1 (j))  | (in Watts and rounde  |  | al place)         | configuration: 167.4                   | configuration: 421.7                          |  |  |
| (3.1 (k)) Operating condition class  See family 1  (as defined in Table 6 or ErP lot 9)  Or specific to this family: |   |  |                   |  |   |  |  |
| , or specific to this farmly.  |   |  |                   | nce high-end performance               |   |  |  |
|  |   |  |                   | configuration:                         | configuration:                                |  |  |
|  |   |  |                   | A1                                     | A1  |  |  |
|  |   |  |                   | A2                                     | A2  |  |  |
|  |   |  |                   | A3                                     | A3  |  |  |
|  |   |  |                   | ☐ A4                                   | ☐ A4  |  |  |
|  |   |  |                   | Exception comments                     | Exception comments                            |  |  |
|  |   |  |                   |  |   |  |  |
| F2.h   | idle state power at th  |  |                   | See family 1                           |   |  |  |
| (3.1 (I))  | of the declared opera<br>(in Watts)   | ating condition class  | S                 | Or specific to this family:            |   |  |  |
|  | (III vvalls)  |  |                   | atandard or law and parforma           | nee high and parformance                      |  |  |
|  |   |  |                   | standard or low-end performation: 91.1 | nce high-end performance configuration: 144.2 |  |  |
| F2.i   | the active state effici   | ency and the perfor  | mance in          | See family 1                           | comgaration. 17712                            |  |  |
| (3.1 (m))  |   |  |                   |  |   |  |  |
|  |   |  |                   |  |   |  |  |
|  |   |  |                   | standard or low-end performan          |   |  |  |
|  |   |  |                   | configuration: 13.1                    | configuration: <b>36.1</b>                    |  |  |