

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo		
Company name *	Lenovo			
Contact information *				
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html			
Additional information				

The company declares (based on product specification or test results b	based obtained from sample testing), that the product
conforms to the statements given in this declaration.	

Type of product *	Traditional Desktop
Commercial name *	Lenovo H515
Model number *	10125; 90A4
Issue date *	2014-06-03
Intended market *	🔀 Global 📃 Europe 🗌 Asia, Pacific & Japan 🗌 Americas 🗌 Other
Additional information	Energy Star Qualified (Model 10125; 90A4)

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number * Lenovo H515 MT: 10125; 90A4								
Issue dat	e *	2014-06-03 Logo	lena	JVC) .			
Duralizat			.					
Item	environ	mental attributes - Legal requirements	Require Yes					
P1	Hazardo	ous substances and preparations	res	No	n.a.			
P1.1*		s do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent						
	chromiu	m, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See erence and Note B1)						
P1.2*	Products	s do not contain Asbestos (see legal reference).	\boxtimes					
P1.3*		nt: Legal reference has no maximum concentration value. s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\square					
11.5	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.							
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /I (PCT) in preparations (see legal reference).	\boxtimes					
P1.5*	5* Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).							
P1.6*	Textile a Tris-(azi	Ind leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Int: Legal reference has no maximum concentration values.			\square			
P1.7*	Textile a	ind leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split ; amines. (See legal reference and Note B1)			\square			
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as lorophenol and derivatives (see legal reference).						
P1.9*	Parts wi microgra	nt: Legal reference has no maximum concentration values. th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm ² /week (see legal reference). nt: Max limit in legal reference when tested according to EN1811:1998.	\boxtimes					
P1.10*	Comme							
1 1.10		Article 33 information about substances in articles is available at (add URL or mail contact): www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment	\bowtie					
P2	Batterie	S						
P2.1*	more tha marked	oduct contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains an 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is I in user manual. (See legal reference)						
P2.2*	Button c	ells used in the product do not contain more than 2% by weight of mercury. Other batteries or lators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes					
P2.3*	Batteries design c	s and accumulators are easily removable by either users or service providers (as dependent on the of the product). Exception: Batteries that are permanently installed for safety, performance, medica ntegrity reasons do not have to be "easily removable". (See legal reference)						
P3		EMC connection to the telephone network and labeling						
P3.1*		duct complies with legally required safety standards as specified (see legal reference).						
P3.2*	-	duct complies with legally required standards for electromagnetic compatibility (see legal						
P3.3*	If produc	c). It is intended for connection to a public telecom network or contains a radio transmitter, it complies ally required standards for radio and telecommunication devices (see legal reference).						
P3.4*		duct is labeled to show conformance with applicable legal requirements (see legal reference).	\square					
P4	Consun	nable materials						
P4.1*	If a phot	o conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see erence and Note B1).						
P4.2*		her is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes			
P4.3*	product/ requiren	(/toner formulation/preparation is classified as hazardous according to applicable regulations, the packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these nents is available (see legal reference).						
P5		t packaging						
P5.1*	hexavale	ng and packaging components do not contain more than 0.01% lead, mercury, cadmium and ent chromium by weight of these together.	d 🔀					
P5.2*		packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes					
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the Montrea (see legal reference). nt: Legal reference has no maximum concentration values.	al 🔀					

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Issue da	ate *	2014-06-03 Logo	lenc	DVC).
roduc tem		mental attributes - Market requirements - Environmental conscious design atory to fill in. Additional information regarding each item may be found under P14.	Require Yes	No	
26		ent information	res	INO	n.a
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).	\square		
77	Design				
	•	mbly, recycling			
P7.1*	Parts the	at have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic r	naterials in covers/housing have no surface coating.		\boxtimes	
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.	\boxtimes		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.	\boxtimes		
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools			
P7.6*	Labels a	re easily separable. (This requirement does not apply to safety/regulatory labels).			
	Product	lifetime			
P7.7*	Upgradi	ng can be done e.g. with processor, memory, cards or drives	\boxtimes		
² 7.8*	Upgradi	ng can be done using commonly available tools	\square		
P7.9.	Spare p	arts are available after end of production for: 5 years			
P7.10		is available after end of production for: 5 years			
		and substance requirements			
⁹ 7.11*		cover/housing material type:			
		type: >PC+ABS-FR(40)< Material type: Material type:			
97.12		al cable insulation materials of power cables are PVC free.		\square	
7.13		al cable insulation materials of signal cables are PVC free		\boxtimes	
P7.14	All cove	/housing plastic parts >25g are free from chlorine and bromine.	\square		
P7.15	All printe Note B2	ed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (S)	ee	\square	
P7.16		zerarded plastic parts >25g in covers / housings are marked according ISO 1043-4:			
P7.17		al specifications of flame retardants in printed circuit boards >25g (without components): (additive) , TBBPA (reactive) , Other; chemical name:, CAS #: 26265-08-7			
	Chemica ISO 104	al specifications of flame retardants in printed circuit boards (without components) >25g according 3-4: FR(16)			
P7.18		retarded plastic parts >25g contain the following flame retardant substances/preparations rations above 0.1%:	in 🗌		
	Provide complet 1. Chem 2. Chem	 nt: No legal limits exist, this is a market requirement. a list of all used flame retardants including MSDS for each flame retardant. The list must cont e chemical name, CAS number and supplier. ical name: , CAS #: , Supplier: ical name: , CAS #: , Supplier: ical name: , CAS #: , Supplier: 	ain		
	Alt. 2	<pre>ical name: , CAS #: , Supplier: al specifications of flame retardants in plastic parts >25g according ISO 1043-4:</pre>			C
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)			
P7.20	Of total	plastic parts' weight >25g, recycled material content is 5%.			
P7.21		plastic parts' weight >25g, biobased material content is 0%.			
7.22	<u> </u>	urces are free from mercury			
8	Batterie	s chemical composition: Lithium manganese dioxide coin battery			
°8.1*					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	Lenovo	o H515	MT: 101	25; 90A4		
	2014-06-03			- ,	Logo lenovo	
Product environm	ental attrib	utes - Market I	requirements	(continued)	Requirement	met
Item			equiremento	(continued)	Yes No	n.a.
•••	onsumption					
9.1 For the pr The produ	oduct the foll uct is shipped	lowing power leve d w/ WOL Enable	els or energy con: d.	sumptions are rep	ported: See P14	
Energy mode *	-	ower level at I 00 V AC	Power level a 115 V AC	at Power level 230 V AC	at Reference / Standard for energy modes and test method *	
	W	(50Hz/60Hz)	W	W		
Category 0						
Short Idle State - WO	OL Enabled	W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Long Idle State - WC		W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Sleep (S3) - WOL En	abled	W	W	W	Use for ENERGY STAR V6 registration(P _{sleep})	
Sleep (S3) - WOL Dis	sabled	W	W	W	Reference	
Off (S5) - WOL Enab	led	W	W	W	Use for ENERGY STAR V6 registration(Poff)	
Off (S5) - WOL Disal	bled	W	W	W	Use for EuP	
Category I1		•		•		•
Short Idle State - WO	OL Enabled	15.80 W	15.57 W	16.97 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WC	OL Enabled	15.48 W	15.12 W	16.34 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL En	abled	2.11 W	2.10 W	2.20 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Dis	sabled	2.11 W	2.10 W	2.20 W	Reference	
Off (S5) - WOL Enab	led	1.32 W	1.32 W	1.39 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disal	bled	0.33 W	0.33 W	0.33 W	Use for EuP	
Category I2						
Short Idle State - WO	OL Enabled	W	W	W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WC	OL Enabled	W	W	W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL En	abled	W	W	W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Di	sabled	w	W	W	Reference	F
Off (S5) - WOL Enab		w	W	W	Use for Energy Star V6.0 registration (Port)	H
Off (S5) - WOL Disal	bled	W	W	W	Use for EuP	
Category I3						
Short Idle State - WO	OL Enabled	15.88 W	15.83 W	16.97 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WC	DL Enabled	15.43 W	15.28 W	16.34 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL En		1.93 W	1.93 W	1.98 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL Dis		1.93 W	1.93 W	1.98 W	Reference	H
Off (S5) - WOL Enab		0.97 W	0.97 W	1.05 W	Use for Energy Star V6.0 registration (P _{off})	H
Off (S5) - WOL Disal		0.33 W	0.33 W	0.33 W	Use for EuP	╞
Category D1 Short Idle State - W0	OL Enabled	23.25 W	22.89 W	23.56 W	Use for Energy Star V6.0 registration(PshortIdle)	
Long Idle State - WC		22.98 W	22.03 W	23.31 W	Use for Energy Star V6.0 registration(P _{LongIdle})	
Sleep (S3) - WOL En		1.58 W	1.59 W	23.31 W	Use for Energy Star V6.0 registration(P _{Longidle})	
Sleep (S3) - WOL En		1.58 W	1.59 W	1.67 W	Reference	
Off (S5) - WOL Enab		1.38 W	1.39 W	1.57 W	Use for Energy Star V6.0 registration (Port)	H
Off (S5) - WOL Enab		0.33 W	0.33 W	0.33 W	Use for EuP	븜
	neu	0.00 VV	0.33 W	0.00 VV	USE IVI EUF	
Category D2	OL Enaklad	14/	147	147	Hop for Enormy Oton VC 0 registeration (D	
Short Idle State - Wo		W	W	W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - WC		W	W	W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL En		W	W	W	Use for Energy Star V6.0 registration (P _{sleep})	ЦЦ
Sleep (S3) - WOL Di		W	W	W	Reference	
Off (S5) - WOL Enab		W	W	W	Use for Energy Star V6.0 registration (Port)	Ц
Off (S5) - WOL Disal	bled	W	W	W	Use for EuP	

EPS No-lo	ad	W	W	W		\triangleleft
	oower supply / charge					
	the wall outlet but					
	ted from the product.)					
0.000						
TEC		kWh/week	kWh/week	kWh/week		\triangleleft
	ergy Consumption					
. ,p.ou	iergy concumption					
ETEC *		Cat I1: 74.91 ;	Cat I1: 73.73;	Cat 11:79.94;	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45 + P_{sleep} \times)$	
Annual En	ergy Consumption	Cat 13: 73.63;	Cat 13: 73.28;	Cat 13:78.51;	0.05 + P _{ShortIdle} x 0.35 + P _{LongIdle} x 0.15)	
		CatD1:107.22;	CatD1:105.86;	CatD1:109.67;		
		kWh/year	kWh/year	kWh/year		
		P Off Mode/S5	- WOL Enabled:	P . · · Sleen Mode/9	S3) - WOL Enabled; P _{idle} : Idle State - WOL Enabled	
			- WOL LINDICU,	sleep. Orcep mode(c		
Display res	solution : Megapixel	e				_
Display rea	solution . Megapixer	3				
Print Spee	ed :	Images per minute	e			
Default tim	ne to enter energy sav	e mode: minutes				
P9.2*						
P9.3*	The product meets	the energy requirem	ents of the follow	ving voluntary prog	gram/s:	
	ENERGY STAR® v	ersion: 6.0 Product	category: 11,13,L	01		
	Others specify: Ene	ergy Star for Extern	al Power Suppl	ies Eligibility Cri	teria Version 2 🛛 🕅	
P10	Emissions					
	Noise emission -	Declared according t	o ISO 9296			
P10.1	Mode	Mode description		Declared	Declared A-weighted	
				A-weighted	sound pressure level L_{pAm} (dB)	
				sound power	1	
				level	Operator position 🔀 Bystander positions	
				L_{WAd} (B)	Desktop 🔀	
					or Desk side (only if product is not	
					operator attended)	
						_
	ldle	* System: Idle		* 3. 4		
	CPU Loading	* Intel PTU tool		* 3. 4	Acoustical Noise Emission Values (a)(b)(c)(d) Product Value	
					Machine Instant of the second se	
	Operating(HDD)				CPU: A6-5200 Idle Oper Idle Oper Idle Oper	
					0014 UDD.17P	
	CD accessing				DT PSU: 120W adapter 3.4 3.4 23 24 21 21	
	° °				VGA: HD8470	
					iLeenia:	
	Measured according	g to: 🔀 ISO7779 🗌	ECMA-74			
	Measured according	g to: 🛛 ISO7779 🗌 Other		vered by ECMA-74	4 with L _{n≜m} measurement distance m)	
P10.2			(only if not cov		, uni	_

Model nur	nber *	Lenovo H515 MT: 10125; 90A4				
Issue date	*	2014-06-03	Logo	Іепо	vo	
	environn	nental attributes - Market requirements (continued)		Require		met
Item				Yes	No	n.a.
		al emissions from printing products				
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard 🔀, other specify:		\square		
P10.4	• •	emission rate (print phase) is (mg/h):				
		Dust Ozone Styrene Benzene TVOC				
P10.5		are met for :				
			TVOC			
P10.6		nagnetic emissions				N 7
P10.6	program	er display meets the requirement for low frequency electromagnetic fields of the foll /s:	owing voluntary			
P11	Consum	able materials for printing products				
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	ired (see P4.3)			\boxtimes
P11.2*	Paper co EN12281	ontaining post-consumer recycled fibers can be used, provided that it meets th 1.	e requirements	s of		\square
P11.3*	2-sided ((duplex) printing/copying is an integrated product function.				\times
P12	Ergonor	nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolo	gies.			X
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.			\square	
P13		ng and documentation				
P13.1*		packaging material type(s): EPE weight (kg): 0. 215				
		packaging material type(s): Carton weight (kg):1.3				
		packaging material type(s): BOX weight (kg): 0.09				
		packaging material type(s): Laminatio Bag weight (kg): 0. 042				
		packaging material type(s): PE film weight (kg): 0. 025				
	Product	packaging material type(s): PAD-Tray cover weight (kg): 0.842				
P13.2*	Product	plastic packaging is free from PVC.				
P13.3*		media for user and product documentation (tick box):				
		ic 🔀, Paper 🔀, Other 🗌				_
P13.4*		er user and product documentation, please specify contained percentage of post-cc (Japan only 70%)	onsumer recycle	ed		
P14		nal information (See Note B4)				
	informati knowledg	Supplier makes no representations, guarantees, assurances or warranties whether on contained in this document. All information provided by supplier in this document ge available at the time of completion, and supplier shall have no obligation to upda here is approximate and provided for informational purposes only. See a Lenovo A ion.	nt is provided b ate such inform	ased on sup ation. The in	plier's format	

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo H515	Logo
Model Number	10125 ; 90A4	_
Issue Date	2014-06-03	lenovo
Additional information		

P7.1.1	Product environmental attri	butes		
(d)	Year of manufacture:			Availible on product label
(e)	E TEC value (kWh) and capa are disabled and if the system display:	N/A		
(f)	E TEC value (kWh) and capa are enabled: Cat. B 71.54 Cat. C 74.48 Cat. D 74.69	bility adjustments applied when a	all discrete graphics cards (dGfx)	
(g)	idle state power demand (Wa	tts);		19.70
(h)	sleep mode power demand (V	Vatts);		1.60
(i)	sleep mode with WOL enable	d power demand (Watts) (where	enabled);	1.60
(j)	off mode power demand (Wa	1.03		
(k)	off mode with WOL enabled p	oower demand (Watts) (where en	abled);	
(I)		cy at 10 %, 20 %, 50 % and 100 50% 100%	% of rated output power (if applicable): N/A
(m)	External power supply efficier	ncy (if applicable):		
		0% 100% Aver	age ;	
(0)	or Level: V The minimum number of load computers):	ing cycles that the batteries can	withstand (applies only to notebook	N/A
(f)	the electricity supply system, used for electrical testing: Test voltage in V and frequen Total harmonic distortion of th	 — information and documentation cy in Hz 230V/50Hz ie electricity supply system ≤ 29 on on the instrumentation, set-up	equency in Hz, — total harmonic dist on on the instrumentation, set-up and and circuits used for electrical testing Make and Model **	circuits
	AC Power Source	1~280VAC;1~550HZ;1000V A.	NF;EC1000S; SN:9152124	
	Digital Watch	Full range	CASIO; HS-70W; SN:208Q08R	

					YOKOGAWA;WT210;SN:91M94456		
		Power	r Meter	0~600V;0~20A	0		
		Hygrothe	rmograph	15~35℃/15~90%	testo; 608-H1,SN:1034895602		
		Thermal a	nemometer	0~20m/s,-20~70 ℃	Testo;425;SN:02591883		
		<u> </u>	easuring	1°;1-300cd/ m²	Konica Minolta;LS-110;		
(p-1)		The measurement methodology used to determine information mentioned in points (I) - internal PSU					
	efficiency:						
(p-2)		The measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:					
(p-3)	The measurement methodology used to determine information mentioned in points (o) - loadingcycles						
	batteries:						
IV/A							
(p-4)	4) The measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:						
IEC 62301							
(q)	(q) Sequence of steps for achieving a stable condition with respect to power demand::						
Power on -> Wait 5 minutes ->Stable condition							
(r) Description of how sleep and/or off mode was selected or programmed:							
Begin menu -> Power -> Select sleep or off mode							
(s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:							
Control Panel->Power Options-> Change Settings-> Restore default settings for this plan							
(1)							
(t)	The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30 minutes						
(u)	I)The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):45 minutes45 minutes						
(v)	The length of time before the display sleep mode is set to activate after user inactivity (in minutes): 15 min						
(w)	w) Information on the energy-saving potential of power management functionality:						
(**)	wy mornation on the energy-saving potential of power management functionality.						
N/A							
(x)	(x) User information on how to enable the power management functionality:						
()							
				Refer to User C	auide		
Additio	on Noteb	ook Batter	y Information:				
Yes	No	n/a	This notebook user.	computer is operated by batt	tery/ies that cannot be accessed and replac	ed by a non-professional	
		\boxtimes	The battery	[ies] in this product ca	annot be easily replaced by users	themselves	
Additional information							