



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Desktop/All-in-One Computers

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo				
Company name *	Lenovo					
Contact information * Lenovo Global Environmental Affairs			Lenovo			
e-mail address	e-mail address Alvin L Carter		LCIIOVO			
	alcarter@lenovo.com					
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information	The latest version of this document can be found at:					
	http://www.lenovo.com/ecodeclaration					

The company declares (based on product specification or test results based obtained from sample testing), that the product						
conforms to the statemen	conforms to the statements given in this declaration.					
Type of product *	All in One					
Commercial name *	ideacentre AIO 520S-23IKU					
Model number *	FOCU					
Issue date *	2016/12/30					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information	Energy Star 6.1; Greenguard					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model number *	FOCU	ideacentre AIO 520S-23IKU
Issue date *	2016/12/30	2016/12/30

Product	environmental attributes - Legal requirements	Require	men	t met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do comply with current European RoHS Directive. (See legal reference and NOTE B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\boxtimes		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week			
	(see legal reference). Comment: Max limit in legal reference when tested according to EN1811:2011-5.			
P1.7*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\boxtimes		
	http://www.lenovo.com/social_responsibility/us/en/environment.html			
P2	Batteries (1) The latest the latest tensor of the l		_	
P2.1*	If the product contains a battery or an accumulator, the battery/accumulator is labeled with the disposal symbol. Information on proper disposal is provided in user manual. (See legal reference)		Ш	Ш
P2.2*	Batteries or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See lega reference)			
P2.3*	Batteries and accumulators are readily removable. (See legal reference)	X		
P3	Conformity verification & Eco design (ErP)			
P3.1*	The product is CE-marked to show conformance with applicable legal requirements (see legal reference).			
	The Declaration of Conformity can be requested at (add link or e-mail address):			
P3.2*	http://www.lenovo.com/social_responsibility/us/en/ec_doc_notebooks/ The product complies with the Eco design requirements for energy-related products,			
F 3.2	(see legal reference).		ш	Ш
	Required information is; given in item P15 or added to this document,	\boxtimes		
	available at (add URL):			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0,01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	The packaging materials are marked with abbreviations and numbers indicating the nature of the material(sused (see legal reference).	s) <u></u>		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea	al 🔀		
	Protocol (see legal reference).			
De	Comment: Legal reference has no maximum concentration values. Treatment information			
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).			
1 0.1	inionnation for recycles/a cathletit lacilities is available (see legal reference).			

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	FOCU	Logo	Lanava
Issue date *	2016/12/30		Lei IOVO"

Produc	t environmental attributes - Market requirements (See General NOTE GN below)			
		Require	ment	met
Item	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P7	Design Disassembly, recycling			
P7.1*	Parts that have to be treated separately are easily separable			
P7.2*	Plastic materials in covers/housing have no surface coating.		X	$\overline{}$
P7.3*	Plastic parts > 100 g consist of one material or of easily separable materials.			\overline{H}
P7.4*	Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4.		Ħ	Ħ
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ħ	Ħ
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).			市
	Product lifetime			
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	\boxtimes		
P7.8*	Upgrading can be done using commonly available tools	\boxtimes		
P7.9	Spare parts are available after end of production for: 5 years			
P7.10	Service is available after end of production for: 5 years			
	Material and substance requirements			
P7.11*	Product cover/housing material type (e.g. plastics, metal, aluminum):			
P7.12	Material type: ABS Material type: Material type: Insulation materials of external electrical cables are PVC free.		\square	
P7.13	Insulation materials of external electrical cables are PVC free.	井	\square	+
P7.14	External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1%			╬
1 7.14	weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and		Ш	Ш
	polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts	i		
P7.15	containing more than 25% post-consumer recycled content. Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low			$\overline{}$
1 7.10	halogen as defined in IEC 61249-2-21. (See 1NOTE B2)			ш
P7.16	Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: >PC+ABS-FR(40)<,>ABS+PET<	\boxtimes		
P7.17	Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components):			
	TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>Epoxy Resin</i> , CAS #: 26265-08-7	\boxtimes		
	79-94-7			
	Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: Brominated Epoxy Resin See P15			
P7.18	Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in			
	concentrations above 0,1%:	\boxtimes		
	1. Chemical name: Bisphenol A Diphosphate , CAS #: 181028-79-5 (See NOTE B4) 2. Chemical name: , CAS #: "			
	3. Chemical name: , CAS #: "			
	Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:>PC+ABS-	\boxtimes		
	FR(40)<			ш
P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been		\boxtimes	
	assigned the following Risk phrases; NA and Hazard statements:			
D7 00*	The source(s) for these classifications is/are found at (add URL(s)): , (See note B5)			
P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):			Ш
	If YES; at least one of the two alternatives below shall be answered;			
	a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as			
	a percentage of total plastic by weight) is %. or			
	b) The weight of recycled material is 61.32 g.			

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model nur	nber *	F0CU	Logo	Len		
Issue date	*	2016/12/30		Len	UVC	J _{TM}
Product	environn	nental attributes - Market requirements (continued)		Requi	remer	t met
Item				Yes	No	n.a.
	Material	and substance requirements (continued)				
D7 04*	Diabass	dulantia mantarial agentaritia considiratha arradost (Can NOTE DZ).				

Product environmental a	ttributes - Market r	equirements (conti	inued)	Requirement met
Item				Yes No n.a.
Material and sub	stance requirements	(continued)		
P7.21* Biobased plastic r	naterial content is use	d in the product (See N	IOTE B7):	
 a) Of total plast 	tic parts' weight > 25 (es below shall be answ g, the biobased plastic %.		culated as a percentage
	f the biobased plastic	material is q.		
P7.22* Light sources are		less than 0,1 mg/lamp	num mercury content p	per lamp: mg
P8 Batteries				
	•	on/Lithium Manganes	se Dioxide	
	otion (See NOTE B8)			
		ls or energy consumpti		Defended for some
Energy mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *
Peak (On-max)	W	W	W	Full load
CategoryI1				
Short Idle State - WOL Enabled	31.31 W	33.3 W	34 W	Use for ENERGY STAR V6 registration (P _{idle})
Long Idle State - WOL Enabled	12.33 W	12.1 W	12.2 W	Use for ENERGY STAR V6 registration (P _{idle})
Sleep (S3) - WOL Enabled	0.83 W	0.7 W	0.7 W	Use for ENERGY STAR V6 registration(P _{sleep})
Sleep (S3) - WOL Disabled	0.74 W	W	W	Reference
Off (S5) - WOL Enabled	0.61 W	0.5 W	0.5 W	Use for ENERGY STAR V6 registration(P _{off})
Off (S5) - WOL Disabled	0.39 W	W	W	Use for ErP
	W	W	W	Reference
Category				
Short Idle State - WOL Enabled	W	W	W	Reference
Long Idle State - WOL Enabled	W	W	W	Reference
Sleep (S3) - WOL Enabled	W	W	W	Reference
Sleep (S3) - WOL Disabled	W	W	W	Reference
Off (S5) - WOL Enabled	W	W	W	Reference
Off (S5) - WOL Disabled	W	W	W	Reference
	W	W	W	Reference
Category				
Short Idle State - WOL Enabled	W	W	W	Reference
Long Idle State - WOL Enabled	W	W	W	Reference

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Sleep (S3)) - WOL Enabled	W	W	W Reference			
Sleep (S3)) - WOL Disabled	W	W	W	Reference		
Off (S5) -	WOL Enabled	W	W	W	Reference		
Off (S5) -	WOL Disabled	W	W	W	Reference		
		W	W	W	Reference		
EPS No-lo		W	W	W			
	supply / charger plugged in the isconnected from the product.)						
PTEC *		W	W	W			
	nergy Consumption						
ETEC * Annual En	nergy Consumption	I1:114.97 kWh/year		11:122.4 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45 + P_{sleep} \times 0.05 + P_{long_ldle} \times 0.15 + P_{short_ldle} \times 0.35)$		
					Enabled; P _{idle} : Idle State - WOL Enabled		
External P	Power Supply Efficien	cy Level (International	Efficiency Marking Pro	otocol) * :			
Display res	solution * : 2.07 meg	apixels					
Default tim	ne to enter energy sa	ve mode: 25 minutes					
P9.2*	Information about t	the energy save function	on is provided with the	product.			
P9.3	Energy efficiency of	class (monitors only):		•			
P10	Emissions						
	Noise emission -	Declared according to	ISO 9296 (See NOTE	B9)			
P10.1	Mode N	Node description		Statistical upper lim	it A-weighted sound power level, $L_{WA,c}$ (B)		
	Idle *	HDD:Idle		* 2.8			
	Operation *	HDD: Operating		* 3.0			
			d pressure level (dB) L_{pAn}				
	Other mode Declared A-weighted sound pressure level (dB) L_{pAm} 21.2 (operator position desktop – operating)						
	Measured according to: ☐ ISO 7779 C☐ ECMA-74 ☐ Other (only if not covered by ECMA-74)						

Model nu	mber *	ideacentre AIO 5	20S-23 <u>IK</u> U				Logo	Long	N/0	
Issue date	e *	2016/12/30						Lenc	JVO,	гм
Product	environn	nental attributes	- Market require	ments (cor	ntinued)			Require	ment	met
Item								Yes	No	n.a.
		nagnetic emission								
P10.4	Compute program		requirement for low	frequency e	lectromagnetic field	ds of the foll	lowing volunta	ıry 🔀		
P12		mics for computin								
P12.1*			nomic requirements of				gies.			
P12.2*	The phys	sical input device m	eets the requirement	ts of ISO 999	95 and ISO 9241-4	10.			\boxtimes	
P13		ng and document								
P13.1*	Product	packaging material packaging material packaging material	type(s): EPE	weight (kg weight (kg weight (kg	g): 1.74					
P13.2*	Product	plastic primary pacl	kaging is free from P	VC.				\boxtimes		
P13.3*		duct primary corruger recovered fiber of	ated fiberboard pac ontent: 100 %	kaging, spec	cify the contained	percentage	of minimum	post-		
P13.4*		media for user and ronic, Paper,	oroduct documentation	on (tick box):						
P13.5	Ùser and		tem if paper docume ation on paper media							
	Totally c	hlorine-free						\bowtie		
	•	al chlorine-free						Ä		
	Processe	ed chlorine-free								
P14	Volunta	ry programs								
P14.1			irements of the follow	ving voluntar	y program(s):					
	ENERG` Eco-labe Eco-labe		Criteria version: 6. Criteria version: Criteria version:	1	Date: 2017/1/4 Date: Date:	Product	category: <i>I1</i> category: category:			
P15		nal information (Se								
P9			pecific configuration							
	informati knowled provided informati	ion contained in this ge available at the t I here is approximat ion.	epresentations, guar document. All inforr ime of completion, a e and provided for in	nation provid nd supplier s iformational p	led by supplier in the shall have no obligate purposes only. See	nis documer ation to upda a Lenovo A	nt is provided interest. In the such information of th	based on supmation. The in	plier's format	ion
P9	See Ene http://ww	rgy Star Qualified N w.energystar.gov/ii	lotebooks & Tablet C ndex.cfm?fuseaction:	Computers fo =find_a_prod	r the latest informa duct.showProductG	tion: Froup&pgw_	_code=CO			
										

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ideacentre AIO 520S-23IKU	Logo	
Model Number	F0CU		Lonovo
Issue Date	2016/12/30		Lenovo.
Additional information	Energy Star 6.1;Greenguard		

(d)	year of manufacture:			Plea	ase see product na			
(e)	Etec value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display.							
(f)	Etec value (kWh) per ErP Lot 3 Categor enable	y and capability adjust	ments applied when a	II discrete graphics o	cards (dGfx) are			
		Category A (according to ErP Lot 3)	Category B (according to ErP Lot 3)	Category C (according to ErP Lot 3)	Category D (according to ErP Lot 3)			
	Memory over base [GB]		16					
ents	Additional internal storage	(Yes / No)	No (Yes / No)	(Yes / No)	(Yes / No)			
capability adjustments applied during testing	Discrete television tuner	(Yes / No)	No (Yes / No)	(Yes / No)	(Yes / No)			
ability a	Discrete Audio Card	(Yes / No)	Yes (Yes / No)	(Yes / No)	(Yes / No)			
cap	Discrete graphics Card(s) [number / #]	#: (Yes / No)	No #: (Yes / No)	#: (Yes / No)	#: (Yes / No)			
	Category of discrete graphics Card(s)							
saults	Etec Value (kWh) - dGfx disabled all discrete graphics cards (dGfx) are disabled/ UMA is active for switchable graphics/ product has no graphics cards (dGfx)		47.86					
Test results	Etec Value (kWh) - dGfx enabled all discrete graphics cards (dGfx) are enabled							
(g)	Idle state power demand (Watts);	-	-	•	12.67			
(h)	Sleep mode power demand (Watts);							
(i)	Sleep mode with WOL enabled power demand (Watts) (where enabled);							
(j)	Off mode power demand (Watts); 0.86 Off mode power demand (Watts);							
(k)	Off mode with WOL enabled power demand (Watts) (where enabled); 0.64							
(I)	Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):							
	10% 20% 50%	100% Avera	ige					
(m)	External power supply efficiency (if applicable)*:							
	Average active efficiency: 90W 88.52%							
(o)	*internal note: show values for all available external power supplies Minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): N/A							
(p-1)	Measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:							
ir '/		N/A						

Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: N/AIEC 62623 Edition 1.0 2012-10 - Desktope and notebook computers - Measurement of energy consumption IEC EN85984.2011 measurement methodology Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on-Wait 5 minutes->Stable condition	p-2)		or Calculating the Energy Efficie	ency of Single-V	points (m) – external PSU efficiency:				
Measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration: NAIEC 62623 Edition 1.0 3912-10 - Desktop and notebook computers - Measurement of energy consumption/ IEC EN50584:2011 measurement methodology Sequence of sleeps for achieving a stable condition with respect to power demand: Based on user manual/Power on-Wait 5 minutes-> Stable condition	p-3)	Measurement method							
power as defined in Point P9.1 in the Product IT Eco Declaration: N/AIEC 62623 Edition 1.0 2012-10 - Desktop and notebook computers - Measurement of energy consumption/ IEC EN5984:2011 measurement methodology 3. Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on->Walt 5 minutes->Stable condition 4. Description of how sleep and/or off mode was selected or programmed: Based on user manual/Begin menu -> Power -> Select sleep or off mode 8. Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan 5. Duration of Idle state condition before the computer automatically reaches sleep mode (in minutes): 6. Duration of Idle state condition before the computer automatically reaches a power mode that has a lower power demand requirement had neget mode (in minutes): 6. Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement had neget mode (in minutes): 6. Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 7. Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 8. Based on user manual 8. Will be used the set of the step of the second of the electrical setting of the electrical setting of power management functionality: 8. Based on user manual 8. Based on user manual 8. Based on user manual 9. Will be used the set voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 8. Based on user manual 9. Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentati	,								
aconsumption / IEC ENSOS64.2011 measurement methodology Sequence of steps for achieving a stable condition with respect to power demand: Based on user manual/Power on->Wait 5 minutes->Stable condition Description of how sleep and/or off mode was selected or programmed: Based on user manual/Begin menu -> Power -> Select sleep or off mode Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan	p-4)								
Based on user manual/Power on->Wait 5 minutes->Stable condition Power									
Based on user manual/Begin menu -> Power -> Select sleep or off mode Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options> Change Settings-> Restore default settings for this plan Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): U Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): V Length of time before the display sleep mode is est to activate after user inactivity (in minutes): 10 Information on the energy-saving potential of power management functionality: Based on user manual X) User information on how to enable the power management functionality: Based on user manual X) User information on how to enable the power management functionality: Based on user manual X) User information on the energy-saving potential of power management functionality: Based on user manual X) User information on how to enable the power management functionality: Based on user manual X) User information on the instrumentation, set-up and circuits used for electrical testing: 230V, 56Hz, Instrument Range Used Make and Model ** Type Or *** AC Power Source 230V;56Hz EXTECH:6810;SN:1450172 Power Meter 0-200V;0-20A YOKOGAWA:WT210;SN:91H427511 Hygrothermograph -20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +2.5°::0.1-1000cd/ m2 Konica Minota;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. " Internal/built-in Battery Battery[ies] in this product cannot be easily replaced by users themselves. " Internal/built-in Battery Battery[ies] in this product cannot be easily replaced by users themselves. " Internal/built-in	(q)	Sequence of steps for achieving a stable condition with respect to power demand:							
Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan		Bas	sed on user manual/Power on->	Wait 5 minutes-	>Stable condition				
Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan	r)	Description of how sle	ep and/or off mode was selected of	or programmed:					
Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode: **Based on user manual/Control Panel->Power Options-> Change Settings-> Restore default settings for this plan 1) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 25 (i) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 25 26 27 28 29 29 29 20 20 20 30 30 30 30 30 30 30	, ,	Based on user manual/Begin menu -> Power -> Select sleep or off mode Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or							
t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): u) Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): v) Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 Information on the energy-saving potential of power management functionality: Based on user manual 2) User information on how to enable the power management functionality: Based on user manual 2) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Instrument Range Used Make and Model ** Type Or *** AC Power Source 230V;50Hz EXTECH;6810;SN:1450172 Power Meter 0-200V;0-20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph — 20 to 50°;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5°;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery	(s)								
t) Duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): U Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): V Length of time before the display sleep mode is set to activate after user inactivity (in minutes): V Length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10 Information on the energy-saving potential of power management functionality: Based on user manual 2) Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz, Instrument Range Used Make and Model ** Type Or *** AC Power Source 230V;50Hz EXTECH;6810;SN:1450172 Power Meter 0-200V;0-20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph -20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5°;0.1-1000cd/m2 Konica Minotia;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. Internal/bullt-in Battery Sios Backup Battery Cher: Other:									
condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):		based on user man			ettings-> Nestore delaun settings				
condition which does not exceed the applicable power demand requirements for sieep mode (in minutes): Length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes): 10	(t)					25			
Length of time before the display sleep mode is set to activate after user inactivity (in minutes): Information on the energy-saving potential of power management functionality: Based on user manual	(u)				. , ,				
Information on the energy-saving potential of power management functionality: Based on user manual		mode that has a lower power demand requirement than sleep mode (in minutes):							
User information on how to enable the power management functionality: Based on user manual						10			
Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz,			Based on us	ser manual					
Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: 230V, 50Hz,	x)	User information on how to enable the power management functionality:							
the electrically supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Comparison			Based on us	ser manual					
the electrically supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Comparison	(-)								
Instrument Range Used Make and Model ** Type Or **** AC Power Source 230V;50Hz EXTECH;6810;SN:1450172 Power Meter 0~200V;0~20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph —20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5° ;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery Information: External/detachable Battery Information: Internal/built-in Battery Information: Internal/bu	(2)	the electricity supply s	ystem, — information and docume						
Type Or *** AC Power Source 230V;50Hz EXTECH;6810;SN:1450172 Power Meter 0~200V;0~20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph -20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5°;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery									
AC Power Source 230V;50Hz EXTECH;6810;SN:1450172 Power Meter 0~200V;0~20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph -20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5°;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery					Make and Model **				
Power Meter 0~200V;0~20A YOKOGAWA;WT210;SN:91H427511 Hygrothermograph -20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5° ;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery External/detachable Battery Diss Backup Battery Other:									
Hygrothermograph —20 to 50°C;20 to 90% SEKONIC;ST-50 Light Measuring +-2.5°;0.1-1000cd/ m2 Konica Minolta;CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery		AC Power Source	230V;50Hz		EXTECH;6810;SN:1450172				
Light Measuring +-2.5°; 0.1-1000cd/ m2 Konica Minolta; CA-210 Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery External/detachable Battery Bios Backup Battery Other:		Power Meter	0~200V;0~20A	YOR	(OGAWA;WT210;SN:91H427511				
Addition Notebook Battery Information: Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery External/detachable Battery Dios Backup Battery	Hygrothermogra		-20 to 50°C;20 to 90%	6	SEKONIC;ST-50				
Battery[ies] not user replaceable The battery[ies] in this product cannot be easily replaced by users themselves. Internal/built-in Battery External/detachable Battery Bios Backup Battery Cher: Battery[ies] user replaceable n/a Battery[ies] user replaceable n/a Battery[ies] user replaceable n/a Cherical District Cannot be easily replaced by users themselves. District Cannot be easily replaceable District Cannot Canno		Light Measuring	+-2.5°;0.1-1000cd/ m	2	Konica Minolta;CA-210				
The battery[ies] in this product cannot be easily replaced by users themselves. 1) Internal/built-in Battery External/detachable Battery Bios Backup Battery Other:	Addition								
Internal/built-in Battery			· · · · · · · · · · · · · · · · · · ·		Battery[ies] user replaceable	n/a			
External/detachable Battery			The battery[ies] in this product cannot be easily replaced by users themselves. 1)						
Bios Backup Battery	Internal/	built-in Battery							
Other:	External	/detachable Battery							
	Bios Backup Battery								
Additional information	Other:								
	Addition	al information	<u> </u>						
)								

The battery[ies] in this product cannot be easily replaced by users themselves.

Акумулаторната[ите] батерия[и] в този продукт не може да се замени[ят] лесно от самите потребители.

Las baterías de este producto no pueden ser sustituidas fácilmente por los propios usuarios.

Výměnu baterie/baterií v tomto výrobku by neměli provádět sami uživatelé.
Brugeren kan ikke uden videre udskífte batteriet/batterierne i dette produkt.
Der Akku/die Akkus dieses Produkts kann/können nicht ohne weiteres vom Benutzer selbst ausgetauscht werden.
Kasutajad ei saa selle toote akut/akusid ise hõlpsasti asendada.

Η μπαταρία[-ες] στο προϊόν αυτό δεν μπορούν να αντικατασταθούν εύκολα από τους ίδιους τους χρήστες

La/les batterie(s présente(s) dans ce produit ne peuvent être facilement remplacée(s) par les utilisateurs eux-mêmes. Korisnik ne može lako zamijeniti Bateriju sam u ovom proizvodu.

La batteria/le batterie in questo prodotto non può/possono essere facilmente sostituita/e dall'utente.

Lietotāji paši nevar nomainīt šā ražojuma akumulatoru(-us). Šio gaminio baterijos [baterijų] pats vartotojas negali lengvai pakeisti. A termék akkumulátorát/akkumulátorait a felhasználó nem tudja egyedül egyszerűen kicserélni.

Il-batterija/batteriji f'dan il-prodott ma tistax/jistgħux tiġi/jiġu sostitiwita/i mill-utenti stess. Batteriet [ene] i dette produktet kan ikke lett erstattes av brukerne selv.

De batterij(en) in dit product is (zijn) door de gebruiker niet gemakkelijk vervangbaar.

Użytkownik nie może sam w łatwy sposób wymienić baterii w tym produkcie. A ou as baterias deste produto não podem ser facilmente substituídas pelos próprios utilizadores.

Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Bateria (bateriile) din acest produs nu poate (pot) fi uşor înlocuită (înlocuite) de utilizatorii înşişi. Baterii/baterije v tem izdelku uporabniki sami ne morejo zlahka zamenjati.

Tämän tuotteen akku [akut] ei[vät] ole helposti käyttäjän vaihdettavissa

Det är inte enkelt för kunden att själv byta ut batteriet/batterierna. Bu üründeki batarya(lar) kullanıcılar tarafından kolaylıkla değiştirilemez.