

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo		
Company name *	Lenovo			
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.		
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	t.html		
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_notebooks.html			

	The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Notebook PC				
Commercial name *	Lenovo N22				
Model number *	<i>80</i> S6				
Issue date *	2016-01-06				
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other				
Additional information					

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).		

Model number *	<i>80</i> S6		
Issue date *	2016-01-06	Logo	lenovo

Product	environmental attributes - Legal requirements	Require	ment	met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/materials.html			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	X		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes	\Box	
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			\boxtimes
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).		\Box	$\overline{\mathbf{X}}$
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	al 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	<i>80</i> S6		
Issue date *	2016-01-06	Logo	lenovo.

*-mandatory to fill in . Additional information regarding each item may be found under P14.	Product	environmental attributes - Market requirements - Environmental conscious design	Require	ment	met
PR.1 Information for recyclers/treatment facilities is available (see legal reference).					
Disasembly, recycling	P6				
P7.1° Parts that have to be treated separately are easily separable P7.2° Plastic materials in covers/housing have no surface coating. P7.3° Plastic parts >250 gas be treated separately are easily separable materials. P7.4° Plastic parts >250 gas be material or of easily separable materials. P7.5° Plastic parts >260 gas be material codes according to ISO 11409 referring ISO 1043. P7.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Spare parts are available after end of production for. 5 years P7.9° Spare parts are available after end of production for. 5 years Material and substance requirements P7.11° Product coverhousing material type: Material upge: PC-ABS-FR(40) Material type: PC-ABS-FR(40) Material type: PC-ABS-FR(40) Material type: PC-ABS-FR(40) Note B2) P7.14 All cover-housing plastic parts >25g are free from chlorine and bromine. Note B2) P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Att 1 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: P7.18 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.18 Alt. 1 Chemical specifications of flame retardants in plastic parts >2	P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes		
P7.1º Parts that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic materials in covers/housing have no surface coating. P7.4º Plastic parts >25g have material cord easily separable materials. P7.5 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.6 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for: 5 years Material and substance requirements P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Material type: P6.4458-FR(40) Material	P7				
P7.3* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Upgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done using commonly available tools P7.9* Spara parts are available after end of production for: 5 years P7.9* Spare parts are available after end of production for: 5 years P7.9* Service is available after end of production for: 5 years P7.10* Product cover/housing material type: Material and substance requirements P7.11* Product clover/housing materials of power cables are PVC free. Material type: PC-4485-FR(40) Material type: PC-4485-FR(40) Material type: PC-4485-FR(40) Material type: PC-4585-FR(40) All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.14 All cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4: Material specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) ☐ TBBPA (reactive) ☑, Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: P7.15 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Chemical name: , CAS #: 5. Chemical name: , CAS #: 6. Chemical name: , CAS #: 7. Chemical na	P7.1*		\boxtimes		
P7.4* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts as refer from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 5 years P7.9* Spare parts are available after end of production for: 5 years Material and substance requirements P7.10* Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material type: PC+ABS-FR(40) Material type: Material type: PC+ABS-FR(40) Material type: Material type: PC+ABS-FR(40) Material type: Material does insulation materials of signal cables are PVC free. P7.13* Electrical cable insulation materials of signal cables are PVC free. P7.14* All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15* All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16* Plame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: PR.10* Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive)	P7.2*	Plastic materials in covers/housing have no surface coating.		$\overline{\boxtimes}$	
P7.4 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material type: Material type: PC+ABS-FR(40) Material type: Material upe: PC+ABS-FR(40) Material type: Material upe: PC-ABS-FR(40) Material type: PC+ABS-FR(40) Material upe: PC-ABS-FR(40) Material upe: P	P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	X	Ħ	Ħ
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	P7.4*			Ħ	Ħ
P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.110 Service is available after end of production for: 5 years P7.110 Service is available after end of production for: 5 years P7.111 Service is available after end of production for: 5 years P7.112 Service is available after end of production for: 5 years P7.113 Electrical cable insulation materials of power cables are PVC free. P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) .TBBPA (reactive) .Other; chemical name: , CAS #: Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical pacefications of flame retardants in plastic parts >25g according ISO 1043-4: P7.18 Alt. 1 Flame retarded plastic parts vest, this is a market requirement. 1. Chemical pacefications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 P1.9 P1.9 P1.9 P1.9 P1.9 P1.9 P1.9 P	P7.5	, c		Ħ	\overline{H}
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives				H	H
P7.8° Upgrading can be done e.g. with processor, memory, cards or drives					
P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material and substance requirements P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards 225g (without components): TBBPA (additive) . TBBPA (reactive) . Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 F1.11 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Chemical specifications of flame retardant substances/ preparations above 0.1% classified as R45, FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, FR(40) P7.20 Of total plastic parts' weight >25g, plobased material content is 6%. Light sources are free from mercury Immercury is used specify: Number of lamps: and max. mercury content per lamp: mg	P7.7*			П	П
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years				\overline{H}	
P7.10 Service is available after end of production for: 5 years Material and substance requirements					\vdash
Material and substance requirements					\dashv
P7.11* Product cover/housing material type: Material type: Material type: PC+ABS-FR(40)	1 7.10	, ,			
Material type: PC+ABS-FR(40) Material type: Material type: P7.12 Electrical cable insulation materials of power cables are PVC free P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.11*				
P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:					
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40)	P7.12	Electrical cable insulation materials of power cables are PVC free.		\boxtimes	
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:	P7.13	Electrical cable insulation materials of signal cables are PVC free		$\overline{\boxtimes}$	
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.		$\overline{\Box}$	Ī
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: FR(40) P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) ☐, TBBPA (reactive) ☒, Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.15		• 🗍		
P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) ☐, TBBPA (reactive) ☒, Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg	P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:			
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components):			
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 6.20%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: <i>Brominated Epoxy Resin See P14</i>			
1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.18	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%:	n 🔲		
3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		· · · · · · · · · · · · · · · · · · ·			
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: FR(40) P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries					
P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.20%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:	\square		
P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45,			
P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.20	Of total plastic parts' weight >25g, recycled material content is 6.20% .			
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries mg	P7.21	Of total plastic parts' weight >25g, biobased material content is %.			
P8 Batteries	P7.22	,	\boxtimes		
	DO				
P8 1* Rattery chamical composition: Lithium Ion/Lithium Manganasa Diovido	P8.1*	Batteries Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide			
P8.2 Batteries meet the requirements of the following voluntary program/s: <i>US RBRC</i>					<u> </u>

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	<i>80</i> S6		
Issue date *	2016-01-06	Logo	lenovo

	environinental a	ittributes - Market red	uli elliellis (colli	illiueu)	Requirement	
Item	_				Yes	No n.a.
P9	Energy consump					
9.1	For the product the	ne following power levels of	or energy consump	tions are reporte	d: See P14	
Energy mo	de *	Power level a 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and t method *	est
Peak (On-	max)	45 W	45 W	45 W	Full load	
Category	v I1		·	J.		·
	State - WOL Enal	bled 6.000 W	5.947 W	5.758 W	Use for ENERGY STAR V6 registration (Pidle	e) 🔀
Long Idle	State - WOL Enal		3.424 W	3.286 W	Use for ENERGY STAR V6 registration (Pidli	
Sleep (S3) - WOL Enabled		0.422 W	0.422 W	0.425 W	Use for ENERGY STAR V6 registration(P _{slee}	(p)
Sleep (S3)	- WOL Disabled	0.422 W	0.422 W	0.425 W	Reference	
Off (S5) - I	NOL Enabled	0.360 W	0.360 W	0.371 W	Use for ENERGY STAR V6 registration(Poff)	
Off (S5) - I	WOL Disabled	0.360 W	0.360 W	0.371 W	Use for EuP	
Category	Category D 1/2					
Short Idle	Short Idle State - WOL Enabled W W Use for ENERGY STAR V6 registration (P _{idle})					a)
Long Idle	State - WOL Enal	oled W	W	W	Use for ENERGY STAR V6 registration (Pidlo 1997)	<u>,)</u>
Sleep (S3)	- WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration (Psle	ер)
	- WOL Disabled	W	W	W	Reference	
	WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(Poff)	
	NOL Disabled	W	W	W	Use for EuP	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)			0.049 W	0.072 W		
PTEC * Typical Energy Consumption		W	W	W		
TEC * Typical End	ergy Consumption	kWh/week	kWh/week	kWh/week		
ETEC * Annual Ene	ergy Consumption	20.76 kWh/year	20.71 kWh/year	20.13 kWh/year	E _{TEC} = (8760/1000) x (P _{off} x 0.25 + P _{sleep} x 0. + P _{short idle} x 0.3+ P _{long idle} x 0.1)	35
		P _{off} : Off Mode(S5)	- WOL Enabled; P _{slee}	p: Sleep Mode(S3)	- WOL Enabled; P _{idle} : Idle State - WOL Enabled	
Display res	solution* : 1920*10	080 Megapixels				
Print Speed	d* : I	mages per minute				
Default tim	e to enter energy s	save mode: 25 minutes				
P9.2*	Information about	the energy save function	is provided with the	e product.		
P9.3*		ts the energy requirement version: <i>Version 6.1</i> To		oluntary program category: <mark>A</mark>	/s: 	
P10	Emissions					
D10.1		Declared according to Is Made description	SO 9296	Doctored	Declared A west-bland	
P10.1	Mode	Mode description		Declared A-weighted	Declared A-weighted sound pressure level $L_{p m Am}$ (dB)	
				sound power	er Sound pressure level $L_{p \text{Am}}$ (dB)	
				level L_{WAd} (B) Operator position Bystander position	ons
					Desktop (only if product is	
	Idle	* HDD:Idle		* NA	operator attend	ea)
	Operation	* HDD: Operating		* NA	NA	$\neg \mid \exists \mid$
	Other mode	-				_ _
	Measured accord		CMA-74			
D40.0	The area don't				L _{pAm} measurement distance m)	
P10.2	P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:					

Model number *	<i>80</i> S6		
Issue date *	2016-01-06	Logo	lenovo

	environinental a	ittributes - Market requ	illements (com	illiueu)		Requirement me	
Item	_					Yes No	n.a.
P9	Energy consump						
9.1	For the product the	ne following power levels or	r energy consumpt	tions are reporte	ed: Se	e P14	
Energy mo	de *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Refe meth	erence / Standard for energy modes and test nod *	
Peak (On-	max)	45 W	45 W	45 W	Ful	ll load	
Category	v I2	<u> </u>			1		1
	State - WOL Enal	bled 6.230 W	6.120 W	6.504 W	Use	for ENERGY STAR V6 registration (P _{idle})	
Long Idle	State - WOL Enak	oled 3.656 W	3.492 W	3.476 W	Use	for ENERGY STAR V6 registration (P _{idle})	
Sleep (S3) - WOL Enabled		0.422 W	0.419 W	0.431 W	Use	for ENERGY STAR V6 registration(P _{sleep})	
Sleep (S3)	- WOL Disabled	0.422 W	0.419 W	0.431 W	Refe	erence	
Off (S5) - I	WOL Enabled	0.378 W	0.378 W	0.382 W	Use	for ENERGY STAR V6 registration(Poff)	
Off (S5) - I	NOL Disabled	0.378 W	0.378 W	0.382 W	Use	for EuP	
Categor	Category D 1/2						
Short Idle	State - WOL Enal	bled W	W	W	Use	for ENERGY STAR V6 registration (Pidle)	
Long Idle	State - WOL Enal	oled W	W	W	Use	for ENERGY STAR V6 registration (P _{idle})	
Sleep (S3)	- WOL Enabled	W	W	W	Use	for ENERGY STAR V6 registration (P _{sleep})	
	- WOL Disabled	W	W	W	Refe	erence	
	NOL Enabled	W	W	W		for ENERGY STAR V6 registration(Poff)	
	NOL Disabled	W	W	W	Use	for EuP	
EPS No-load (External power supply / charger plugged in the wall outlet but disconnected from the product.)			0.049 W	0.072 W			
PTEC * Typical Energy Consumption		W	W	W			
TEC * Typical End	ergy Consumption	kWh/week	kWh/week	kWh/week			
ETEC * Annual Ene	ergy Consumption	21.70 kWh/year	21.25 kWh/year	22.30 kWh/year		c = (8760/1000) x (P _{off} x 0.25 + P _{sleep} x 0.35 thort idle x 0.3+ P _{long idle} x 0.1)	
		P _{off} : Off Mode(S5) -	WOL Enabled; P _{slee}	: Sleep Mode(S3)	- WOL	Enabled; P _{idle} : Idle State - WOL Enabled	
Display res	olution* : 1920*10	080 Megapixels					
Print Speed	d * : I	mages per minute					
Default tim	e to enter energy s	save mode: 25 minutes					
P9.2*	Information about	t the energy save function i	s provided with the	e product.			
P9.3*		ts the energy requirements version: Version 6.1 Tie		oluntary program category: <mark>A</mark>	n/s:		
P10	Emissions	Dealered according 10	0.0000				
P10.1	Mode Mode	 Declared according to IS Mode description 	U 9296	Declared	1	Declared A waighted	
i- 10.1	IVIUUE	wode description		A-weighted		Declared A-weighted sound pressure level $L_{p m Am}$ (dB)	
				sound power			4
				level L_{WAd} ((B) C	Operator position Bystander positions	
						or Desk side (only if product is not	
	Idle	* HDD:Idle		* NA		operator attended) NA	┨┌┐┞
		* HDD: Operating		* NA		NA NA	1 🗂 🛭
	Other mode	<u> </u>]
	Measured accord		CMA-74				
D40.0	The product or					measurement distance m)	
P10.2	P10.2 The product meets the acoustic noise requirements of the following voluntary program/s:						

Model number * 80S6			
Issue date * 2016-01-06 Logo	nove) .	
• • • • • • • • • • • • • • • • • • • •	quirem		
	Yes I	No	n.a.
Chemical emissions from printing products			
P10.3* Test performed according to ECMA-328 (ISO/IEC 28360) standard, other specify:			\boxtimes
P10.4 Typical emission rate (print phase) is (mg/h):			\boxtimes
Dust Ozone Styrene Benzene TVOC			
P10.5 Chemical emission requirements of the following voluntary program/s are met for :			\boxtimes
Dust Ozone Styrene Benzene TVOC			
Electromagnetic emissions			
P10.6 Computer display meets the requirement for low frequency electromagnetic fields of the following voluntary			
program/s: MPR-II			
P11 Consumable materials for printing products P11.1* A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).		_	
	<u>Ц</u> ,	_	
P11.2* Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of EN12281.			
P11.3* 2-sided (duplex) printing/copying is an integrated product function.			\boxtimes
P12 Ergonomics for computing products			
P12.1* The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.			
P12.2* The physical input device meets the requirements of ISO 9995 and ISO 9241-410.			
P13 Packaging and documentation			
P13.1* Product packaging material type(s): Corrugated Carton weight (kg): 0.255 Product packaging material type(s): Polyethylene Cushions weight (kg): 0.038			
Product packaging material type(s): <i>Others</i> weight (kg): <i>0.123</i>			
P13.2* Product plastic packaging is free from PVC.			
P13.3* Specify media for user and product documentation (tick box):			Ħ
Electronic , Paper , Other			_
P13.4* For paper user and product documentation, please specify contained percentage of post-consumer recycled fiber: 0%			
P14 Additional information (See Note B4)			
NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implied, re-	garding	the	
information contained in this document. All information provided by supplier in this document is provided based o	n suppli	er's	
knowledge available at the time of completion, and supplier shall have no obligation to update such information.			ion
provided here is approximate and provided for informational purposes only. See a Lenovo Account Representative	e for mo	re	
information. P9 See Energy Star Qualified Notebooks & Tablet Computers for the latest information:			
http://www.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&pgw_code=CO			
mapin ministral gjoldingo mindokomi maodada om-inia_a_produce om roddotorodpapgii_code=oo			

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo N22	Logo
Model Number	80S6	_
Issue Date	2016-01-06	lenovo.
Additional information		

(d)	year of manufacture:	2014				
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display:					
	Category (according to ErP Lot 3): A Etec: 12.83					
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graphics cards (dGfx) are enabled:					
	Category (according to ErP Lot 3): Etec:					
(g)	idle state power demand (Watts);	3.98				
(h)	sleep mode power demand (Watts);	0.42				
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);					
(j)	off mode power demand (Watts);	0.38				
(k)	off mode with WOL enabled power demand (Watts) (where enabled);					
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):					
	10% 20% 50% 100% Average					
(m)	external power supply efficiency (if applicable):					
	Average 45W:87.58%;88.35%;					
	*internal note: show values for all available external power supplies					
(o)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	300 cycles				
(p-1)	the measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency:					
	NA NA					
(p-2)	the measurement methodology used to determine information mentioned in points (m) – external PSU efficiency:					
	Energy-star requirement					
(p-3)	the measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries:					
	IEC 61960 measurement methodology					

(p-4)	the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:						
		IEC 6262	3 / IEC I	EN50564:2011 measurement methodology			
(q)	sequence of ste	condition with respect to power demand::					
		EC 62623	3 / IEC E	EN50564:2011 measurement methodology			
(r)	description of h	ow sleep and/or of	ff mode	was selected or programmed:			
				Based on user manual			
(s)	sequence of ev off mode:	ents required to re	ach the	mode where the equipment automatically changes to sleep and/or			
				Based on user manual			
(t)	the duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):						
(u)	the length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):						
(v)				o mode is set to activate after user inactivity (in minutes):	10		
(w)				I of power management functionality:			
				Based on user manual			
(x)	user information	n on how to enable	the pov	wer management functionality:			
				Based on user manual			
(z)		upply system, — ir		st voltage in V and frequency in Hz, — total harmonic distortion of on and documentation on the instrumentation, set-up and circuits			
		2:	30V/50H	Iz, Total Harmonic Distortion <2 %			
Addition No	tebook Battery	Information:					
Yes		No	n/a	This notebook computer is operated by battery/ies that cannot replaced by a non-professional user.	be accessed and		
(Battery replaceable	not user	(Battery user replaceable)		The battery[ies] in this product cannot be easily	v replaced by		
	<u> </u>			users themselves	, ., .,		
Additional	nformation	<u> </u>		I			
			•				
1							