

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo				
Company name *	Lenovo					
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com	Lenovo.				
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html					
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_notebooks.html					

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Desktop - SFF			
Commercial name *	Lenovo S510			
Model number *	10KY, 10L0, 10LB, 10LC, 10LF, 10LG			
Issue date *	2016-3-24			
Intended market *	🛛 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 🗌 Other			
Additional information	ENERGY STAR® Qualified; EPEAT GOLD Rating; GREENGUARD Certified			

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	10KY, 10L0, 10LB, 10LC, 10LF, 10LG	
Issue date *	2016-3-24	L

.ogo

Lenovo.

Product	environmental attributes - Legal requirements	Require		tmet
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.	\boxtimes		
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/environment.html			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\boxtimes		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\square		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			\square
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\square
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	\boxtimes		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	\boxtimes		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Issue date* 2016-3-24 Logo Lenovo Product anvironmental attributes - Market requirements - Environmental conscious design Requirement met Product anvironmental attributes - Market requirements - Environmental conscious design Requirement met Product anvironmental attributes - Market requirements - Environmental conscious design Yes Poisage Disage Disage P11 Information Yes No P72 Plastic materials in covershousing have no surface coaling. Disage Disage P73 Plastic parts >100 gromsit of one material or of easily separable materials. Disage Disage P73 Plastic parts >25g have material codes according to ISO 11489 referring ISO 1043. Disage Disage P74 Plastic parts setzign the metal illago rable isola to a promoved with commonly available tools. Disage Disage P75 Labels are easily separable. (This requirement does not apply to safely/regulatory labels). Disage Disage P77 Upgrading can be done using commonly available tools Disage Disage Disage P77 Upgrading can be done using commonly available tools Disage Disage	Model nu	umber *	10KY, 10L0, 10LB, 10LC, 10LF, 10LG				
Product environmental attributes - Market requirements - Environmental conscious design Requirement mett Requirement metter Requirement information regarding each item may be found under P14. Yes No n.a. Requirement information regarding each item may be found under P14. Yes No n.a. Requirement information regarding each item may be found under P14. Yes No n.a. Requirement information regarding each item may be found under P14. Yes No n.a. Prior Parts that have to be treated separately are easily separable Prior Parts that have to be treated separately are easily separable materials. P717 Prats that have to be treated separately are easily separable materials. Image: Ima	Issue dat	te *		Logo	Lend)VO	
Item *-mandatory to fill in. Additional information regarding each item may be found under P14. Yes No no. P6 Teatment information Important information Important information Important information P7. Design Design Important information Important information P7.1 Parts that have to be treated separately are easily separable materials. Important information Important information P7.3 Plastic parts >100g consist of one material or of easily separable materials. Important information Important information P7.4 Plastic parts >26g have material codes according to ISO 11489 referring ISO 1043. Important information Important information P7.6 Lables are easily separable. (This requirement does not apply to sefety/regulatory labels). Important information Important information P7.4 Upgrading can be done using commonly available tools Important information Important information Important information P7.1 Upgrading can be done using commonly available tools Important information for Syears Important information Important information P7.11 Product Heftme Important information for Syears Important information Important information P7.13 Service available after end of poduction for: Syears Important informatio prover cobles are PVC free <t< td=""><td></td><td></td><td></td><td></td><td>LOIN</td><td></td><td></td></t<>					LOIN		
Item *=mandatory to fill in. Additional information regarding each item may be found under P14. Yes No no. P6 Teatment information Important information for recyclers/incatment facilities is available (see legal reference). Important information for recyclers/incatment facilities is available (see legal reference). Important information for recyclers/incatment facilities is available (see legal reference). Important information for recyclers/incatment facilities is available (see legal reference). Important information for recyclers/incatment facilities is available (see legal reference). Important information for recyclers/incatment facilities is available sparable material. Important information for recyclers/incatment facilities is available sparable material. Important information for recyclers/incatment facilities is available for all segmetable. Important information for recyclers/incatment facilities is available for all segmetable. Important information for recyclers/incatment facilities is available for all segmetable. Important information for recyclers/incatment facilities is available for all segmetable. Important information for recyclers is available for all on processor, memory, cards or drives Important information for recyclers is available for and or production for: 7 years Important information for recyclers is available for and or production for: 7 years Important information for recyclers is available for and or droduction for: 7 years Important information for recyclers is available for and or droduction for: 7 years Important information for recyclers is available for and or droduction for: 7 years Important infore recyclers is available for and or dr	Product	t environ	mental attributes - Market requirements - Environmental conscious d	lesign	Require	ment	met
P6.1* Information for recyclers/treatment facilities is available (see legal reference). ☑ P7 Design Disassembly, recycling ☑ P7.1* Parts that have to be treated separately are easily separable ☑ P7.2* Plastic materials in covershousing have no surface coating. ☑ ☑ P7.4* Plastic parts >1000 consist of one material or of easily separable materials. ☑ ☑ P7.4* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. ☑ ☑ P7.4* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. ☑ ☑ P7.4* Usgrading can be done e.g. with processor, memory, cards or drives ☑ ☑ P7.4* Usgrading can be done e.g. with processor, memory, cards or drives ☑ ☑ P7.4* Plastic anta's easilable after end of production for: 5 years ☑ ☑ P7.1* Product coverhousing material type: AC Material type: Steel ☑ P7.11 Product coverhousing material type: AC Material type: Steel ☑ ☑ P7.14 All cover/housing material type: AC Material type: Steel ☑<							
P7 Design Image: Construction of the second se							
Dissistentify, recycling P711 Practs that have to be treades deparately are easily separable P72 Plastic materials in covers/housing have no surface coating. P73 Plastic parts >100g consist of one material or of easily separable materials. P74 Plastic parts >250 parts are free from metal inlays or have inlays that can be removed with commonly available tools. Product lifetime Product lifetime P770 Upgrading can be done e.g. with processor, memory, cards or drives P78 Upgrading can be done e.g. with processor, memory, cards or drives P78 Upgrading can be done e.g. with processor, memory, cards or drives P78 Upgrading can be done e.g. with processor parts are available after end of production for: 5 years P710			ion for recyclers/treatment facilities is available (see legal reference).				
P7.1 Protes that have to be treated separately are easily separable Image: Contemportal Section 2012 P7.2 Plastic materials in covers/housing have no surface coaling. Image: Contemportal Section 2012 P7.3 Plastic parts >25g have material code saccording to ISO 11469 referring ISO 1043. Image: Contemportal Section 2013 P7.5 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. Image: Contemportal Section 2013 P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Image: Contemportal Section 2013 P7.7 Upgrading can be done e.g. with processor, memory, cards or drives Image: Contemportal Section 2013 P7.9 Spare parts are available after end of production for: 5 years Image: Contemportal Section 2014 P7.10 Service is available after end of production for: 5 years Image: Contemportal Section 2014 P7.11 Product cover/housing material type: PC Material type: Steel P7.11 Product cover/housing material section prove cables are PVC free Image: Contemportal Section 2014 P7.12 Electrical cable insulation materials of signal cables are PVC free Image: Contemportal Section 2014 P7.13 Electrical cable insulation materials or printed circuit boards (without components): Contemportsice contemportsis: Contemportal Section 20	P7	•	mbly, recycling				
P7.3* Plastic parts >100g consist of one material or of easily separable materials. Image: Constraint of the constraints in printed	P7.1*				\square		
P7.4* Plastic parts >255 have material codes according to ISO 11469 referring ISO 1043. □ P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. □ P7.6* Lables are easily separable. (This requirement does not apply to safely/regulatory labels). □ P7.6* Lables are easily separable. (This requirement does not apply to safely/regulatory labels). □ P7.7* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done using commonly available tools □ P7.8* Upgrading can be done using commonly available tools □ P7.8* Upgrading can be done using commonly available tools □ P7.8* Upgrading can be done using commonly available tools □ P7.8* Upgrading can be done using commonly available tools □ P7.8* Upgrading can be done using commonly available tools □ P7.10* Service is available after end of production for: 5 years □ P7.11* Product Cover/housing material type: MC Material type: Steel P7.12 Electrical cable insulation materials of goner cables are PVC free □ P7.14 All cover/housing plastic parts >25g are f	P7.2*	Plastic m	naterials in covers/housing have no surface coating.			\times	
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. Image: Commonly available after easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Image: Commonly available after end of production for 5 years P7.9 Upgrading can be done e.g. with processor, memory, cards or drives Image: Commonly available after end of production for 5 years P7.10 Service is available after end of production for 5 years Image: Commonly available after end of production for 5 years P7.11 Product Cover/housing material type: PC Material type: Steef P7.12 Electrical cable insulation materials of signal cables are PVC free. Image: Commonly available after end production for 5 years P7.13 Electrical cable insulation materials of signal cables are PVC free. Image: Commonly available after end of production for 5 years P7.14 All cover/housing plastic parts >25g are free from chorine and bromine. Image: Commonly available after end of plastic parts >25g are free from chorine and bromine. Image: Commonly available after end available aft	P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.		\square		
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. Image: Commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Image: Commonly available tools. Image: Commonly available tools. P7.7 Upgrading can be done e.g. with processor, memory, cards or drives Image: Commonly available tools Image: Commonly available tools P7.8 Upgrading can be done e.g. with processor, memory, cards or drives Image: Commonly available tools Image: Commonly available tools P7.10 Service is available after end of production for: 5 years Image: Commonly available tools Image: Commonly available tools P7.11 Product cover/housing material type: PC Material type: Steel Image: Commonly available tools P7.12 Electrical cable insulation materials of signal cables are PVC free. Image: Commonly available tools Image: Commonly available tools P7.13 Electrical cable insulation materials of signal cables are PVC free. Image: Commonly available tools Image: Commonly available tools P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. Image: Commonly available tools Image: Commonly available tools P7.15 All traine retardants in printed circuit boards (without components):	P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.				
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). □ P7.7 Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.1* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.10 Service is available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.11 Protuct Cover/housing material so fower cables are PVC free. □ P7.12 Electrical cable insulation materials of power cables are PVC free □ P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. □ P7.15 All printed circuit boards (without components) >25g are marked according ISO 1043-4: □ Marking: P7.17 Alt 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ TBPA (additive) □ TBBPA (reactive) □ Other; chemical aname: browinated epoxy	P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly a	vailable tools.			Ē
Product lifetime Image: Steel of the set	P7.6*	-				Ħ	Ħ
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.8* Upgrading can be done e.g. with processor, memory, cards or drives □ P7.9 Spare parts are available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ P7.11 Product cover/housing material type: Material and substance requirements ■ P7.12 Electrical cable insulation materials of power cables are PVC free. ■ P7.13 Electrical cable insulation materials of signal cables are PVC free. ■ P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. ■ P7.14 All cover/housing plastic parts >25g in covers / housings are marked according ISO 1043-4: ■ Marking: ■ ■ ■ P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components) >25g according ISO 1043-4: ■ Marking: ■ ■ ■ ■ P7.18 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: ■							
P7.8 Upgrading can be done using commonly available tools □ P7.9 Spare parts are available after end of production for: 5 years □ P7.10 Service is available after end of production for: 5 years □ Material and substance requirements □ P7.11 Product cover/housing material type: Material type: APC Material type: Steel P7.12 Electrical cable insulation materials of signal cables are PVC free. □ P7.13 Electrical cable insulation materials of signal cables are PVC free. □ P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. □ P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) □ P7.16 Filme retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: □ P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ P7.18 Alt. 1 Premical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □	P7.7*						
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing materials of power cables are PVC free. P7.12 Electrical cable insulation materials of signal cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Matring: P7.16 P7.14 Att. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)						Ē	Ħ
P7.10 Service is available after end of production for: \$ years Material and substance requirements P7.11* Product coverhousing material type: Material type: ABS Material type: ABS Material type: PC Material type: ABS Material type: Stee/ P7.12 Electrical cable insulation materials of gnad cables are PVC free. ○ P7.13 Electrical cable insulation materials of signal cables are PVC free ○ P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. ○ P7.15 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: ○ Marking: P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: ○ Marking: D. The retarded plastic parts >25g context in printed circuit boards >25g (without components): □ TBBPA (additive)							H
P7.11 Material and substance requirements P7.11 Product cover/housing material type: Material type: PC Material type: Steel P7.12 Electrical cable insulation materials of signal cables are PVC free. Image: Steel P7.13 Electrical cable insulation materials of signal cables are PVC free. Image: Steel P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. Image: Steel P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Image: Steel P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Image: Steel P7.17 Att. 1 Chemical specifications of flame retardants in printed circuit boards (without components): Image: Steel TBBPA (additive) TBBPA (reactive) Other, chemical name: brominated epoxy resins, CAS #: 2265-8-7 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Image: Steel Image: Steel P7.18 Att. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Image: Steel Image: Steel P7.18 Att. 1 Flame retarded plastic parts >25g according ISO 1043-4			· · · · · ·				⊢⊢
P7.11* Product cover/housing material type: Material type: ABS Material type: PC Material type: Stee/ P7.12 Electrical cable insulation materials of power cables are PVC free □ □ P7.13 Electrical cable insulation materials of signal cables are PVC free □ □ P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. □ □ P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2:21. (See □ Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: □ Material type: Image: The PR A (additive) □ Image: The PR A (additive) □ P7.17 Att. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ □ TBBPA (additive) □ TBBPA (reactive) ☑, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 Att. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according □ □ ISO 1043-4: □ □ □ □ □ P7.18 Att. 1 Flame retarded plastic parts >25g contai	17.10						
Material type: ABS Material type: PC Material type: Stee/ P7.12 Electrical cable insulation materials of power cables are PVC free Image: Comparison of Static Comparis Comparison	P7.11*						
P7.12 Electrical cable insulation materials of power cables are PVC free. Image: Comparison of the comparison of				al type: Steel			
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. □ P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: □ P7.17 Att. 1 □ □ Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ □ TBBPA (additive) _, TBBPA (reactive) ○, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 Alt 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ □ P7.18 Alt 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ □ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: □ □ 2. Chemical name: , CAS #: □ □ □ □ □ 3. Chemical name: , CAS #: □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ <td>P7.12</td> <td></td> <td></td> <td>71</td> <td></td> <td>\boxtimes</td> <td></td>	P7.12			7 1		\boxtimes	
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. □ P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) □ P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: □ P7.17 Att. 1 □ □ Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ □ TBBPA (additive) _, TBBPA (reactive) ○, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ □ P7.18 Att. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ □ Cohemical name: _, CAS #: 3. Chemical name: _, CAS #: □ □ Att. 2 Chemical name: _, CAS #: □ □ □ □ P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) □ □ P7.20 Of tota	P7.13	Electrica	I cable insulation materials of signal cables are PVC free				Ē
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: □ P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ TBBPA (additive) _, TBBPA (reactive) _, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 □ □ Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: □ 3. Chemical name: , CAS #: □ □ □ Att. 2 Chemical specifications of flame retardant substances/ preparations above 0.1%: □ □ P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1%: classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) □ □ P7.20 Of total plastic parts' weight >25g, recycled mater	P7.14	All cover	/housing plastic parts >25g are free from chlorine and bromine.				Ħ
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: □ Marking: □ □ P7.17 Alt. 1 □ □ Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) □, TBBPA (reactive) ☑, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 □ □ Alt. 2 □ □ □ □ ISO 1043-4: □ □ □ □ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ □ ☑ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: . CAS #: . Chemical name: . CAS #: . Chemical name: . CAS #: . Chemical specifications of flame retardant substances/ preparations above 0.1% classified as R45, . R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) □ □ P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, . R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) □ □ P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. □ □ ☑ ☑ P7.21 Light sources are free from mercury		All printe	ed circuit boards (without components) >25g are halogen free. as defined in IEC6	31249-2-21. (Se			
Marking: P7.17 Alt. 1 P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) □, TBBPA (reactive) ☑, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 □ □ Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ □ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ ☑ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: . CAS #: 2. Chemical name: . CAS #: 3. Chemical name: . CAS #: 4.t. 2 □ ☑ P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) □ ☑ P7.20 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Ight sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: 8 ☑ ☑ ☑ P8 Batteries □ ☑ ☑ ☑ ☑ ☑	D7.40						
Chemical specifications of flame retardants in printed circuit boards >25g (without components): □ TBBPA (additive) □, TBBPA (reactive) ○, Other; chemical name: brominated epoxy resins, CAS #: 26265-8-7 Alt. 2 □ □ Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: □ □ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: □ ⊠ Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: □ ⊠ Alt. 2 Chemical specifications of flame retardant substances/preparations in concentrations above 0.1%: COmment: No legal limits exist, this is a market requirement. □ ⊠ 1. Chemical name: , CAS #: □ ○ ○ ○ Alt. 2 Chemical specifications of flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) ○ ○ P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. ○ ○ ○ P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. ○ ○ ○		Marking:					
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Image: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4.t. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide	P7.17	Chemica TBBPA ((additive) 🔲, TBBPA (reactive) 🔀, Other; chemical name: brominated epoxy re	nts): <mark>sins</mark> , CAS #:			
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in Image: State St		Alt. 2 Chemica ISO 1043	al specifications of flame retardants in printed circuit boards (without components) >:	25g according			
1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide	P7.18	Flame r concentr	ations above 0.1%:	/preparations i	n 🗌		
P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) Image: Comparison of the comparation of the c		1. Chem 2. Chem 3. Chem Alt. 2	ical name: , CAS #: ical name: , CAS #: ical name: , CAS #:				
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide							
P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide	P7.19	R40, R4	6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	ified as R45,			
P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide							
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries Eastername Eastername P8.1* Battery chemical composition: Lithium Manganese Dioxide							
P8 Batteries P8.1* Battery chemical composition: Lithium Manganese Dioxide	P7.22			ma			\bowtie
P8.1* Battery chemical composition: <i>Lithium Manganese Dioxide</i>	P8			mg			
	P8.2	-					Ħ

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	10KY, 10L0, 10LB, 10LC, 10LF, 10LG		
Issue date *	2016-3-24	Logo	Lenovo.

Item	<mark>t environmental attri</mark>			//	Requirement Yes No	n
P9	Energy consumptio	n				
9.1	For the product the fo		els or energy cons	umptions are re	ported: See P14	
Energy r	mode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	[
Peak (O	n-max)	W	W	W	Full load	[
Catego	ory I1					
	lle State - WOL Enabled	19.41 W	19.49 W	19.23 W	Use for ENERGY STAR V6 registration (Pidle)	
Long Idle State - WOL Enable		19.08 W	18.58 W	18.30 W	Use for ENERGY STAR V6 registration (P _{idle})	
Sleep (S	S3) - WOL Enabled	1.21 W	1.21 W	1.22 W	Use for ENERGY STAR V6 registration(P _{sleep})	
	53) - WOL Disabled	W	W	W	Reference	
	- WOL Enabled	0.65 W	0.65 W	0.67 W	Use for ENERGY STAR V6 registration(Port)	
	- WOL Disabled	W	W	W	Use for EuP	
Catego						
	lle State - WOL Enableo	1 19.39 W	19.48 W	19.47 W	Use for ENERGY STAR V6 registration (P _{idle})	
	le State - WOL Enabled		18.63 W	18.61 W	Use for ENERGY STAR V6 registration (P _{idle})	
	63) - WOL Enabled	1.21 W	1.20 W	1.21 W	Use for ENERGY STAR V6 registration(P _{sleep})	
	63) - WOL Disabled	W	W	W	Reference	
	- WOL Enabled	0.65 W	0.65 W	0.67 W	Use for ENERGY STAR V6 registration(P _{off})	
	- WOL Disabled	W	W	W	Use for EuP	
		٧٧	vv	vv	ose for Eur	
Catego	<u>Ory 13</u> lle State - WOL Enableo	20.66 W	20.42 W	20.44 W	Use for ENERCY STAR V6 registration (D)	
					Use for ENERGY STAR V6 registration(P _{idle})	
	le State - WOL Enabled		19.45 W	19.50 W	Use for ENERGY STAR V6 registration(P _{idle})	
	S3) - WOL Enabled	1.22 W	1.22 W	1.23 W	Use for ENERGY STAR V6 registration (P _{sleep})	
	S3) - WOL Disabled	W	W	W	Reference	
	- WOL Enabled	0.65 W	0.65 W	0.67 W	Use for ENERGY STAR V6 registration(Poff)	
	- WOL Disabled	W	W	W	Use for EuP	
Catego						
Short Id	lle State - WOL Enabled		25.26 W	25.18 W	Use for ENERGY STAR V6 registration(P _{idle})	
-	le State - WOL Enabled	24.13 W	24.34 W	24.27 W	Use for ENERGY STAR V6 registration(P _{idle})	
Sleep (S	S3) - WOL Enabled	1.22 W	1.22 W	1.23 W	Use for ENERGY STAR V6 registration (P _{sleep})	[
Sleep (S	S3) - WOL Disabled	W	W	W	Reference	[
Off (S5)	- WOL Enabled	0.65 W	0.65 W	0.67 W	Use for ENERGY STAR V6 registration(P _{off})	[
Off (S5)	- WOL Disabled	W	W	W	Use for EuP	
Catego	ory D2	- ·	•	·	•	•
Short Id	lle State - WOL Enabled	25.66 W	25.67 W	27.54 W	Use for ENERGY STAR V6	[
Long Id	le State - WOL Enabled	24.82 W	24.72 W	24.45 W	Use for ENERGY STAR V6	
Sleep (S	S3) - WOL Enabled	1.22 W	1.22 W	1.22 W	Use for ENERGY STAR V6 registration	
Sleep (S	S3) - WOL Disabled	W	W	W	Reference	
Off (S5)	- WOL Enabled	0.65 W	0.65 W	0.66 W	Use for ENERGY STAR V6 registration(Poff)	Π
Off (S5)	- WOL Disabled	W	W	W	Use for EuP	
plugged	-load al power supply / charger in the wall outlet but ected from the product.)	W	W	W		
PTEC * Typical E	Energy Consumption	W	W	W		[

TEC * Typical Energy Consumption kWh/week k		kWh/week	kWh/week				
ETEC *		Cat. 11 87.7	Cat. I1 87.7 Cat. I1 87.3		$E_{TEC} = (8760/1000) \times (P_{off} \times 0.45 + P_{sleep} \times 0.45)$		
Annual En	ergy Consumption	Cat. 12 86.8	Cat. 12 87.3	Cat. 12 87.4	0.05 + P _{long_ldle} x 0.15+ P _{short_ldle} x 0.35)		
		Cat. 13 91.9	Cat. I3 91.3	Cat. 13 91.5			
		Cat. D1 112.0	Cat. D1 112.6	Cat. D1 112.3			
		Cat. D2 114.4	Cat. D2 114.3	Cat. D2 119.8			
		kWh/year	kWh/year	kWh/year			
		Poff: Off Mode(S5) - WOL Enabled; P	sleep: Sleep Mode(S3) - WOL Enabled; P _{idle} : Idle State - WOL Enabled		
Display re	solution* :	Megapixels				\square	
Print Spee	Print Speed * : Images per minute					\square	
Default time to enter energy save mode: 25 minutes							
P9.2*	Information about the energy save function is provided with the product.						
P9.3*		ets the energy requireme [®] version: <i>Version 6.1</i>		g voluntary progra luct category: 11,12,			
P10	Emissions						
		 Declared according to 	o ISO 9296				
P10.1	Mode	Mode description		Declared A-weighted	Declared A-weighted sound pressure level L_{pAm} (dB)		
				sound power level $L_{WAd}(B)$			
	Idle	* HDD:Idle	IDD:Idle		23		
	Operation	* HDD: Operating	HDD: Operating		24		
	Other mode						
	Measured according to: ISO7779 ECMA-74 Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)						
P10.2	The product mee	ets the acoustic noise re		,	P	\square	

Model nu	mber *	10KY,	10L0	, 10LI	B, 10)LC,	10L	.F, 1	0LG						
Issue date	e *	2016-3-24				,					Logo		Leno	VO,	
	-														
	environn	nental attri	butes - I	Market re	equirer	nents	(cont	inued)				F	Require		
Item													Yes	No	n.a.
	Chemica	al emission	s from pri	nting pro	ducts										
P10.3*	Test per	formed acco	rding to E0	CMA-328	(ISO/IE	C 2836	0) stan	dard 🔄	, other s	pecify:					\square
P10.4	Typical e	emission rate	(print pha	ase) is (mg	g/h):										\mathbb{X}
		Dust	Ozone		tyrene		Benzei		TVO	С					
P10.5	Chemica	al emission re	equiremen	ts of the fo	ollowing	volunt	ary pro	gram/s	а	re met for	:				\mathbf{X}
	0	Dust 📃	Ozone	e 🗌	Styre	ne 🗌		Ben	zene		TVOC			_	_
		nagnetic en													
P10.6	Compute	er display me	ets the re	quirement	t for low	freque	ncy ele	ctromag	netic fiel	ds of the	following volu	untary			\mathbf{X}
	program														_
P11		nable materi													
P11.1*	A Safety	Data Sheet	(SDS) is a	available fo	or the in	k/toner	r prepar	ation, e	ven if no	t legally re	equired (see	P4.3).			\bowtie
P11.2*	Paper c EN1228		st-consum	ner recycl	ed fiber	s can	be use	ed, provi	ded that	t it meets	the require	ments of			\boxtimes
P11.3*	2-sided ((duplex) print	ting/copyin	ng is an in	tegrated	l produ	ct funct	ion.							\mathbb{X}
P12	Ergonor	mics for con	nputing p	roducts											
P12.1*	The disp	lay meets th	e ergonom	nic require	ements c	of ISO 9	9241-30	07 for vis	sual disp	lay techno	ologies.		\boxtimes		
P12.2*	The phys	sical input de	evice meet	s the requ	uirement	ts of IS	O 9995	and ISC	D 9241-4	10.			\boxtimes		
P13		ing and doc													
P13.1*		packaging m					ht (kg):								
		packaging m					ht (kg):								
P13.2*		packaging m			10	weig	ht (kg):								
-		plastic packa											\boxtimes		
P13.3*		media for use			mentatio	on (tick	box):								
		ic 🔀, Papei													
P13.4*	fiber: 3	%			on, plea	se spe	cify con	ntained p	ercenta	ge of post	-consumer re	ecycled			
P14		nal informat													
											er express or				
											nent is provid				
	knowledge available at the time of completion, and supplier shall have no obligation to update such information. The information provided here is approximate and provided for informational purposes only. See a Lenovo Account Representative for more						ion								
	informati		oximate a			iomat	ισπαι ρι	nposes	only. Se	e a Lenov	O ACCOUNT RE	epresenta		nore	
P9		ergy Star Qu	alified No	tebooks	& Table	t Com	outers	for the	latest in	formatio	n:				
											n. oup&pgw_co	ode=CO			
											1 110 _1				

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	Lenovo S510	Logo
Model Number	10KY, 10L0, 10LB, 10LC, 10LF, 10LG	Lenovo
Issue Date	2016-3-24	LEIIOVO
Additional information		

17.1.1	Product environmental attributes	
(d)	year of manufacture:	Available on product label
(e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graph disabled and if the system is tested with switchable graphics mode with UMA driving the display:	iics cards (dGfx) are
	Category (according to ErP Lot 3): Etec:	
(f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graph enabled:	ics cards (dGfx) are
	Category (according to ErP Lot 3): BEtec: 95.32Category (according to ErP Lot 3): DEtec: 96.9	
(g)	idle state power demand (Watts);	26.58
(h)	sleep mode power demand (Watts);	1.23
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	1.23
(j)	off mode power demand (Watts);	0.67
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	0.67
(I)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):	
	10% 82.26% 20% 87.39% 50% 88.50% 100% 85.78% Average 87.22%	
(m)	external power supply efficiency (if applicable):	
	10% 20% 50% 100% Average ;	
(-)	or level:	
(0)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook comput	ers):
(p-1)	the measurement methodology used to determine information mentioned in points (I) - internal	PSU
	efficiency: 80 PLUS® Program	
(p-2)	the measurement methodology used to determine information mentioned in points (m) - external efficiency:	PSU
	N/A	
(p-3)	the measurement methodology used to determine information mentioned in points (o) - loadingo batteries:	cycles
	<u>N/A</u>	

(p-4)	the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:								
	IEC 62623 / IEC EN50564:2011 measurement methodology								
(q)	sequence of steps for achieving a stable condition with respect to power demand::								
	Power on -> Wait 5 minutes ->Stable condition								
(r)	description of how sleep and/or off mode was selected or programmed:								
	Begin menu -> Power -> Select sleep or off mode								
(s)	sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:								
	Control Panel->Power Options-> Change Settings-> Restore default settings for this plan								
(t)	the duration of idle state condition before the computer automatically reaches sleep mode , or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 25								
(u)	the length of time after a period of user inactivity in which the computer automatically reaches apower mode that has a lower power demand requirement than sleep mode (in minutes):25								
(v)	the length of time before the display sleep mode is set to activate after user inactivity (in minutes): 10								
(w)	informatior	on the energy-savi	ng poter	ntial of power managemen	t functionality:				
				N/A					
(x)	user inform	nation on how to ena	ble the	power management functi	onality:				
				Refer to User Guid	e				
(z)	test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:								
Test voltage in V and frequency in Hz 230V/50Hz Total harmonic distortion of the electricity supply system $\leq 2\%$ Information and documentation on the instrumentation, set-up and circuits used for electrical testing									
	Instrument			Range Used Or ***	Make and Model **				
	Type AC Power Source		1~280VAC;1~550HZ;1000VA.		NF;EC1000S; SN:9152124				
	Digital Watch		Full range		CASIO; HS-70W; SN:208Q08R				
	Power Meter		0~600V;0~20A		YOKOGAWA;WT210;SN:91M944 560				
		othermograph		15~35℃/15~90%	testo; 608-H1,SN:1034895602				
		nal anemometer		0~20m/s,-20~70℃	Testo;425;SN:02591883				
A ddition	-	ht Measuring		1°;1-300cd/ m ²	Konica Minolta;LS-110;				
Yes	NOTEDOOK D	attery Information: No	n/a		is operated by battery/ies that cannot	be accessed and replaced			
(Battery not user (Battery user replaceable)				by a non-professional user. The battery[ies] in this product cannot be easily replaced by users themselves					