

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environmen	t.html
Additional information		

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.					
Type of product *	Personal Computer				
Commercial name *	ThinkCentre M83 Tower;				
Model number *	<u>Tower:</u> 10AG, 10AK, 10AL, 10BE				
Issue date *	2014-05-13				
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other				
Additional information	Only 10AG, 10BE is Energy Star 6.0 Qualified and EPEAT Silver; GREENGUARD				
	Certification				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control Re		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	\square	

Model number *	ThinkCentre M83 Tower	MTs: 10AG, 10AK, 10A	AL, 10BE
Issue date *	2014-05-13	Logo	lenovo

	t environmental attributes - Legal requirements	Require		
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\boxtimes		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment	\square		
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).			
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	;		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\mathbf{X}		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium an hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\square		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

	· · ·	2014-05-13 Logo	_		
ssue da	ite *	2014-05-13 Logo	end		D.
Produc	t onvironn	nental attributes - Market requirements - Environmental conscious design	Require	mont	mo
tem		bry to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a
P6		t information	100	110	
P6.1*	Informatio	n for recyclers/treatment facilities is available (see legal reference).			
P7	Design				
		bly, recycling			
P7.1*		have to be treated separately are easily separable	\square		
P7.2*		terials in covers/housing have no surface coating.	\square		
P7.3*		rts >100g consist of one material or of easily separable materials.	\square		
P7.4*	-	rts >25g have material codes according to ISO 11469 referring ISO 1043.	\square		
P7.5		rts are free from metal inlays or have inlays that can be removed with commonly available tools.	\square		
P7.6*	Labels are	easily separable. (This requirement does not apply to safety/regulatory labels).	\boxtimes		
	Product I				
P7.7*		can be done e.g. with processor, memory, cards or drives	\square		
P7.8*	Upgrading	can be done using commonly available tools	\square		
P7.9.	Spare par	ts are available after end of production for: 5 years	_		
P7.10	Service is	available after end of production for: 5 years	_		
		nd substance requirements			
P7.11*		over/housing material type:			
P7.12	Material ty	pe: ABS Material type: PC/ABS Material type: Steel cable insulation materials of power cables are PVC free. Material type: Steel			_
			<u> </u>		
P7.13		cable insulation materials of signal cables are PVC free			
P7.14		nousing plastic parts >25g are free from chlorine and bromine.			
P7.15	Note B2)	circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (Se	e 🗌		
P7.16	Marking:	arded plastic parts >25g in covers / housings are marked according ISO 1043-4:			
P7.17		specifications of flame retardants in printed circuit boards >25g (without components): dditive) , TBBPA (reactive) , Other; chemical name: , CAS #:			
		specifications of flame retardants in printed circuit boards (without components) >25g according 4: <i>Brominated Epoxy Resin See P14</i>			
P7.18		arded plastic parts >25g contain the following flame retardant substances/preparations i tions above 0.1%:	n 🗌		
	Provide a complete 1. Chemic 2. Chemic	al name: , CAS #: , Supplier:	n		
	3. Chemic Alt. 2 Chemical	al name: , CAS #: , Supplier: specifications of flame retardants in plastic parts >25g according ISO 1043-4:			C
P7.19		rts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	\square		
P7.20		astic parts' weight >25g, recycled material content is Tower: 55.97%,			
P7.21		astic parts' weight >25g, biobased material content is 0%.			N
97.22	<u> </u>	ces are free from mercury			
28	Batteries	emical composition:			
°8.1*					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	ThinkC	entre M8	3 Tower	MTs: 10/	AG, 10AK, 10AL, 10BE	
Issue date *	2014-05-13				Logo lenovo	•
Product environm	nental attrib	utes - Market r	equirements	(continued)	Requirement	met
Item					Yes No	n.a.
•••	consumption				astadi Cas D14	
The proc	luct is shipped	w/ WOL Enabled	ls of energy cor	nsumptions are rep		
Energy mode *		wer level at 00 V AC	Power level 115 V AC	at Power level 230 V AC	at Reference / Standard for energy modes and test method *	
Category 0			-	-		
Short Idle State - W		W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Long Idle State - W		W	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
Sleep (S3) - WOL E		W	W	W	Use for ENERGY STAR V6 registration(P _{sleep})	
Sleep (S3) - WOL D		W	W	W	Reference	
Off (S5) - WOL Ena		W	W	W	Use for ENERGY STAR V6 registration(P _{off})	
Off (S5) - WOL Disa	bled	W	W	W	Use for EuP	
Category I1		1				
Short Idle State - W		23.85 W	23.98 W	23.90 W	Use for Energy Star V6.0 registration(P _{shortIdle})	
Long Idle State - W		22.76 W	22.68 W	22.65 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL E		0.80 W	0.82 W	1.03 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL D		0.80 W	0.82 W	1.03 W	Reference	
Off (S5) - WOL Ena		0.53 W	0.55 W	0.75 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disa	bled	0.35 W	0.35 W	0.35 W	Use for EuP	
Category I2				•		
Short Idle State - W		24.32 W	24.37 W	24.68 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - W		23.12 W	22.96 W	23.82 W	Use for Energy Star V6.0 registration(P _{Longidle})	
Sleep (S3) - WOL E		0.80 W	0.81 W	1.02 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL D	isabled	0.80 W	0.82 W	1.03 W	Reference	
Off (S5) - WOL Ena		0.53 W	0.54 W	0.73 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disa	bled	0.35 W	0.35 W	0.35 W	Use for EuP	
Category 13						
Short Idle State - W	OL Enabled	24.35 W	23.91 W	24.16 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - W	OL Enabled	23.13 W	22.78 W	22.75 W	Use for Energy Star V6.0 registration(P _{Longldle})	
Sleep (S3) - WOL E	nabled	0.81 W	0.83 W	1.03 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL D	isabled	0.80 W	0.82 W	1.03 W	Reference	
Off (S5) - WOL Ena	bled	0.54 W	0.55 W	0.74 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disa	bled	0.35 W	0.35 W	0.35 W	Use for EuP	
Category D1		•				
Short Idle State - W	OL Enabled	32.19 W	32.31 W	31.73 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - W	OL Enabled	31.09 W	31.07 W	30.58 W	Use for Energy Star V6.0 registration(PLongIdle)	
Sleep (S3) - WOL E	nabled	0.80 W	0.82 W	1.03 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL D	isabled	0.80 W	0.82 W	1.03 W	Reference	
Off (S5) - WOL Ena	bled	0.53 W	0.55 W	0.74 W	Use for Energy Star V6.0 registration (Poff)	
Off (S5) - WOL Disa	bled	0.35 W	0.35 W	0.35 W	Use for EuP	
Category D2				·		
Short Idle State - W	OL Enabled	31.93 W	32.24 W	31.71 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	
Long Idle State - W	OL Enabled	30.82 W	32.84 W	30.56 W	Use for Energy Star V6.0 registration(P _{Longidle})	
Sleep (S3) - WOL E	nabled	0.80 W	0.82 W	1.03 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S3) - WOL D	isabled	0.80 W	0.82 W	1.03 W	Reference	
Off (S5) - WOL Ena	bled	0.53 W	0.55 W	0.74 W	Use for Energy Star V6.0 registration (Pott)	Ē
Off (S5) - WOL Disa		0.35 W	0.35 W	0.35 W	Use for EuP	F

plugged i	load I power supply / cha in the wall outlet bu ected from the produ	ıt	W	W	
TEC Typical E	Energy Consumption	kWh/week n	kWh/week	kWh/week	
Etec * Annual E	Energy Consumption	<i>Cat I3: 107.53;</i> <i>CatD1:141.71;</i> <i>CatD2:140.83;</i> kWh/year	Cat 11: 105.84; Cat 12: 107.39; Cat 13: 105.77; CatD1:142.44; CatD2:142.20; kWh/year	Cat I1:106.45; Cat I2:110.32; Cat I3:107.34; CatD1:140.83; CatD2:140.75; kWh/year P _{sleep} : Sleep Mode(S	ETEC = (8760/1000) x (Poff x 0.45 + Psleep x 0.05 + Pshortidle x 0.35 + PLongidle x 0.15)
Dicplay	resolution :	Megapixels			
Print Spe		Images per minute			
	•••	save mode: 30 minutes			
P9.2*	Information abo	ut the energy save funct	ion is provided w	vith the product.	
P9.3*	ENERGY STAR	ets the energy requirem Reversion: Version 6.0			
	Others specify:			<i>er 10, 2013</i> Produ	ct category: 11,12,13,D1,D2
P10				<i>er 10, 2013</i> Produ	ct category: <i>I1,I2,I3,D1,D2</i>
P10	Emissions	n – Declared according t		<i>er 10, 2013</i> Produ	ct category: 11,12,13,D1,D2
P10 P10.1	Emissions			Declared A-weighted sound power level L _{WAd} (E	Declared A-weighted sound pressure level L _{pAm} (dB)
	Emissions Noise emission	n – Declared according t		Declared A-weighted sound power	$\begin{array}{c c} & & & \\ \hline & & \\ r \\ s \\ \hline \\ r \\ r \\ \hline \\ r \\ s \\ \hline \\ r \\ r \\ \hline \\ r \\ s \\ \hline \\ r \\ \hline \\ \hline$
	Emissions Noise emission Mode	n – Declared according t Mode description		Declared A-weighted sound power level L _{WAd} (E	r B) Declared A-weighted sound pressure level L_{pAm} (dB) Operator position Bystander positions Desktop (only if product is not operator attended)
	Emissions Noise emission Mode	n – Declared according t Mode description * HDD: Idle		Declared A-weighted sound power level L _{WAd} (E	Declared A-weighted sound pressure level L_{pAm} (dB) Operator position S Desktop Operator position S Operator position S Desktop Operator attended 0 operator attended
	Emissions Noise emission Mode Idle Operation Other mode	n – Declared according t Mode description * HDD: Idle	o ISO 9296	Declared A-weighted sound power level L _{WAd} (E * 3.4 * 3.6	Declared A-weighted sound pressure level L_{pAm} (dB) Operator position S Desktop Operator position S Operator position S Desktop Operator attended 0 operator attended

Model nu	mber *	ThinkCentre M83 Tower MTs: 10AG, 10AK, 10AL, 1	0BE		
Issue date	e *	2014-05-13 Logo	епо	VO	P
		· · · · · · · · · · · · · · · · · · ·	<u> </u>		
	environn	nental attributes - Market requirements (continued)	Require		
Item			Yes	No	n.a.
Dia at		al emissions from printing products			
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard _, other specify:			
P10.4	Typical e	emission rate (print phase) is (mg/h):			\boxtimes
		Dust Ozone Styrene Benzene TVOC			
P10.5		Il emission requirements of the following voluntary program/s are met for :			\bowtie
		Dust Ozone Styrene Benzene TVOC			
D40.0		nagnetic emissions			
P10.6	, program				
P11	Consum	able materials for printing products			
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).			\boxtimes
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the requirements to 1.	of 🗌		\square
P11.3*	2-sided (duplex) printing/copying is an integrated product function.			\boxtimes
P12	Ergonor	nics for computing products			
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technologies.	\boxtimes		
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.	\boxtimes		
P13	Packagi	ng and documentation			
P13.1*	Product Product	packaging material type(s): <i>Paper</i> weight (kg): <i>1.746</i> packaging material type(s): <i>Arcel</i> weight (kg): <i>0.303</i> packaging material type(s): <i>HDPE</i> weight (kg): <i>0.016</i>			
P13.2*	Product	plastic packaging is free from PVC.	\boxtimes		
P13.3*		nedia for user and product documentation (tick box):			
P13.4*	For pape	r user and product documentation, please specify contained percentage of post-consumer recycled % (Japan only 70%)			
P14	Additior	al information (See Note B4)			
	informati knowledg provided informati		ed on sup on. The in	plier's forma	
P7.17	Product	does not contain free TBBPA in printed circuit boards(without components)>25g.			
P9		ergy Star Qualified (insert appropriate Product type; i.e. Desktop, Notebook, etc.) for the lates ownloads.energystar.gov/bi/qplist/laptops_prod_list.xls (insert appropriate web url)	t informat	ion:	

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkCentre M83 Tower	Logo
Model Number	10AG, 10AK, 10AL, 10BE	
Issue Date	2014-05-07	lenovo
Additional information	Only 10AG, 10BE is Erp Lot3 Qualified, which is equipped with I	ES PSU.

P7.1.1	Product environmental attributes	
(d)	Year of manufacture: Ava	ilible on product label
(e)	E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (dGfx) are disabled and if the system is tested with switchable graphics mode with UMA driving the display: Cat. B 88.10 Cat. C 91.52	
(f)	Cat. D 94.92 E TEC value (kWh) and capability adjustments applied when all discrete graphics cards (dGfx) are enabled: Cat. B 121.89 Cat. C 121.87 Cat. D 123.15	
(g)	idle state power demand (Watts);	34.15
(h)	sleep mode power demand (Watts);	1.25
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	1.25
(j)	off mode power demand (Watts);	0.57
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	0.61
(I)	Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 78.61% 20% 84.02% 50% 86.51% 100% 83.02%	
(m)	External power supply efficiency (if applicable): 10% 20% 50% 100% Average ; or Level:	N/A
(0)	The minimum number of loading cycles that the batteries can withstand (applies only to notebook computers):	N/A
(f)	Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion o the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Test voltage in V and frequency in Hz 230V/50Hz Total harmonic distortion of the electricity supply system ≤ 2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing Instrument Range Used Make and Model ** Type Or *** AC Power Source 1~280VAC;1~550HZ;1000V	

Hauttil		mation					
	onal info		The ballery			1961769	
100			user.		annot be easily replaced by users them	·	
Additic Yes	<mark>on Noteb</mark> No	ook Batter n/a	ry Information: This notebook c	omputer is operated by batt	ery/ies that cannot be accessed and replaced by	a non-professional	
				Refer to User G	Guide		
(x)	Use	r informatio	on on how to enab	le the power management f	unctionality:		
				N/A			
(w)	Info	mation on	the energy-saving	potential of power manage	ment functionality:		
(v)	The	length of	time before the c	lisplay sleep mode is set t	o activate after user inactivity (in minutes):	15 minutes	
(u)	pow	The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):45 minutes45 minutes					
(t)	cond	The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30 minutes					
					-> Restore default settings for this plan		
(s)		uence of e node:	vents required to r	reach the mode where the e	quipment automatically changes to sleep and/or		
			Beg	in menu -> Power -> Selec	ct sleep or off mode		
(r)	Des	cription of I	how sleep and/or	off mode was selected or pr	ogrammed:		
			Pc	ower on -> Wait 5 minutes	->Stable condition		
(q)	Seq	uence of st	teps for achieving	a stable condition with resp	ect to power demand::		
	pow	ei as ueilli	50 III I UIIL F 3 . I II	ILEC 62301			
(p-4)	-4) The measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:						
(p-3)		The measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries:					
		iency:		N/A			
(p-2)		The measurement methodology used to determine information mentioned in points (m) – external PSU					
N ² 7		iency:		80 PLUS® Proc			
(p-1)	The		easuring	1° ;1-300cd/m ² v used to determine inform	Konica Minolta;LS-110; mation mentioned in points (I) – internal PSU		
		Thermal a	nemometer	0~20m/s,-20~70℃	Testo;425;SN:02591883		
			r Meter ermograph	0~600V;0~20A 15~35℃/15~90%	0 testo; 608-H1.SN:1034895602		
	Digital Watch			, i i i i i i i i i i i i i i i i i i i	YOKOGAWA;WT210;SN:91M94456		
		Digita	Watch	Full range	CASIO; HS-70W; SN:208Q08R		