

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environmen	t.html
Additional information		

	ased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Server
Commercial name *	ThinkServer RD530
Model number *	2569,2570,2573,2574,2575,2576
Issue date *	2012,May 29
Intended market *	🔀 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other
Additional information	ENERGY STAR® V1.1 Qualified

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control F	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	\boxtimes	

Model number *	ThinkServer RD530	MT : 2569,2570,2573,2574,25	575,2576
Issue date *	2012 , May 29	Logo	enovo

	t environmental attributes - Legal requirements	Require		
ltem		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference).	\boxtimes		
P1.3*	Comment: Legal reference has no maximum concentration value. Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),			
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\square		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\square		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentration sabove 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\square		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).			
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\square		
i J. 4				
	Consumable materials			
P4	Consumable materials If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4 P4.1* P4.2*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			
P4.1* P4.2* P4.3*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference). If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P4.1* P4.2* P4.3* P5	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference). If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference). Product packaging			
P4.1* P4.2* P4.3* P5	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference). If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P4.1* P4.2* P4.3*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1). If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference). If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference). Product packaging Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model n	umber *	ThinkServer RD530 MT : 2569,2570,2573,257	4,257	' 5,2	<u>576</u>
Issue da	ate *	2012 , May 29 Logo	lena)V C	D.
Produc	t environ	mental attributes - Market requirements - Environmental conscious design	Require	ment	met
Item		atory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.a.
P6		Int information	100	110	ma.
P6.1*		ion for recyclers/treatment facilities is available (see legal reference).			
P7	Design	· · · · · · · · · · · · · · · · · · ·			
		mbly, recycling			
P7.1*		at have to be treated separately are easily separable	\boxtimes		
P7.2*	Plastic n	naterials in covers/housing have no surface coating.		\square	
P7.3*	Plastic p	arts >100g consist of one material or of easily separable materials.	\square		
P7.4*	Plastic p	arts >25g have material codes according to ISO 11469 referring ISO 1043.		Ē	Ē
P7.5	Plastic p	arts are free from metal inlays or have inlays that can be removed with commonly available tools.		Ē	Ħ
P7.6*		re easily separable. (This requirement does not apply to safety/regulatory labels).		H	H
		lifetime			
P7.7*		ng can be done e.g. with processor, memory, cards or drives			
P7.8*		ng can be done using commonly available tools		⊢⊢	\dashv
P7.9.					╞
P7.10		arts are available after end of production for: 5 years			
F7.10		s available after end of production for: 5 years			
P7.11*		and substance requirements cover/housing material type:			
F7.11					
P7.12		type: Stee1 Material type: Material type: I cable insulation materials of power cables are PVC free. Material type: Material type:		\square	
P7.13		I cable insulation materials of power cables are PVC free			╞
P7.13		/housing plastic parts >25g are free from chlorine and bromine.			
					<u> </u>
P7.15	•	ed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (Se	e	\bowtie	
P7.16	Note B2) tarded plastic parts >25g in covers / housings are marked according ISO 1043-4:			
F7.10			\boxtimes		
P7.17	Marking: Alt. 1				
17.17		I specifications of flame retardants in printed circuit boards >25g (without components):			
		(additive) , TBBPA (reactive) , Other; chemical name:, CAS #:			
	Alt. 2			_	_
		al specifications of flame retardants in printed circuit boards (without components) >25g according	\bowtie		
D7 10	ISO 104	5-4.			
P7.18	Alt. 1 Flame r	etarded plastic parts >25g contain the following flame retardant substances/preparations i	in 🗖		
		ations above 0.1%:	··· 🗀		
	Comme	nt: No legal limits exist, this is a market requirement.			
	Provide	a list of all used flame retardants including MSDS for each flame retardant. The list must contain	in		
	complete	e chemical name, CAS number and supplier.			
		ical name: , CAS #: , Supplier:			
		ical name: , CAS #: , Supplier:			
	Alt. 2	ical name: , CAS #: , Supplier:	\square		
		I specifications of flame retardants in plastic parts >25g according ISO 1043-4:			
P7.19		arts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, 6, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	\boxtimes		
P7.20		plastic parts' weight >25g, recycled material content is 0 %.			
P7.21		plastic parts' weight >25g, biobased material content is 0 %.			
P7.22		urces are free from mercury			\boxtimes
P8	Batterie				لالمع
P8.1*		shemical composition: Lithium Manganese Dioxide; Lithium Ion			
P8.2		meet the requirements of the following voluntary program/s:			H
	240000				

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	ThinkServer RD530	MT : 2569,2570,25	5 <mark>73</mark> ,	2574,2575,2576
Issue date *	2012 , May 29	Lo	ogo	lenovo

Product	environmental	attributes - Market	requirements (co	ontinued)	Requirement	met
Item					Yes No	n.a.
P9	Energy consum					
9.1		he following power lev hipped w/ WOL Enable		mptions are report	ed: <i>See P14</i>	
Energy mo	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *	
Max conf	iguration (@60 Hz)				
Peak(On-	max)	527.0 W	521.0 W	510.0 W	Use for Energy Star V1.1 registration	
Idle		158.0 W	166.0 W	164.0 W	Use for Energy Star V1.1 registration	
Min confi	guration (@60 Hz)		1		
Peak(On-	max)	136.0 W	136.0 W	133.0 W	Use for Energy Star V1.1 registration	
Idle		78.9W	77.1 W	76.8 W	Use for Energy Star V1.1 registration	
Max conf	iguration (@50 Hz)		I		
Peak(On-	max)	518.0 W	W	508.0 W	Use for Energy Star V1.1 registration	
Idle		153.0 W	W	164.0 W	Use for Energy Star V1.1 registration	
Min confi	guration (@50 Hz)		1		
Peak(On-	max)	134.0 W	W	129.0 W	Use for Energy Star V1.1 registration	
Idle		78.8 W	W	76.7 W	Use for Energy Star V1.1 registration	
EPS No-lo		W	W	W		
charger pl	power supply / ugged in the wall disconnected from ct.)					
TEC Typical Er	nergy Consumption	kWh/week	kWh/week	kWh/week		
Etec * Annual Er	ergy Consumption	kWh/year	kWh/year	kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.6 + P_{sleep} \times 0.1 + P_{idle} \times 0.3)$	
		Poff: Off Mode(S5) -	WOL Enabled; P _{sleep} : S	Sleep Mode(S3) - WO	L Enabled; P _{idle} : Idle State - WOL Enabled	
Display re	solution : Megapi	xels				
Print Spee	ed :	Images per minu	ite			
Default tin	ne to enter energy	save mode: minutes				
P9.2*	Information abou	t the energy save fund	ction is provided with	the product.		
P9.3*		ts the energy requirer version: <i>Version 1.</i>			n/s: ation for Computer Servers	
P10	Emissions					
		 Declared according 	to ISO 9296	-		
P10.1	Mode	Mode description		Declared A-weighted	Declared A-weighted	
				sound power	sound pressure level L_{pAm} (dB)	
				level L_{WAd} (B)	Operator position Bystander positions Desktop Image: Constraint of the sector of the	
	Idle	* HDD : Idel		* 5.7	39.94	
	Operation	* HDD:Operating		* 5.7	40.45	
	Other mode		_			
	Measured accord	ding to: 🔀 ISO7779 [Other	ECMA-74	ed by ECMA-74 with	th L _{pAm} measurement distance m)	
P10.2	The product mee	ts the acoustic noise				
				subming voluntary	p. vg, 0.	

Model nu	mber *	ThinkServer RD530 MT : 2569,2570,25	573,2574,2	575,2	257	6
Issue date	*	2012 , May 29	Logo	eno	vo	
Product	environn	nental attributes - Market requirements (continued)		Require	ment	met
Item				Yes	No	n.a.
	Chemica	al emissions from printing products				
P10.3*	Test per	formed according to ECMA-328 (ISO/IEC 28360) standard, other specify:				\boxtimes
P10.4	Typical e	emission rate (print phase) is (mg/h):				\boxtimes
	1	Dust Ozone Styrene Benzene TVOC				
P10.5	Chemica	I emission requirements of the following voluntary program/s are met for :				\times
	0	Dust Ozone Styrene Benzene	TVOC			
		nagnetic emissions				
P10.6	Compute program	er display meets the requirement for low frequency electromagnetic fields of the foll /s:	owing voluntary			
P11		able materials for printing products				
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ	iired (see P4.3).			\boxtimes
P11.2*	Paper co EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets th 1.	e requirements of			\square
P11.3*	2-sided ((duplex) printing/copying is an integrated product function.				\boxtimes
P12	Ergonor	nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technological	gies.			\times
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.				
P13	Packagi	ng and documentation				
P13.1*	Product Product Product	packaging material type(s): Corrugated paper weight (kg): packaging material type(s): Recycled Molded Pulp Cushion weight (kg): packaging material type(s): weight (kg): packaging material type(s): weight (kg): packaging material type(s): weight (kg):				
P13.2*		plastic packaging is free from PVC.		\boxtimes		
P13.3*		nedia for user and product documentation (tick box): ic 🔀, Paper 🔀, Other 🗌				
P13.4*	For pape fiber: 0	er user and product documentation, please specify contained percentage of post-cc % (Japan only 70%)	nsumer recycled			
P14		nal information (See Note B4)				
	informati knowledg	Supplier makes no representations, guarantees, assurances or warranties whether ion contained in this document. All information provided by supplier in this documer ge available at the time of completion, and supplier shall have no obligation to upda here is approximate and provided for informational purposes only. See a Lenovo A ion.	nt is provided base ate such informatic	d on sup n. The in	plier's forma	

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- Workstation/Server -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Workstation, mobile workstation, desktop thin client, small-scale server and computer server

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkServer RD530	Logo
Model Number	MT:2569,2570,2573,2574,2575,2576	
Issue Date	2014/4/14	lenovo.
Additional information	N/A	

(d)	year of manufacture:				See name plate of product
(e)	internal/external power supply	efficiency:			,
	DPS-550LB A	000/ 000/	E00/ 000/	100% 88%	
	Power Efficiency :10% 80% Power Factor : 10% 0.65	20% 88% 20% 0.8	50% 92% 50% 0.9	100% 88% 100% 0.95	
		20/0 0.0	00/0 0.0	10070 0.00	
	DPS-800RB A				
	Power Efficiency :10% 80%	20% <mark>88%</mark>		100% 88%	
	Power Factor : 10% 0.65	20% 0.8	50%	100%	
(f)	test parameters for measureme	ents: — test vo	oltage in V ar	nd frequency in Hz, — total harm	onic distortion of the electricity
			ation on the	nstrumentation, set-up and circu	its used for electrical testing:
	-Test Voltage : 230V, Frequer				
	-Total harmonic distortion : <2			Please refer to additional inform	
		on on the instru	imentation :		
	 Set-up and circuits used for e 	lectrical testing	n [.] Please re		
	•	lectrical testing	g: Please re	fer to additional information	
(g)	- Set-up and circuits used for e maximum power (Watts)	lectrical testing	g: <i>Please re</i>		
(g)	maximum power (Watts)	lectrical testing	g: <i>Please re</i>		529
	•	lectrical testing	g: <i>Please re</i>		529
(g) (h)	maximum power (Watts)	lectrical testing	g: <i>Please re</i>		
(h)	maximum power (Watts)	lectrical testing	g: <i>Please re</i>		529 165
(h)	idle state power (Watts)	lectrical testing	g: Please re		529
(h) (i)	idle state power (Watts)	lectrical testing	g: <i>Please re</i>		529 165
h) i)	maximum power (Watts) idle state power (Watts) sleep mode power (Watts)	lectrical testing	g: <i>Please re</i>		529 165
(h) (i) (j)	maximum power (Watts) idle state power (Watts) sleep mode power (Watts) off mode power (Watts)			fer to additional information	529 165 N/A
(i) (j)	maximum power (Watts) idle state power (Watts) sleep mode power (Watts)		mine informa	fer to additional information	529 165 N/A
(h) (i) (j) (l-1)	maximum power (Watts) idle state power (Watts) sleep mode power (Watts) off mode power (Watts) the measurement methodology	v used to deter	mine informa 80 PL	fer to additional information	529 165 N/A 14
h) i) j)	maximum power (Watts) idle state power (Watts) sleep mode power (Watts) off mode power (Watts) the measurement methodology	v used to deter	mine informa 80 PLI	fer to additional information	529 165 N/A 14

