

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo
Company name *	Lenovo	
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	html
Additional information		

	based on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Personal Computer
Commercial name *	ThinkCentre M79 SFF
Model number *	10CT, 10CU, 10CV, 10CW, 10J9, 10JA, 10JB, 10JC
Issue date *	2015-07-07
Intended market *	🛛 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other
Additional information	ENERGY STAR® 6.0 Qualified (10CT, 10CU, 10JA, 10JB); EPEAT Gold Rating,
	GREENGUARD Certified

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	ent met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes	
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	10CT, 10CU, 10CV, 10CW, 10J9, 10JA, 10JB	, 10JC)
Issue date *	2015-07-07	Logo	lenovo

Product	Require	ment	met	
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)	, 🛛		
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.	\square		
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC),	\square		
	hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-			
	trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\square		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			\square
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			\square
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as			\boxtimes
	pentachlorophenol and derivatives (see legal reference).			
D 4.0*	Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm ² /week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.		Ш	
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact):	\boxtimes		
	http://www.lenovo.com/social_responsibility/us/en/ThinkGreen_products.html#environment			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\square		
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the	\boxtimes		
	design of the product). Exception: Batteries that are permanently installed for safety, performance, medical			
	or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference)	. 🖂		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).	\boxtimes		
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			\boxtimes
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protoco (see legal reference).	I 🔀		
	Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model n	^{umber*} 10CT, 10CU, 10CV, 10CW, 10J9, 10JA, 10JB, 10JC	ь Р
lssue da	te * 2015-07-07 Logo	lenovo
Produc	t environmental attributes - Market requirements - Environmental conscious design	Requirement met
ltem	*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes No n.a.
P6	Treatment information	
P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	
P7	Design Disassembly, recycling	
P7.1*	Parts that have to be treated separately are easily separable	
P7.2*	Plastic materials in covers/housing have no surface coating.	
P7.3*	Plastic parts >100g consist of one material or of easily separable materials.	
P7.4*	Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043.	
P7.5	Plastic parts are free from metal inlays or have inlays that can be removed with commonly available too	ols. 🛛 🗌
P7.6*	Labels are easily separable. (This requirement does not apply to safety/regulatory labels).	
	Product lifetime	
P7.7*	Upgrading can be done e.g. with processor, memory, cards or drives	
P7.8*	Upgrading can be done using commonly available tools	
P7.9.	Spare parts are available after end of production for: 5 years	
P7.10	Service is available after end of production for: 5 years	<u> </u>
17.10	Material and substance requirements	
P7.11*	Product cover/housing material type:	
	Material type: ABS Material type: PC Material type: PC-	ABS
P7.12	Electrical cable insulation materials of power cables are PVC free.	
P7.13	Electrical cable insulation materials of signal cables are PVC free	
P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.	
P7.15	All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21.	
	Note B2)	
P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:	
P7.17	Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) Mit. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g accorditions of flame retardants in printed circuit boards (without components) >25g accorditions	ing 🛛 🗌 🗌
P7.18	ISO 1043-4: <i>Brominated Epoxy Resin See P14</i> Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparation	ns in
	 concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for each flame retardant. The list must co complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 	
	3. Chemical name: , CAS #: , Supplier: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4:	
P7.19	Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45 R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3)	5, 🔀 🗌
P7.20	Of total plastic parts' weight >25g, recycled material content is 42%	
P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.	
P7.22	Light sources are free from mercury	
P8	Batteries	
P8.1*	Battery chemical composition:	
P8.2	Batteries meet the requirements of the following voluntary program/s:	

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	10CT, 10CU, 10CV, 10CW, 10J9, 10JA, 10JB	, 10JC	
Issue date *	2015-07-07	Logo	lenovo

Item	t environmental atti	ributes - warket	requirements	(continued)	Requirement Yes No	<u>n.</u>
P9	Energy consumption	on			Tes No	
9.1	For the product the f		els or energy con	sumptions are rep	oorted: See P14	_
	The product is shipp					
Energy n	mode *	Power level at 100 V AC	Power level 115 V AC	at Power level 230 V AC	at Reference / Standard for energy modes and test method *	
Catan		IUU VAC	IIJ VAC	230 V AC	lest method	
Catego	ory u lle State - WOL Enable	d W	W	W	Use for ENERGY STAR V6 registration (Pidle)	Тг
	le State - WOL Enable	-	W	W	Use for ENERGY STAR V6 registration (P _{idle})	
	S3) - WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(P _{sleep})	
	S3) - WOL Disabled	W	W	W	Reference	
	- WOL Enabled	W	W	W	Use for ENERGY STAR V6 registration(Poff)	
	- WOL Disabled	W	W	W	Use for EuP	
Catego			-	1	1	
	lle State - WOL Enable		25.01 W	26.27 W	Use for Energy Star V6.0 registration(P _{shortIdle})	
	le State - WOL Enable		21.85 W	21.88 W	Use for Energy Star V6.0 registration(P _{Longidie})	
	S3) - WOL Enabled	1.01 W	1.02 W	1.24 W	Use for Energy Star V6.0 registration (P _{sieep})	
	S3) - WOL Disabled	1.01 W	1.02 W	1.24 W	Reference	
	- WOL Enabled	0.49 W	0.51 W	0.70 W	Use for Energy Star V6.0 registration (P _{off})	
Off (S5)	- WOL Disabled	0.37 W	0.37 W	0.37 W	Use for EuP	[
Catego	ory 12					
	lle State - WOL Enable		W	W	Use for Energy Star V6.0 registration(P _{ShortIdle})	[
Long Idl	le State - WOL Enable	d W	W	W	Use for Energy Star V6.0 registration(P _{Longldle})	Τ
Sleep (S	S3) - WOL Enabled	W	W	W	Use for Energy Star V6.0 registration (P _{s/eep})	
Sleep (S	S3) - WOL Disabled	W	W	W	Reference	
Off (S5)	- WOL Enabled	W	W	W	Use for Energy Star V6.0 registration (P _{off})	Π
Off (S5)	- WOL Disabled	W	W	W	Use for EuP	1
Catego	ory I3					T
Short Id	lle State - WOL Enable	d 27.92 W	27.87 W	27.80 W	Use for Energy Star V6.0 registration(P _{ShortIdle})	T
Long Id	le State - WOL Enable	d 25.75 W	25.58 W	25.36 W	Use for Energy Star V6.0 registration(P _{Longldle})	+
Sleep (S	S3) - WOL Enabled	1.00 W	1.01 W	1.24 W	Use for Energy Star V6.0 registration (P _{sleep})	
Sleep (S	S3) - WOL Disabled	1.00 W	1.01 W	1.24 W	Reference	ti
Off (S5)	- WOL Enabled	0.48 W	0.50 W	0.71 W	Use for Energy Star V6.0 registration (P _{off})	ti
	- WOL Disabled	0.37 W	0.37 W	0.37 W	Use for EuP	ti
	ory D1					+
	lle State - WOL Enable	d 30.50 W	30.52 W	30.11 W	Use for Energy Star V6.0 registration(P _{shortIdle})	┼╴
	le State - WOL Enabled		29.95 W	30.15 W	Use for Energy Star V6.0 registration(P _{Longidle})	-
	63) - WOL Enabled	0.99 W	1.01 W	1.23 W	Use for Energy Star V6.0 registration (P _{sleep})	┼╴
	63) - WOL Disabled	0.99 W	1.01 W	1.23 W	Reference	┼
	- WOL Enabled	0.99 W	0.51 W	0.71 W	Use for Energy Star V6.0 registration (P _{ort})	╞
	- WOL Disabled	0.49 W	0.37 W	0.77 W	Use for EuP	╇
		0.37 VV	0.37 VV	0.37 VV	036 101 EUF	+L
	ory D2	d 05 04 W	25.0514/	26.20.14/	Hee few Energy Ofen MO () and to the the co	╇
	lle State - WOL Enable		35.25 W	36.30 W	Use for Energy Star V6.0 registration(P _{shortdle})	╷
	le State - WOL Enabled		35.02 W	35.53 W	Use for Energy Star V6.0 registration(P _{LongIdle})	
	53) - WOL Enabled	1.00 W	1.02 W	1.24 W	Use for Energy Star V6.0 registration (P _{sieep})	
	S3) - WOL Disabled	1.00 W	1.02 W	1.24 W	Reference	
	- WOL Enabled	0.49 W	0.50 W	0.70 W	Use for Energy Star V6.0 registration (P _{off})	
Off (S5)	- WOL Disabled	0.37 W	0.37 W	0.37 W	Use for EuP	

plugged i	load I power supply / c in the wall outlet b octed from the prod	but	W	W			
TEC Typical E	Energy Consumpti	kWh/week	kWh/week	kWh/week			
Etec * Annual E	nergy Consumpti	on Cat I1: 109.06; Cat I3: 121.77; Cat D1: 135.30; Cat D2:156.05; kWh/year	Cat I1: 107.85; Cat I3: 121.47; Cat D1:135.38; Cat D2:156.51; kWh/year	Cat I1:112.60 ; Cat I3:121.90 ; Cat D1:135.27; Cat D2:161.28; kWh/year	$E_{TEC} = (8760/1000)$ + $P_{ShortIdle} \times 0.35$ +	$) \times (P_{off} \times 0.45 + P_{sleep} \times 0.95)$ $P_{Long/dle} \times 0.15)$	05
		Poff: Off Mode(S	5) - WOL Enabled;	P _{sleep} : Sleep Mode(S3) - WOL Enabled; P	P _{idle} : Idle State - WOL Enabled	1
Display re	esolution :	Megapixels					
Print Spe	ed :	Images per minute					
•		y save mode: 30 minutes	3				
P9.2*		out the energy save func		vith the product.		\square	
	ENERGY STA	R® version: Version 6.0	dated Septemb	or 10 2013 Produ	at actor on v 11 12 D1	רס 🔽 🚺	
	Others specify	:			c category. 11,13,01 ,		
P10	Emissions				c calegoly. <i>11,13,0</i> 1,		
	Emissions Noise emissio	on – Declared according					
P10 P10.1	Emissions			Declared A-weighted sound powe level L _{WAd} (Dec sound pre	clared A-weighted ssure level L_{pAm} (dB) on \square Bystander position p \square (only if product is	not
	Emissions Noise emissio	on – Declared according		Declared A-weighted sound powe	r 3) Operator positio Deskto	clared A-weighted issure level L_{pAm} (dB) m \square Bystander position p \square (only if product is	not
	Emissions Noise emissio Mode	on – Declared according Mode description		Declared A-weighted sound power level L _{WAd} (r 3) Operator positio Deskto	clared A-weighted essure level L_{pAm} (dB) on \boxtimes Bystander position p \boxtimes (only if product is operator attendo	not
	Emissions Noise emissio Mode	on – Declared according Mode description * HDD: Idle		Declared A-weighted sound power level L _{WAd} (* 3.6	r 3) Operator positio Deskto	clared A-weighted ssure level L_{pAm} (dB) m \boxtimes Bystander position p \boxtimes (only if product is operator attendor 24	not
	Emissions Noise emission Mode	on – Declared according Mode description * HDD: Idle * HDD: Operating ording to: X ISO7779	to ISO 9296	Declared A-weighted sound power level L _{WAd} (* 3.6 *3.7	r 3) Operator positio Deskto	clared A-weighted essure level L_{pAm} (dB) m \square Bystander position p \square (only if product is a second strength le \square (operator attended 24 26	not

Model nu	umber *	10C7	, 10CU, 1	0CV, 10	CW, 1	0 J 9, 1	10JA, 10.	JB, 10JC			
Issue da	te *	2015-07-	07					Logo	leno	VO	
Product	t environr	nental at	tributes - Mark	<u>et requirem</u>	ents (cont	tinued)			Require	ment	met
Item									Yes	No	n.a.
	Chemic	al emissio	ons from printing	products							
P10.3*	Test per	formed acc	cording to ECMA-	328 (ISO/IEC	28360) star	ndard 🗌,	other specify:				\boxtimes
P10.4	Typical e	emission ra	ate (print phase) is	s (mg/h):							\boxtimes
		Dust	Ozone	Styrene	Benze	ene	TVOC				
P10.5	Chemica	al emission	requirements of t	the following v	oluntary pro	ogram/s	are met fo	or:			X
	[Dust 🗌	Ozone 🗌	Styren	e 🗌	Benz	ene 🗌	TVOC 🗌			_
	Electron	nagnetic e	emissions								
P10.6	Compute program		neets the requirer	ment for low fr	equency ele	ectromagn	etic fields of the	e following voluntar	ry 🖂		
P11	Consun	able mate	erials for printing	products							

A Safety Data Sheet (SDS) is available for the ink/toner preparation, even if not legally required (see P4.3).

The display meets the ergonomic requirements of ISO 9241-307 for visual display technologies.

Product does not contain free TBBPA in printed circuit boards(without components)>25g.

http://downloads.energystar.gov/bi/qplist/laptops_prod_list.xls (insert appropriate web url)

The physical input device meets the requirements of ISO 9995 and ISO 9241-410.

Product packaging material type(s): Corrugated paper weight (kg): 1.6 Product packaging material type(s): Fabricate PE weight (kg): 0.277

Product packaging material type(s): PP weight (kg):0.06

Specify media for user and product documentation (tick box):

2-sided (duplex) printing/copying is an integrated product function.

Ergonomics for computing products

Product plastic packaging is free from PVC.

Packaging and documentation

Electronic X. Paper X. Other

Additional information (See Note B4)

fiber: 0% (Japan only 70%)

information.

Paper containing post-consumer recycled fibers can be used, provided that it meets the requirements of

For paper user and product documentation, please specify contained percentage of post-consumer recycled

NOTE: Supplier makes no representations, guarantees, assurances or warranties whether express or implied, regarding the information contained in this document. All information provided by supplier in this document is provided based on supplier's knowledge available at the time of completion, and supplier shall have no obligation to update such information. The information provided here is approximate and provided for informational purposes only. See a Lenovo Account Representative for more

See Energy Star Qualified (insert appropriate Product type; i.e. Desktop, Notebook, etc.) for the latest information:

P11.1*

P11.2*

P11.3*

P12.1*

P12.2*

P13

P13.1*

P13.2*

P13.3*

P13.4*

P14

P7.17

P9

P12

EN12281

 \times

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet - PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkCentre M79 SFF	Logo
Model Number	10CT, 10CU, 10CV, 10CW, 10J9, 10JA, 10JB, 10JC	lenovo
Issue Date	2015-07-07	
Additional information	Only 10CT, 10CU, 10JA, 10JB is Erp Lot3 Qualified, which is equ	ipped with ES PSU.

P7.1.1 Product environmental attributes									
(d)	Year of manufacture:	Availible on product label							
(e)		lity adjustments applied when a is tested with switchable graphic	II discrete graphics cards (dGfx) cs mode with UMA driving the						
(f)	E TEC value (kWh) and capab are enabled: Cat. B 125.84 Cat. C 141.99 Cat. D 146.33	lity adjustments applied when a l	ll discrete graphics cards (dGfx)						
(g)	idle state power demand (Watts	40.64							
(h)	sleep mode power demand (Wa	1.72							
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);								
(j)	off mode power demand (Watts);								
(k)	off mode with WOL enabled po	0.70							
(I)	Internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable): 10% 79.37% 20% 84.71% 50% 86.83% 100% 83.69%								
(m)	External power supply efficience		N/A						
	10% 20% 50% 100% Average ; or Level:								
(0)	The minimum number of loading cycles that the batteries can withstand (applies only to notebook computers): N/A								
(f)	Test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing: Test voltage in V and frequency in Hz 230V/50Hz Total harmonic distortion of the electricity supply system ≤2% Information and documentation on the instrumentation, set-up and circuits used for electrical testing								
	Instrument Type	Range Used Or ***	Make and Model **						
	AC Power Source	1~280VAC;1~550HZ;1000V A.	NF;EC1000S; SN:9152124						
	Digital Watch	Full range	CASIO; HS-70W; SN:208Q08R						

		Powe	r Meter	0~600V;0~20A	YOKOGAWA;WT210;SN:91M94456 0					
		Hvarothe	ermograph	15~35℃/15~90%	testo; 608-H1,SN:1034895602					
	-		nemometer	0~20m/s,-20~70℃	Testo;425;SN:02591883					
			easuring	1°;1-300cd/ m ²	Konica Minolta;LS-110;					
(p-1)	The n	neasurem	ent methodology	· · · · ·	mentioned in points (I) – internal PSI Leffici	ency:				
(P ')	(p-1) The measurement methodology used to determine information mentioned in points (I) – internal PSU efficiency: 80 PLUS® Program									
(p-2)	The measurement methodology used to determine information mentioned in points (m) - external PSU									
	efficiency:									
(p-3)	The measurement methodology used to determine information mentioned in points (o) – loadingcycles batteries: N/A									
(p-4)	The measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:									
IEC 62301										
(q)	Sequ	ence of st	teps for achievin	g a stable condition with respe	ct to power demand::					
Power on -> Wait 5 minutes ->Stable condition										
(r) Description of how sleep and/or off mode was selected or programmed:										
Begin menu -> Power -> Select sleep or off mode										
(s)	(s) Sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:									
Control Panel->Power Options-> Change Settings-> Restore default settings for this plan										
(t) The duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes): 30 minutes										
(u)	(u)The length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):45 minutes45 minutes									
(v)	The length of time before the display sleep mode is set to activate after user inactivity (in minutes): 15 minutes									
(w)	Inforr	nation on	the energy-savir	ng potential of power managem	nent functionality:					
N/A										
(x)	User	informatio	on on how to ena	able the power management fur	nctionality:					
Refer to User Guide										
Additio	n Notebo	ok Batter	ry Information:							
Yes	No	n/a		computer is operated by batte	ery/ies that cannot be accessed and replac	ed by a non-professional				
			The battery	[ies] in this product ca	nnot be easily replaced by users	themselves				
			,							
Additional information										
Additio		lation								