

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Think	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5F1 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo.	
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment	html	
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_i		

	pased on product specification or test results based obtained from sample testing), that the product ts given in this declaration.
Type of product *	Notebook
Commercial name *	ThinkPad S3; ThinkPad Yoga 460;
	ThinkPad Yoga 14
Model number *	20G0, 20G1, 20EL, 20EM, 20FY
Issue date *	
Intended market *	☑ Global Europe Asia, Pacific & Japan Americas Other
Additional information	

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Control	Requireme	nt met
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality control such as organized by IT-Företagen (see www.itecodeclaration.org).	ol 🔀	

Model number *	20G0, 20G1, 20EL, 20EM, 20FY		
Issue date *	2015/7/23	Logo	lenovo

Product	roduct environmental attributes - Legal requirements			met
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).	\boxtimes		
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes		
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1) (\boxtimes
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/materials.html			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\boxtimes		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	X		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.			
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montreal Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.			

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	20G0, 20G1, 20EL, 20EM, 20FY		
Issue date *		Logo	lenovo.

**mandatory to fill in .Additional information regarding each item may be found under P14.	Product	oduct environmental attributes - Market requirements - Environmental conscious design				et
Information for recyclers/treatment facilities is available (see legal reference).		*=mandatory to fill in. Additional information regarding each item may be found under P14.	Yes	No	n.	a.
Design Disassembly, recycling P7.1° Parts that have to be treated separately are easily separable						_
Disassembly, recycling P7.1º Plast that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.4º Plastic parts > 250 paws material coate of easily separable materials. P7.4º Plastic parts > 250 paws material coate according to 150 11469 referring ISO 1043. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6º Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.70 Upgrading can be done e.g. with processor, memory, cards or drives P7.8º Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.9. Service is available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Product cover/housing material type: Material and substance requirements P7.11 Electrical cable insulation materials of power cables are PVC free. P7.12 Electrical cable insulation materials of signal cables are PVC free P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 Hame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Note E2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: CAS #. 40039-93-8 All 2 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) □ TBBPA (reactive) ☑ Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER. CAS #. 40039-93-8 All 2 Chemical specifications of flame retardants in printed circuit boards (without components): ≥25g according ISO 1043-4: Chemical aname: , CAS #: 3. Chemical name: , CAS #: 4. Chemical pastic parts >25g or free from mercury in the follo				Ш		
P7.1º Parts that have to be treated separately are easily separable P1.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic parts >25g have material or of easily separable materials. P7.4º Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.6 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.6 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Product cover/housing material type: P7.12 Electrical cable insulation materials of signal cables are PVC free Material yepe: PA+50%GF Material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.12 Electrical cable insulation materials of signal cables are PVC free P7.13 Electrical cable insulation materials of signal cables are PVC free All cover/housing plastic parts >25g are free from chlorine and bromine. P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Note B2) P7.17 All: Chemical specifications of flame retardants in printed circuit boards (without components): P7.18 All infinited circuit boards (without components): P7.19 All: Chemical specifications of flame retardants in printed circuit boards (without components): P7.10 All: Chemical apecifications of flame retardants in printed circuit boards (without components): P7.11 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in Science Processor (Processor Processor Processor Processor Processor Processor Proces	P7					
P7.3* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material coates according to ISO 11469 referring ISO 1043. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.8* Upgrading can be done using commonly available tools P7.9* Service is available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymen) P7.12* Electrical cable insulation materials of signal cables are PVC free. P7.13* Electrical cable insulation materials of signal cables are PVC free P7.14* All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15* All printed circuit boards (without components) >25g are halogen free, as defined in IEC61249-2-21. (See Note B2) P7.16* Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: CAS #: 40039-93-8 Alt 2 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive)	P7.1*	Parts that have to be treated separately are easily separable			T	$\overline{}$
P7.3* Plastic parts > 100g consist of one material or of easily separable materials. P7.4* Plastic parts > 25g have material codes according to ISO 11469 referring ISO 1043. P7.5* Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 5 years P7.10* Service is available after end of production for: 5 years P7.11* Product cover/housing material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.12* Electrical cable insulation materials of signal cables are PVC free. P7.13* Electrical cable insulation materials of signal cables are PVC free. P7.14* All cover/housing plastic parts >25g are free from chlorine and bromine. All printed circuit boards (without components) > 25g are hadgen free. as defined in IEC61249-2-21. (See Note B2) P7.16* Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: BBPA (additive)				$\overline{\nabla}$	-	╡
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 5 years Material and substance requirements P7.10* Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: PC+ABS Material type: PC+BS Material type:			\dashv		+	╡
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done e.g. with processor, memory, cards or drives Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Spare parts are available after end of production for: 5 years Material and substance requirements P7.11 Service is available after end of production for: 5 years Material and substance requirements P7.12 Electrical cable insulation materials of power cables are PVC free Material byte: PA+50%GF Material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.13 Electrical cable insulation materials of signal cables are PVC free All cover/housing plastic parts >25g are free from chlorine and bromine. P7.14 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Marking: Label PR) All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Marking: Label PR) All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Marking: Label PR) All Printed circuit boards (without components): TBBPA (reactive) District Printed Carbon Printed		, ,		井		┿
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material land substance requirements P7.12* Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See □ □ Note B2) P7.16 Hame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) □, TBBPA (reactive) □, Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER. CAS #. 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) □, TBBPA (reactive) □, Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER. CAS #. 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components): □ concentrations above 0.1%; Comment: No legal limits exist, this is a market requirement. 1. Chemical aname: , CAS #: 2. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: W □ 1 P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1%; classified as R45, □ 1 R40, R46, R46, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts weight >25g, biobased material content is 0%. Under the product in the production of lames. P7.19 Plastic parts >25g are free from mercury from mercury fr				╫	-	┽
P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Product cover/housing material type: P7.12				井	<u> </u>	┽
P7.75 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for 5 years P7.10 Service is available after end of production for 5 years Material and substance requirements P7.11 Product cover/housing material type: PC+ABS Material type: PA+50%GF Material type: PC+ABS Material type: PA+50%GF Material type: PC+ABS Material type: PA+50%GF Material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) Note B2) P7.16 Alt. 1 Chemical specifications of fiame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.0			Щ		
P7.8° Upgrading can be done using commonly available tools	P7 7*				T	_
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years				-	-	+
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11' Product cover/housing material type: Material type: PC+ABS Material					_	┽
Material and substance requirements						
P7.11* Product cover/housing material type: Material type: PA+50%GF Material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) ☐, TBBPA (reactive) ☑, Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brainer retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 3. Chemical name: , CAS #: 3. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Ught sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg Batteries Batteries Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,	P7.10					<u></u>
Material type: PA+50%GF Material type: PC+ABS Material type: CFRP (Carbon fiber-reinforced polymer) P7.12 Electrical cable insulation materials of power cables are PVC free	D7 11*					
P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts 'weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts 'weight >25g, recycled material content is 0%. P7.22 Light sources are free from mercury	P1.11		ed not	mer)		
P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.12					1
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:		·	$\overline{\square}$		+	┪
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:		<u> </u>		H		╡
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:				\dashv	-	╡
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: P7.17	1 7.10	· · · · · · · · · · · · · · · · · · ·		ш	_	_
P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) ☐, TBBPA (reactive) ☑, Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8. Batteries Batteries meet the requirements of the following voluntary program/s: US Cali2Recycle, and add EPBA,	P7.16	/	\square			1
Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) . TBBPA (reactive) . Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
TBBPA (additive), TBBPA (reactive), Other; chemical name: BISPHENOL A DIGLYCIDYL ETHER, CAS #: 40039-93-8 Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Batteries meet the requirements of the following voluntary program/s: US Call/2Recycle, and add EPBA,	P7.17					-
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,				Ш	L	
Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Brominated Epoxy Resin See P14 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium lon/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide			\boxtimes			
P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium lon/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call/2Recycle,and add EPBA,						
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries Batteries Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,	P7 18					
Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Batteries meet the requirements of the following voluntary program/s: US Call/2Recycle, and add EPBA,	1 1.10			\boxtimes		
1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,		· · · · · · · · · · · · · · · · · · ·				
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle, and add EPBA,						
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,				_	_	_
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,						
P7.20 Of total plastic parts' weight >25g, recycled material content is 6.9% P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,	P7.19					
P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,	D7 00					
P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,						
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries P8.1* Battery chemical composition: Lithium lon/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,		1 1 0				1
P8 Batteries P8.1* Battery chemical composition: Lithium Ion/Lithium Manganese Dioxide P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,	11.22			ш	L	_
P8.2 Batteries meet the requirements of the following voluntary program/s: US Call2Recycle,and add EPBA,	P8					
	P8.1*				[
	P8.2					

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model num	nber*	20G0 :	20G1 20F	EL, 20EM,	20FY					
Issue date		2000, 1	1001, 202	L, LULIN,	201 1			Logo	lenovo	
Product o	nvironm	ontal attrib	utos - Markot i	requirements (continued)				Requiremen	t mot
Item	HIVITOIIIII	entai attiib	utes - Market	requirements (continueu)				Yes No	
P9	Energy c	onsumption							100 110	11.0.
9.1		•		els or energy cons	umptions are	rep	orted: See P14	(PIC: Env.)	
Energy mod	-			Power level at		at			energy modes and test	
Peak (On-r	max)		W	W	W		Full load			
Category	v I1			1						- I
		OL Enabled	7.116 W	7.224 W	7.572 W	Us	se for ENERGY	STAR V6.1	registration (P _{idle})	
Long Idle	State - WO	L Enabled	5.112W	4.596W	5.532W	Us	se for ENERGY	STAR V6.1	registration (P _{idle})	
Sleep (S3)	- WOL En	abled	0.456 W	0.480 W	0.540 W	Us	se for ENERGY	STAR V6.1	registration (P _{sleep})	
Off (S5) - V	VOL Enab	led	0.216 W	0.228W	0.300W	Us	se for ENERGY	STAR V6.1	registration (P _{off})	
Category	y <u>12</u>		ı	1	L	<u> </u>				
Short Idle	State - WC	OL Enabled	W	W	W	Us	se for ENERGY	STAR V6.1	registration (P _{idle})	\boxtimes
Long Idle	State - WO	L Enabled	W	W	W	Us	se for ENERGY	STAR V6.1	registration (P _{idle})	
Sleep (S3)	- WOL En	abled	W	W	W	Us	se for ENERGY	STAR V6.1	registration (P _{sleep})	
Off (S5) - V	VOL Enab	led	W	W	W	Us	se for ENERGY	STAR V6.1	registration (P _{off})	
EPS No-loa			W	W	W					
		ly / charger								
plugged in the disconnected										
4.000		p. 0 a a o a ,								
PTEC *	_		W	W	W					
Typical Ene	ergy Consu	ımption								
TEC *										
Typical Ene	ergy Consu	ımption	kWh/week	kWh/week	kWh/week					
ETEC *			25.05	24.98	27.06	F	= (8760/1000)	x (P _{o#} x 0	.25 + P _{sleep} x 0.35 +	
Annual Ene	ergy Consu	ımption	kWh/year	kWh/year	kWh/year		$p_{ong_Idle} \times 0.10 + P_s$			
				5) - WOL Enabled; I	P _{sleep} : Sleep M	ode(S3) - WOL Enable	d; P _{idle} : Idle	State - WOL Enabled	
Display res	olution* :	3.686 Megap	oixels							
Print Speed	d * :	Image	es per minute							
Default time	e to enter e	energy save i	mode: 20minutes							
P9.2*	Informatio	n about the	energy save func	tion is provided wi	th the produc	t.	- 1			
P9.3*				ents of the followi			ram/s:			
	ENERGY Others sp		sion: Version 6.1	Tier: Pro	duct category	/ :				
P10	Emission									
1 10			clared according	to ISO 9296						
P10.1	Mode		e description		Declar			Declared A	-	
					A-weight sound p			pressure le	evel $L_{p{\sf Am}}$ (dB)	
					level L_{W}			sition 🔀	Bystander positions	1
					11.1. Z _W	ΑU '	-,	sktop 🔀	/ambaif and the first	
							or Desk	side 🗌	(only if product is not operator attended)	
	Idle	* Idl	e mode		* 2.8			2.		1 🔲
	Operation	•	erating(HDD)		* 2.8			2		
	Other mod	de Op	erating(CPU)		3.5			2	7	

Other (only if not covered by ECMA-74 with L_{pAm} measurement distance)
The product meets the acoustic noise requirements of the following voluntary program/s:

P10.2

Measured according to: ☐ ISO7779 ☐ ECMA-74

m)

Model nu	mber *	20G0, 20G1, 20EL, 20EM, 20FY				
Issue date	e *	2015/7/23 L	ogo	leno	10 .	
	environn	nental attributes - Market requirements (continued)		Require		
Item	01	I ambadaa faa adadaa aa dada		Yes	No	n.a.
P10.3*		al emissions from printing products				
		formed according to ECMA-328 (ISO/IEC 28360) standard, other specify:				
P10.4	,,	emission rate (print phase) is (mg/h):				\boxtimes
		Dust Ozone Styrene Benzene TVOC				
P10.5			oc 🗌			
		nagnetic emissions				
P10.6	program		ing voluntary			
P11	Consum	able materials for printing products				
P11.1*	A Safety	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally require	d (see P4.3).			\boxtimes
P11.2*	EN1228		requirements	of		
P11.3*	2-sided (duplex) printing/copying is an integrated product function.				\boxtimes
P12		nics for computing products				
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technologie	S.	\boxtimes		
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.		\boxtimes		
P13		ng and documentation				
P13.1*	Product Product Product	packaging material type(s): 80% recycled corrugated paper weight (kg): packaging material type(s): 100% recycled Thermoform cushion packaging material type(s): plastic bags weight (kg): 0.0155 packaging material type(s): plastic handle weight (kg): 0.0075				
P13.2*	Product	plastic packaging is free from PVC.				
P13.3*	Specify r	media for user and product documentation (tick box):				
P13.4*		er user and product documentation, please specify contained percentage of post-cons	umer recycled	t		
P14		nal information (See Note B4)				
	informati knowled provided informati		s provided bas such informa	sed on supp tion. The inf	olier's formati	ion
P9	See Ene	rgy Star Qualified Notebooks & Tablet Computers for the latest information: ww.energystar.gov/index.cfm?fuseaction=find_a_product.showProductGroup&	ogw_code=C	0		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19

Lenovo ErP Lot3 Information Sheet

- PC / Notebook -

As required by COMMISSION REGULATION (EU) No 617/2013 of 26 June 2013 implementing Directive 2009/125/EC of the European Parliament and of the Council with regard to ecodesign requirements for computers and computer servers (ErP Lot3).

Products scope of this sheet:

Desktop computer, integrated desktop computer, and notebook computer

This document is only valid in connection with the IT Eco Declaration of the specific Product.

Commercial name	ThinkPad S3; ThinkPad Yoga 460; ThinkPad Yoga 14	Logo
Model Number	20G0, 20G1, 20EL, 20EM, 20FY	_
Issue Date	2015/8/25	lenovo.
Additional information		

d)	year of manufacture:	2015
e)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete gr disabled and if the system is tested with switchable graphics mode with UMA driving the display:	raphics cards (dGfx) are
	Category (according to ErP Lot 3): A Etec: 15.78 Etec: 16.93	
f)	E TEC value (kWh) per ErP Lot 3 Category and capability adjustments applied when all discrete graenabled:	aphics cards (dGfx) are
	Category (according to ErP Lot 3): A Etec: 15.80 Etec: 16.94	
(g)	idle state power demand (Watts);	A:4.88 / B:5.62
(h)	sleep mode power demand (Watts);	A:0.73/B:0.62
(i)	sleep mode with WOL enabled power demand (Watts) (where enabled);	A:0.75 / B: 0.62
(j)	off mode power demand (Watts);	A:0.44/ B:0.31
(k)	off mode with WOL enabled power demand (Watts) (where enabled);	A:0.44/ B:0.31
(l)	internal power supply efficiency at 10 %, 20 %, 50 % and 100 % of rated output power (if applicable):	
	10% 20% 50% 100% Average	
(m)	external power supply efficiency (if applicable):	
	Average: 45W: 87,27%,87,31%,88,83%	
(0)	the minimum number of loading cycles that the batteries can withstand (applies only to notebook con	nputers): 800 cycles
(p-1)	the measurement methodology used to determine information mentioned in points (I) – interefficiency:	rnal PSU
(p-2)	the measurement methodology used to determine information mentioned in points (m) – exte efficiency: EPA "Test Method for Calculating the Energy Efficiency of Single-Voltage External AC-DC and Power Supplies" dated August 11, 2004	
(p-3)	the measurement methodology used to determine information mentioned in points (o) - load batteries:	lingcycles

IEC 61960 measurement methodology	
(p-4) the measurement methodology used to determine information mentioned in maximum, idle, sleep, off mode power as defined in Point P9.1 in the Product IT Eco Declaration:	
IEC 62623 measurement methodology	
(q) sequence of steps for achieving a stable condition with respect to power demand::	
IEC 62623 measurement methodology	
(r) description of how sleep and/or off mode was selected or programmed:	
By selecting sleep and/or off mode thru Windows operating system	
(s) sequence of events required to reach the mode where the equipment automatically changes to sleep and/or off mode:	
Automatically changes to sleep after 20 minutes	
(t) the duration of idle state condition before the computer automatically reaches sleep mode, or another condition which does not exceed the applicable power demand requirements for sleep mode (in minutes):)
(u) the length of time after a period of user inactivity in which the computer automatically reaches a power mode that has a lower power demand requirement than sleep mode (in minutes):	
(v) the length of time before the display sleep mode is set to activate after user inactivity (in minutes):)
(w) information on the energy-saving potential of power management functionality:	
User information described in User Guide and Power Manager under ThinkVantage menu in all programs	
(x) user information on how to enable the power management functionality:	
User information described in User Guide and Power Manager under ThinkVantage menu in all programs	
(z) test parameters for measurements: — test voltage in V and frequency in Hz, — total harmonic distortion of the electricity supply system, — information and documentation on the instrumentation, set-up and circuits used for electrical testing:	
230V, 50Hz, Total Harmonic Distortion <2 %	
Addition Notebook Battery Information:	
Yes No n/a This notebook computer is operated by battery/ies that cannot be accessed and by a non-professional user.	replaced
(Battery not user replaceable) (Battery user replaceable) The battery[ies] in this product cannot be easily replaced by themselves	users
Additional information	