

Product environmental attributes – THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P14.

Brand *	ThinkPad	Logo	
Company name *	Lenovo		
Contact information *	Lenovo Global Environmental Affairs Alvin L Carter 1009 Think Place Building 2 / 5J3 Morrisville, North Carolina 27560 alcarter@lenovo.com	lenovo	
Internet site *	www.pc.ibm.com/ww/lenovo/about/environment		
Additional information			

	based on product specification or test results based obtained from sample testing), that the product ts given in this declaration.			
Type of product *	Notebook PC			
Commercial name *	ThinkPad X1			
Model number *	M/T: 1286/1291/1292/1293/1294/1295/1296			
Issue date *	011, May 17			
Intended market *	🛛 Global 📃 Europe 📃 Asia, Pacific & Japan 📃 Americas 📃 Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality Control			Requirement met		
Item		Yes	No		
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration	\boxtimes			
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).				

Model nu	Imber *	ThinkPad X1 M/T: 1286/1291/1292/1293/1294/1295	/129	6			
Issue date *		2011, May 17 Logo	lene	DVC			
Product	environ	mental attributes - Legal requirements	Require	ment	met		
Item			Yes	No	n.a.		
P1	Hazardo	ous substances and preparations					
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)						
P1.2*		s do not contain Asbestos (see legal reference). nt: Legal reference has no maximum concentration value.	\boxtimes				
P1.3*	hydrobro trichloro	s do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), pmofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- ethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum ration values.					
P1.4*		s do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated /l (PCT) in preparations (see legal reference).	\boxtimes				
P1.5*		s do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the ntaining at least 48% per mass of chlorine in the SCCP (see legal reference).	\boxtimes				
P1.6*	Textile a Tris-(azi	nd leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), ridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). ht: Legal reference has no maximum concentration values.					
P1.7*		nd leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split amines. (See legal reference and Note B1)			\boxtimes		
P1.8*	Wooden pentach	parts do not contain arsenic and chromium as a wood preservation treatment as well as orophenol and derivatives (see legal reference). ht: Legal reference has no maximum concentration values.			\square		
P1.9*	Parts wit	th direct and prolonged skin contact do not release nickel in concentrations above 0.5 am/cm ² /week (see legal reference).	\square				
P1.10*	Comment: Max limit in legal reference when tested according to EN1811:1998. REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/environment.html						
P2	Batterie						
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)						
P2.2*		ells used in the product do not contain more than 2% by weight of mercury. Other batteries or ators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)	\boxtimes				
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medical or data integrity reasons do not have to be "easily removable". (See legal reference)						
P3	Safety,	EMC connection to the telephone network and labeling					
P3.1*	The proc	duct complies with legally required safety standards as specified (see legal reference).	\square				
P3.2*	The prod	duct complies with legally required standards for electromagnetic compatibility (see legal reference)					
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies						
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).						
P4	Consumable materials						
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see						
P4.2*		er is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes		
P4.3*	If the ink product/	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).					
P5	Product	packaging					
P5.1*		ng and packaging components do not contain more than 0.01% lead, mercury, cadmium and ent chromium by weight of these together.	1				
P5.2*		ackaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes				
P5.3*	Protocol	duct packaging material is free from ozone depleting substances as specified in the Montrea (see legal reference). (see legal reference has no maximum concentration values.	I 🛛				

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Issue date * 2011, May 17 Product environmental attributes - Market requirements - Environ Item *=mandatory to fill in. Additional information regarding each item ma Period Context P61 Information for recyclers/treatment facilities is available (see legal re P7 Design Disassembly, recycling P7.1 P7.1 Parts that have to be treated separately are easily separable P7.3 Plastic materials in covers/housing have no surface coating. P7.4 Plastic parts >25g have material codes according to ISO 11469 refe P7.5 Plastic parts are free from metal inlays or have inlays that can be re P7.6 Labels are easily separable. (This requirement does not apply to sal Product lifetime Product lifetime P7.7 Upgrading can be done using commonly available tools P7.8 Spare parts are available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material type: MS P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g in covers / housings are marked a Marking: FR(40) P7.15	92/1293/1294/1295/1296
*=mandatory to fill in. Additional information regarding each item maps P61 Information for recyclers/treatment facilities is available (see legal repr P7 Design Disassembly, recycling P7.1 Parts that have to be treated separately are easily separable P7.2 Plastic materials in covers/housing have no surface coating. P7.3 Plastic parts >25g have material codes according to ISO 11469 refe P7.4 Plastic parts are free from metal inlays or have inlays that can be re P7.6 Labels are easily separable. (This requirement does not apply to sal P7.6 Labels are easily separable. (This requirement does not apply to sal P7.6 Upgrading can be done e.g. with processor, memory, cards or drive: P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years Material and substance requirements P7.12 P7.13 Electrical cable insulation materials of power cables are PVC free. P7.14 All cover/housing plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.14 All cover/housing plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.16 Flame retarded plastic parts >25g contain the following flame concentrat	Logo <i>lenovo</i>
=mandatory to fill in. Additional information regarding each item mapped P61 Information for recyclers/treatment facilities is available (see legal representation) P71 Parts that have to be treated separately are easily separable P72. Plastic materials in covers/housing have no surface coating. P73.* Plastic parts >25g have material codes according to ISO 11469 refe P7.4 Plastic parts are free from metal inlays or have inlays that can be re P7.5 Plastic parts are free from metal inlays or have inlays that can be re P7.6 Labels are easily separable. (This requirement does not apply to sal Product lifetime Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drive: P7.8 Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years Material and substance requirements P7.11 P7.11 Product cover/housing material type: P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.16 Filame retarded p	tel conceieus design Beguirement me
P66 Treatment information P6.1* Information for recyclers/treatment facilities is available (see legal reprint of the production production of the production producting producting producting production production producting produ	
26.1* Information for recyclers/treatment facilities is available (see legal reference) 27 Design 27.1* Parts that have to be treated separately are easily separable 27.2* Plastic materials in covers/housing have no surface coating. 27.3* Plastic parts >25g have material codes according to ISO 11469 refe 27.4* Plastic parts >25g have material codes according to ISO 11469 refe 27.5 Plastic parts are free from metal inlays or have inlays that can be re 27.6* Labels are easily separable. (This requirement does not apply to sal 27.6* Upgrading can be done e.g. with processor, memory, cards or drives 27.8 Upgrading can be done using commonly available tools 27.9 Spare parts are available after end of production for: 5 years 27.10 Service is available after end of production for: 5 years 27.11* Product cover/housing material type: 27.12 Electrical cable insulation materials of power cables are PVC free. 27.13 Electrical cable insulation protessor proteins and protessor prote	
Disassembly, recycling P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >25g have material codes according to ISO 11469 reference P7.4* Plastic parts are free from metal inlays or have inlays that can be reprint P7.4* Plastic parts are free from metal inlays or have inlays that can be reprint P7.4* Upgrading can be done e.g. with processor, memory, cards or drives P7.4* Upgrading can be done e.g. with processor, memory, cards or drives P7.4* Upgrading can be done e.g. with processor, memory, cards or drives P7.4* Upgrading can be done e.g. with processor, memory, cards or drives P7.4* Upgrading can be done e.g. with processor, memory, cards or drives P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.10* P7.10 Service is available after end of production for: 5 years Material type: <i>PC+ABS-FR(40)</i> Material type: <i>PPS</i> P7.11* Product cover/housing material sof power cables are PVC free P7.12 Electrical cable insulation materials of power cables are PVC free P7.14 All cover/housing plastic parts >25g are free	ce).
P7.1* Parts that have to be treated separately are easily separable P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts >100g consist of one material or of easily separable mm P7.4* Plastic parts >25g have material codes according to ISO 11469 refe P7.5* Plastic parts are free from metal inlays or have inlays that can be re P7.6* Labels are easily separable. (This requirement does not apply to sat Product lifetime Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drive: P7.8 Spare parts are available after end of production for: 5 years Material and substance requirements P7.1 P7.10 Service is available after end of production for: 5 years Material type: $PC+ABS-FR(40)$ Material type: PPS P7.12 Electrical cable insulation materials of signal cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen 1 Note B2) P7.16 P7.17 Alt. 1 Chemical specifications of flame retarda	
P7.2' Plastic materials in covers/housing have no surface coating. P7.3' Plastic parts >100g consist of one material or of easily separable material codes according to ISO 11469 reference P7.4' Plastic parts are free from metal inlays or have inlays that can be reference P7.4' Plastic parts are free from metal inlays or have inlays that can be reference P7.5' Plastic parts are free from metal inlays or have inlays that can be reference P7.6' Upgrading can be done e.g. with processor, memory, cards or driver P7.7' Upgrading can be done using commonly available tools P7.8' Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Product cover/housing material type: Material type: $PC+ABS-FR(40)$ Material type: PC P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g in covers / housings are marked a Marking: $FR(40)$ P7.16 Flame retarded plastic parts >25g in covers / housings are marked a ISO 1043-4: $FR(40)$ P7.18 Alt 1	
Plastic parts >100g consist of one material or of easily separable material codes according to ISO 11469 refe Product lifetime Product cover/housing material type: material spears Material and substance requirements Profile Product cover/housing material sof power cables are PVC free. Pr.11 Product cover/housing plastic parts >25g are free from chlorine and bron Pr.13 Electrical cable insulation materials of signal cables are PVC free. Pr.14 All cover/housing plastic parts >25g are free from chlorine and bron Pr.15 All printed circuit boards (without components) >25g are halogen for Note B2 Pr.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> Pr.17 Alt. 1 <	
P7.4* Plastic parts >25g have material codes according to ISO 11469 refe P7.5 Plastic parts are free from metal inlays or have inlays that can be refered. Product lifetime Product lifetime P7.5* Upgrading can be done e.g. with processor, memory, cards or driver P7.8* Upgrading can be done e.g. with processor, memory, cards or driver P7.8* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 5 years Material and substance requirements Product cover/housing material type: P7.11* Product cover/housing materials of power cables are PVC free. P7.12 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen 1 Note B2) P7.16 P7.17 Alt 1 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt 1 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: </td <td></td>	
 Plastic parts are free from metal inlays or have inlays that can be ferent. Plastic parts are free from metal inlays or have inlays that can be ferent. Product lifetime Product lifetime Product lifetime Product lifetime Product lifetime Upgrading can be done e.g. with processor, memory, cards or driver. Spare parts are available after end of production for: 5 years Material and substance requirements Product cover/housing material type: Material type: PC+ABS-FR(40) Material problem insulation materials of signal cables are PVC free. Pr.13 Electrical cable insulation materials of signal cables are PVC free. Pr.14 All cover/housing plastic parts >25g are free from chlorine and bront Note B2) Pr.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: FR(40) Pr.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) , TBBPA (reactive) , Other; chemical name phosphaphenanthrene-10-oxide), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: FR(40) Pr.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants in plustic parts >25g acc Complete chemical name; CAS #: , Supplier: Chemi	s. 🛛 🗌
P7.6* Labels are easily separable. (This requirement does not apply to sat Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or driver P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type: P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) _, TBBPA (reactive) P7.18 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) _, TBBPA (reactive) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is	SO 1043.
Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or driver P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type: P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen 1 Note B2) P7.16 P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name; CAS #:	d with commonly available tools.
P7.7* Upgrading can be done e.g. with processor, memory, cards or driver P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11* Product cover/housing material type: Material type: $PC+ABS-FR(40)$ Material type: PPS P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen 1 Note B2) P7.16 P7.17 Att. 1 Chemical specifications of flame retardants in printed circuit boards 1SO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier:	gulatory labels).
P7.8Upgrading can be done using commonly available toolsP7.9.Spare parts are available after end of production for: 5 yearsP7.10Service is available after end of production for: 5 yearsP7.11Product cover/housing material type: Material type: $PC+ABS-FR(40)$ P7.12Electrical cable insulation materials of power cables are PVC free.P7.13Electrical cable insulation materials of signal cables are PVC free.P7.14All cover/housing plastic parts >25g are free from chlorine and bronP7.15All printed circuit boards (without components) >25g are halogen 1 Note B2)P7.16Flame retarded plastic parts >25g in covers / housings are marked a Marking: $FR(40)$ P7.17Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (reactive)	
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material type: <i>PC+ABS-FR(40)</i> P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive)	
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material type: <i>PC+ABS-FR(40)</i> P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen for Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: 2. Chemical aname: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4.1. 2 Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4.1. 2	
P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type: Material type: $PC+ABS-FR(40)$ Material type: PPS P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen for Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: $FR(40)$ P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) [], TBBPA (reactive) [], Other; chemical name phosphaphenanthrene-10-oxide), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: $FR(40)$ P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4.1. 2 Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4.1. 2 Supplier: 4.1. 2 Chemical apacifications of flame	
Material and substance requirements P7.11* Product cover/housing material type: Material type: <i>PC+ABS-FR(40)</i> Material type: <i>PPS</i> P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen 1 Note B2) P7.16 P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive), TBBPA (reactive), Other; chemical name phosphaphenanthrene-10-oxide), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name:	
 Product cover/housing material type: Material type: <i>PC+ABS-FR(40)</i> Material type: <i>PPS</i> P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and brom Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive), TBBPA (reactive), Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4.1. 2 Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th 77.20 Of total plastic parts' seight >25g, recycled material content is 0 %. Batteries 	
 P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 P7.18 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive), TBBPA (reactive), Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: <i>35948-25-5</i> Alt. 2 P7.18 Alt. 1 P7.18 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: P7.18 Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name:	
 P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bron P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) TBBPA (reactive) Other; chemical name phosphaphenanthrene-10-oxide), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: Chemical specifications of flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: Chemical specifications of flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the provide all plastic parts '>25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the provide plastic parts' weight >25g, recycled material content is 0%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and mics parts not included) P7.20 Of total plastic parts' weight >25g, biobased material content is 0%. Batteries 	Material type:
P7.14 All cover/housing plastic parts >25g are free from chlorine and brom P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) , TBBPA (reactive) , Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: . Chemical name: , CAS #: . Chemical name: , CAS #: . Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R5	
P7.15 All printed circuit boards (without components) >25g are halogen f Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) , TBBPA (reactive) , Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara Alt. 2 Chemical specifications of flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and a	
Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive), TBBPA (reactive), Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the plastic parts / 25g are free from flame retarial content is 0 %. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0 %. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.22 Light sources are free from mercury	
 P7.16 Flame retarded plastic parts >25g in covers / housings are marked a Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive), TBBPA (reactive), Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name: , CAS #: , Supplier:	as defined in IEC61249-2-21. (See 🗌 🔀
Marking: <i>FR(40)</i> P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) , TBBPA (reactive) , Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS mumber and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. <td></td>	
 Chemical specifications of flame retardants in printed circuit boards TBBPA (additive) , TBBPA (reactive) , Other; chemical name <i>phosphaphenanthrene-10-oxide</i>), CAS #: 35948-25-5 Alt. 2 Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: <i>FR(40)</i> P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS number and supplier. Chemical name: , CAS #: , Supplier: Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th P7.20 Of total plastic parts' weight >25g, recycled material content is <i>0</i>%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is <i>0</i>%. Batteries 	ling ISO 1043-4:
Chemical specifications of flame retardants in printed circuit boards ISO 1043-4: FR(40) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th P7.20 Of total plastic parts' weight >25g, recycled material content is 0 %. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0 %. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.22 Light sources are free from mercury P8 Batteries	
Flame retarded plastic parts >25g contain the following flame concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ preparar R40, R46, R48, R50, R51, R53, R60, R61 and any combination of the P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. Batteries Batteries	out components) >25g according
 Provide a list of all used flame retardants including MSDS for eac complete chemical name, CAS number and supplier. 1. Chemical name: , CAS #: , Supplier: 2. Chemical name: , CAS #: , Supplier: 3. Chemical name: , CAS #: , Supplier: 4. Chemical name: , CAS #: , Supplier: 4. Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0% P7.22 Light sources are free from mercury P8 Batteries 	Irdant substances/preparations in
Alt. 2 Chemical specifications of flame retardants in plastic parts >25g acc P7.19 Plastic parts >25g are free from flame retardant substances/ prepara R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th P7.20 Of total plastic parts' weight >25g, recycled material content is 0 %. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0 % P7.22 Light sources are free from mercury P8 Batteries	ne retardant. The list must contain
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of th P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury P8 Batteries	g ISO 1043-4: <i>FR(40)</i>
Battery, AC adapter, Cords, Drives, Keyboard, LCD, and misc parts not included.) P7.21 Of total plastic parts' weight >25g, biobased material content is 0% P7.22 Light sources are free from mercury P8 Batteries	above 0.1% classified as R45,
P7.22 Light sources are free from mercury P8 Batteries	sment is about main computer parts only.
P8 Batteries	
- A L Battery chemical composition. Lithuim Ion/Lithuim Manganese Di	
 P8.2 Batteries meet the requirements of the following voluntary program/s 	

Annex B of ECMA-370 4th edition, June 2009

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model nu		nkPad X1	M/T: 1286	/1291/1292	/1293/1294/1295/12	296	
Issue date	e * 2011, May 17				Logo	novo	
Product	environmental a	attributes - Market	requirements (c	ontinued)	Re	quirement m	
ltem	tem Yes N						
P9	Energy consum	ption					
9.1		ne following power lev iipped w/ WOL Enable		imptions are reported	ed: See P14		
Energy mo	ode *	Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy and test method *	ergy modes	
Peak (On-	-max)	65/90 W	65/90 W	65/90 W	Full load		
Catego	v A						
	- WOL Enabled	9.30 W	8.48 W	8.76 W	Use for ENERGY STAR Registr	ation(P _{idle})	
Sleep (S3) - WOL Enabled	1.57 W	1.62 W	1.62 W	Use for ENERGY STAR Registr	ation(P _{sleen})	
) - WOL Disabled	1.41 W	1.50 W	1.41 W	Reference		
		1.28 W					
	WOL Enabled	-	1.30 W	1.24 W	Use for ENERGY STAR Registr		
Off (S5) -	WOL Disabled	1.01 W	0.92 W	1.05 W	Use for EuP		
Catego	<u>'y B</u>						
Idle State	- WOL Enabled	W	W	W	Use for ENERGY STAR Registr	ation(P _{idle})	
Sleep (S3) - WOL Enabled	W	W	W	Use for ENERGY STAR Registr	ation(P _{sleep})	
Sleep (S3) - WOL Disabled	W	W	W	Reference		
	WOL Enabled	W	W	W	Use for ENERGY STAR Registr		
	WOL Disabled	W	W	W	Use for EuP		
EPS No-la			0.24 W	0.38 W			
(External pl	oower supply / ugged in the wall disconnected from	W	0.24 W	0.38 W		L	
TEC Typical En	ergy Consumption	kWh/week	kWh/week	kWh/week			
Etec * Annual En	ergy Consumption	32.54 kWh/year	30.54 kWh/year	30.96 kWh/year	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.000) \times (P_{off} \times 0.0000) \times (P_{o$	6 + P _{sleep} x	
		Poff: Off Mode(S5) -	WOL Enabled; Psleep:	Sleep Mode(S3) - WO	DL Enabled; Pidle: Idle State - WOL El	nabled	
Display re	solution : 1366 x	768 Megapixels					
Print Spee		Images per minu	to				
		a 1					
		save mode: 20 minute		h the product			
P9.2*		t the energy save fund	•	•			
P9.3*	ENERGY STAR®	ts the energy requirer version: Version 5.2 NERGY STAR for E	2 dated January, 20	011 Product catego	ry: <mark>A</mark>		
P10	Emissions						
P10.1		 Declared according Mode description 	to ISO 9296	Declared	Declared A-weighted		
F IU.I	Mode	Mode description		Declared A-weighted sound power	sound pressure level L_{pArr}	, (dB)	
				level L_{WAd} (B)	Desktop (only if p	ler positions roduct is not or attended)	
	Idle	* HDD: Idle		* 2.7	18		
	Operation	* HDD: Operating		* 3.7	27		
	Other mode						
	Measured accord	ling to: 🔀 ISO7779 [ECMA-74 (only if not (covered by ECMA-7	4 with L _{pAm} measurement distance		
		m)					

Model nu	mber *	ThinkPad X1 M/T: 1286/1291/1292/1293/1	294/1295/	1296					
Issue date *		2011, May 17 Logo				lenovo			
Product	environn	nental attributes - Market requirements (continued)		Require	mont	mot			
Item		inental attributes - market requirements (continued)		Yes	No	n.a.			
Item	Chemica	al emissions from printing products		163	-	11.a.			
P10.3*		formed according to ECMA-328 (ISO/IEC 28360) standard , other specify:							
P10.4		emission rate (print phase) is (mg/h):							
		Dust Ozone Styrene Benzene TVOC							
P10.5	Chemica	I emission requirements of the following voluntary program/s are met for :				\square			
			TVOC						
		nagnetic emissions							
P10.6		er display meets the requirement for low frequency electromagnetic fields of the follo /s: MPR-II(3 pin AC adapter only)	owing voluntary	\bowtie					
P11		able materials for printing products							
P11.1*	-	Data Sheet (SDS) is available for the ink/toner preparation, even if not legally requ				\boxtimes			
P11.2*	Paper c EN1228	ontaining post-consumer recycled fibers can be used, provided that it meets the 1.	ne requirements o	of 🗌		\square			
P11.3*	2-sided ((duplex) printing/copying is an integrated product function.				\boxtimes			
P12	Ergonor	nics for computing products							
P12.1*	The disp	lay meets the ergonomic requirements of ISO 9241-307 for visual display technolog	gies.						
P12.2*	The phys	sical input device meets the requirements of ISO 9995 and ISO 9241-410.							
P13		ng and documentation							
P13.1*	Product	packaging material type(s): Corrugated Cardboard weight (kg): 0.676 packaging material type(s): Recycled Polyethylene(RLDPE) weight (kg packaging material type(s): Others (plastic bags) weight (kg							
P13.2*		plastic packaging is free from PVC.		\boxtimes					
P13.3*		nedia for user and product documentation (tick box):							
P13.4*		ic 🔀, Paper 🔀, Other 📃 r user and product documentation, please specify contained percentage of post-co							
P13.4		% (Japan only 70%)	nsumer recycled						
P14	Addition	nal information (See Note B4)							
	informati knowled	Supplier makes no representations, guarantees, assurances or warranties whether on contained in this document. All information provided by supplier in this documer ge available at the time of completion, and supplier shall have no obligation to upda here is approximate and provided for informational purposes only. See a Lenovo A on.	t is provided base te such information	d on supp on. The inf	olier's formati				
P9		ERGY STAR Qualified Notebooks & Tablet Computers for the latest informatio ownloads.energystar.gov/bi/qplist/laptops_prod_list.xls	n:						

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19