

Product environmental attributes - THE ECO DECLARATION

The declaration may be published only when all rows and/or fields marked with an * are filled-in (n.a. for not applicable).

Additional information regarding each item may be found under P14.

Brand *	Lenovo	Logo			
Company name *	Lenovo				
Contact information *	enovo Global Environmental Affairs Ivin L Carter 209 Think Place uilding 2 / 5F1 forrisville, North Carolina 27560 foarter@lenovo.com				
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html				
Additional information	The latest version of this document can be found at http://www.lenovo.com/social_responsibility/us/en/datasheets_monitors.html				

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.				
Type of product *	Display			
Commercial name *	L197 Wide			
Model number *	MT:4434			
Issue date *	2013.11.25			
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other			
Additional information				

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

Quality	Quality Control R		
Item		Yes	No
QC1 *	The company enforces an internal quality control scheme to ensure the correctness of this eco declaration		
QC2 *	The company is a member of an eco declaration system that enforces regular independent quality contro such as organized by IT-Företagen (see www.itecodeclaration.org).	I 🔀	

Model number *	L197wA MT:4434		
Issue date *	2013.11.25	Logo	lenovo

Product	environmental attributes - Legal requirements	Requirement met		
Item		Yes	No	n.a.
P1	Hazardous substances and preparations			
P1.1*	Products do not contain more than; 0.1% lead, 0.01% cadmium, 0.1% mercury, 0.1% hexavalent chromium, 0.1% polybrominated biphenyls (PBB) or 0.1% polybrominated diphenyl ethers (PBDE). (See legal reference and Note B1)			
P1.2*	Products do not contain Asbestos (see legal reference). Comment: Legal reference has no maximum concentration value.			
P1.3*	Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1-trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.4*	Products do not contain more than; 0.005% polychlorinated biphenyl (PCB), 0.005% polychlorinated terphenyl (PCT) in preparations (see legal reference).			
P1.5*	Products do not contain more than 0.1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the chain containing at least 48% per mass of chlorine in the SCCP (see legal reference).			
P1.6*	Textile and leather parts with direct skin contact do not contain Tri-(2,3,-dibromopropyl)-phosphate (TRIS), Tris-(aziridinyl)-phosphineoxide (TEPA), polybrominated biphenyl (PBB) (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.7*	Textile and leather parts with direct skin contact do not contain more than 0.003% Azo colorants that split aromatic amines. (See legal reference and Note B1)			X
P1.8*	Wooden parts do not contain arsenic and chromium as a wood preservation treatment as well as pentachlorophenol and derivatives (see legal reference). Comment: Legal reference has no maximum concentration values.			
P1.9*	Parts with direct and prolonged skin contact do not release nickel in concentrations above 0.5 microgram/cm²/week (see legal reference). Comment: Max limit in legal reference when tested according to EN1811:1998.			
P1.10*	REACH Article 33 information about substances in articles is available at (add URL or mail contact): http://www.lenovo.com/social_responsibility/us/en/materials.html			
P2	Batteries			
P2.1*	If the product contains a battery or an accumulator, it is labeled with the disposal symbol and if it contains more than 0.0005% of mercury (for button cells only) by weight, or more than 0.004% of lead, it shall be marked with the chemical symbol for the metal concerned, Hg or Pb. Information on proper disposal is provided in user manual. (See legal reference)			
P2.2*	Button cells used in the product do not contain more than 2% by weight of mercury. Other batteries or accumulators do not contain more than 0.0005% of mercury or 0.002% of cadmium. (See legal reference)			\boxtimes
P2.3*	Batteries and accumulators are easily removable by either users or service providers (as dependent on the design of the product). Exception: Batteries that are permanently installed for safety, performance, medica or data integrity reasons do not have to be "easily removable". (See legal reference)			
P3	Safety, EMC connection to the telephone network and labeling			
P3.1*	The product complies with legally required safety standards as specified (see legal reference).	\square		
P3.2*	The product complies with legally required standards for electromagnetic compatibility (see legal reference).	\boxtimes		
P3.3*	If product is intended for connection to a public telecom network or contains a radio transmitter, it complies with legally required standards for radio and telecommunication devices (see legal reference).			
P3.4*	The product is labeled to show conformance with applicable legal requirements (see legal reference).	\boxtimes		
P4	Consumable materials			
P4.1*	If a photo conductor (drum, belt etc.) is used in the product, it does not contain cadmium max 0.01% (see legal reference and Note B1).			
P4.2*	If ink/toner is used in the product, it does not contain cadmium max 0.1% by weight (see legal reference).			\boxtimes
P4.3*	If the ink/toner formulation/preparation is classified as hazardous according to applicable regulations, the product/packaging is adequately labeled and a Safety Data Sheet (SDS) in accordance with these requirements is available (see legal reference).			
P5	Product packaging			
P5.1*	Packaging and packaging components do not contain more than 0.01% lead, mercury, cadmium and hexavalent chromium by weight of these together.	d 🔀		
P5.2*	Plastic packaging material is marked according to ISO 11469 referring ISO 1043 (see legal reference).	\boxtimes		
P5.3*	The product packaging material is free from ozone depleting substances as specified in the Montrea Protocol (see legal reference). Comment: Legal reference has no maximum concentration values.	I 🔀		

Note B1: Restriction applies to the homogeneous material, unless other specified and expressed in weight %.

Model number *	L197wA MT:4434		
Issue date *	2013.11.25	Logo	lenovo

*-mandatory to fill in. Additional information regarding each item may be found under P14.	Product	environmental attributes - Market requirements - Environmental conscious design	Require	ment	met		
Provided							
Disassembly, recycling	P6						
Disassembly, recycling P7.1º Pats that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic parts >20 plastic parts >100 g consist of one material or of easily separable materials. P7.4º Plastic parts >25 plastic parts >26 plastic parts >	P6.1*	Information for recyclers/treatment facilities is available (see legal reference).	\boxtimes				
P7.1º Parts that have to be treated separately are easily separable P7.2º Plastic materials in covers/housing have no surface coating. P7.3º Plastic parts >25g have material cord easily separable materials. P7.4º Plastic parts >25g have material cordes according to ISO 11469 referring ISO 1043. P7.5 Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.6º Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7º Upgrading can be done e.g. with processor, memory, cards or drives P7.7º Upgrading can be done e.g. with processor, memory, cards or drives P7.8º Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years	P7						
P7.3° Plastic materials in covers/housing have no surface coating. P1.3° Plastic parts >100g consist of one material or of easily separable materials. P7.4° Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.8° Upgrading can be done using commonly available tools P7.8° Upgrading can be done using commonly available tools P7.8° Upgrading can be done using commonly available tools P7.9° Sarvice is available after end of production for: 5 years Material and substance requirements P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Product cover/housing material type: Material and substance requirements P7.12 Electrical cable insulation materials of power cables are PVC free Material type: ABS Material type: PC Material cricuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.15 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Material specifications of flame retardants in printed circuit boards (without components): TBBPA (additive) TBBPA (reactive) On their, chemical name: Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1%: Chemical specifications of flam	P7.1*		\square	П	П		
P7.3* Plastic parts >100g consist of one material or of easily separable materials. P7.4* Plastic parts >25g have material codes according to ISO 11489 referring ISO 1043. P7.5* Plastic parts >25g have material codes according to ISO 11489 referring ISO 1043. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 5 years P7.9* Spare parts are available after end of production for: 5 years P7.10* Service is available after end of production for: 5 years P7.11* Product over/housing material type: P7.12* Electrical cable insulation materials of power cables are PVC free. Electrical cable insulation materials of signal cables are PVC free. P7.13* Electrical cable insulation materials of signal cables are PVC free P7.14* All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15* All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16* Note B2) P7.17* All printed circuit boards (without components) >25g are marked according ISO 1043-4: Marking: P7.17* All t. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.2*				Ħ		
P7.4* Plastic parts >25g have material codes according to ISO 11469 referring ISO 1043. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Sparing and be done using commonly available tools P7.9* Sparing are available after end of production for: 5 years P7.10* Service is available after end of production for: 5 years P7.11* Product cover/housing material type: Material and substance requirements P7.12* Electrical cable insulation materials of power cables are PVC free. P7.13* Electrical cable insulation materials of signal cables are PVC free. P7.14* All cover/housing plastic parts >25g are free from holivine and bromine. P7.15* All printed circuit boards (without components) >25g are marked according ISO 1043-4: Marking: P7.16* Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17* Alt 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according	P7.3*				Ħ		
P7.5° Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels).				Ħ	\overline{H}		
P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Service is available after end of production for: 5 years P7.12 Service is available after end of production for: 5 years P7.13 Material and substance requirements P7.14 Electrical cable insulation materials of yower cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Matking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) TBBPA (reactive) Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exists, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according IS				∺	\blacksquare		
P7.7 Upgrading can be done e.g. with processor, memory, cards or drives		, ,		+	\overline{H}		
P7.7° Upgrading can be done e.g. with processor, memory, cards or drives □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □	17.0			<u> </u>			
P7.8° Upgrading can be done using commonly available tools P7.9. Spare parts are available after end of production for: 5 years Service is available after end of production for: 5 years Material and substance requirements P7.11° Product cover/housing material type: Material type: ABS	P7.7*		\square	$\overline{}$			
P7.9. Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years				\forall	\blacksquare		
P7.10 Service is available after end of production for: 5 years Material and substance requirements					╫		
Material and substance requirements					╫		
P7.11* Product cover/housing material type: Material type: ABS	1 7.10	, ,					
Material type: ABS Material type: PC Material type: ABS Material type: PC Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) TBBPA (reactive) Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 2. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4. Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, biobased material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7 11*						
P7.12 Electrical cable insulation materials of power cables are PVC free. P7.13 Electrical cable insulation materials of signal cables are PVC free. P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name:, CAS #: 3. Chemical name:, CAS #: 3. Chemical name:, CAS #: 3. Chemical name:, CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury							
P7.14 All cover/housing plastic parts >25g are free from chlorine and bromine. P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:	P7.12			\boxtimes			
P7.15 All printed circuit boards (without components) >25g are halogen free. as defined in IEC61249-2-21. (See Note B2) P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive)	P7.13	Electrical cable insulation materials of signal cables are PVC free		$\overline{\boxtimes}$	$\overline{\Box}$		
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive), TBBPA (reactive), Other; chemical name:, CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name:, CAS #: 2. Chemical name:, CAS #: 3. Chemical name:, CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Light sources are free from mercury	P7.14	All cover/housing plastic parts >25g are free from chlorine and bromine.		Ħ	$\overline{\Box}$		
P7.16 Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4: Marking:	P7.15						
P7.17 Alt. 1 Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) ☐, TBBPA (reactive) ☒, Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.16	Flame retarded plastic parts >25g in covers / housings are marked according ISO 1043-4:					
Chemical specifications of flame retardants in printed circuit boards >25g (without components): TBBPA (additive) , TBBPA (reactive) , Other; chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: 4lt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Light sources are free from mercury ff mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	D7 17						
Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: FR(16) P7.18 Alt. 1 Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, biobased material content is 0%. P7.21 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg	17.17	Chemical specifications of flame retardants in printed circuit boards >25g (without components):					
Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in concentrations above 0.1%: Comment: No legal limits exist, this is a market requirement. 1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is %. P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		Chemical specifications of flame retardants in printed circuit boards (without components) >25g according ISO 1043-4: $FR(16)$					
1. Chemical name: , CAS #: 2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.18	Flame retarded plastic parts >25g contain the following flame retardant substances/preparations in	n 🔲				
2. Chemical name: , CAS #: 3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		· · · · · · · · · · · · · · · · · · ·					
3. Chemical name: , CAS #: Alt. 2 Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		,					
Chemical specifications of flame retardants in plastic parts >25g according ISO 1043-4: P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is 0%. P7.21 Of total plastic parts' weight >25g, biobased material content is 0%. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries							
P7.19 Plastic parts >25g are free from flame retardant substances/ preparations above 0.1% classified as R45, R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is %. P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries							
R40, R46, R48, R50, R51, R53, R60, R61 and any combination of these (See Note B3) P7.20 Of total plastic parts' weight >25g, recycled material content is %. P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries		Chemical specifications of flame retardants in plastic parts >25g according 15O 1043-4:			\boxtimes		
P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.19						
P7.21 Of total plastic parts' weight >25g, biobased material content is %. P7.22 Light sources are free from mercury If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.20	<u> </u>					
If mercury is used specify: Number of lamps: and max. mercury content per lamp: mg P8 Batteries	P7.21	Of total plastic parts' weight >25g, biobased material content is 0%.					
P8 Batteries	P7.22						
	Do						
PX 1" Rattery chamical composition:	P8.1*	Batteries Battery chemical composition:					
P8.1* Battery chemical composition:							

Note B2: IEC61249-2--21 has maximum limits for chlorine and bromine but does not address fluorine, iodine and astatine which are included in the group of halogens.

Note B3: 'Starting from January 2009, Risk phrases can be replaced by Hazard phrases according to the Globally Harmonized System (GHS), mandatory by December 2010.

Model number *	L197wA MT:4434		
Issue date *	2013.11.25	Logo	lenovo

Product environme	ental att	tributes - Market	requirements (continued)	Requirement	met		
Item					Yes No	n.a.		
P9 Energy co	•							
9.1 For the pro	oduct the	following power leve			ported: See P14			
Energy mode *		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference / Standard for energy modes and test method *			
Peak (On-max)		18.2 W	18.2W	18.8 W	Full load			
Category A								
Idle State - WOL Ena	bled	18.2 W	18.2 W	18.8 W	Use for ENERGY STAR V5 registration (P _{idle})			
Sleep (S3) - WOL En	abled	0.46W	0.46W	0.52 W	Use for ENERGY STAR registration(P _{sleep})			
Sleep (S3) - WOL Dis	abled	0.46 W	0.46 W	0.52W	Reference			
Off (S5) - WOL Enable	led	0.31W	0.31W	0.35 W	Use for ENERGY STAR V5 registration(Poff)			
Off (S5) - WOL Disab	led	0.31W	0.31W	0.35 W	Use for EuP			
Category B		1	•					
Idle State - WOL Ena	bled	W	W	W	Use for ENERGY STAR V5 registration(Pidle)			
Sleep (S3) - WOL En	abled	W	W	W	Use for ENERGY STAR V5 registration (P _{sleep})			
Sleep (S3) - WOL Dis	abled	W	W	W	Reference			
Off (S5) - WOL Enable	led	W	W	W	Use for ENERGY STAR V5 registration(Poff)			
Off (S5) - WOL Disab	led	W	W	W	Use for EuP			
EPS No-load		W	W	W				
(External power suppl charger plugged in the outlet but disconnecte the product.)	wall							
PTEC *		W	W	W				
Typical Energy Consu	mption							
TEC * Typical Energy Consu	mption	kWh/week	kWh/week	kWh/week				
ETEC * Annual Energy Consu	mption	49.86 kWh/year	49.86 kWh/year	51.70 kWh/ye ar	$E_{TEC} = (8760/1000) \times (P_{off} \times 0.6 + P_{sleep} \times 0.1 + P_{idle} \times 0.3)$			
		P _{off} : Off Mode(S5) -	WOL Enabled; P _{slee}	: Sleep Mode(S3)	- WOL Enabled; P _{idle} : Idle State - WOL Enabled			
Display resolution* :	1400*900	Megapixels						
Print Speed * :	Im	ages per minute						
Default time to enter e	nergy sa	ve mode: 15 second	S					
P9.2* Informatio	n about tl	he energy save func	tion is provided wi	th the product.				
ENERG		ets the energy requir ® version: vers	ements of the follo					
P10 Emission						_		
		Declared according	to ISO 9296					
P10.1 Mode Mode description		Declared	Declared A-weighted					
				A-weighted sound power				
				level L_{WAd} (
				W/tu	Desktop (only if product is not			
Idio	*	UDD:/d/s		*	or Desk side operator attended)			
Idle Operation	*	HDD:Idle HDD: Operating		*				
Other mod	de	. Tob. Operating						
		g to: ISO7779	ECMA-74		<u>_</u>	1		
Other (only if not covered by ECMA-74 with L _{pAm} measurement distance m)								
P10.2 The produ	ct meets	the acoustic noise re	· •	•				

Model nu	mber *	L197wA	MT:4434						
Issue date	e *	2013.11.25				Logo	lenov	10.	
	environn	nental attributes	s - Market require	ements (continued)			Require		
Item							Yes	No	n.a.
D 4 0 0 0			printing products						
P10.3*				EC 28360) standard,	, other specify:				
P10.4	Typical e	emission rate (print	phase) is (mg/h):						\boxtimes
		Dust Ozor			TVOC				
P10.5				ng voluntary program/s	are met for :				\boxtimes
				ene Benz	ene	TVOC			
		nagnetic emission							
P10.6	program.	/s: CE		w frequency electromagr	netic fields of the fo	ollowing voluntary			
P11			printing products						
P11.1*	-			ink/toner preparation, ev					\boxtimes
P11.2*	Paper co EN1228		sumer recycled fibe	ers can be used, provid	led that it meets	the requirements	of		\boxtimes
P11.3*	2-sided (duplex) printing/co	pying is an integrate	ed product function.					\boxtimes
P12		nics for computin							
P12.1*	The disp	lay meets the ergo	nomic requirements	of ISO 9241-307 for vis	ual display techno	ogies.	\boxtimes		
P12.2*	The phys	sical input device m	neets the requiremen	nts of ISO 9995 and ISC	9241-410.				\boxtimes
P13		ng and document							
P13.1*		packaging material		weight (kg): 0.22					
		packaging material		weight (kg): 0.03					
		packaging material		weight (kg): 0.02					
P13.2*	Product	packaging material plastic packaging is	free from PVC	weight (kg): 0.90			\square		\neg
P13.3*			product documenta	tion (tiple boy).					井
F 13.3		ic 🔀, Paper 🔀, C		tion (tick box).					Ш
P13.4*				ase specify contained po	orcentage of post	concumor rocyclos	1		$\overline{}$
1 13.4	fiber: 7		documentation, pie	ase specify contained po	sicerilage or post-	consumer recycled	1		Ш
P14		al information (Se	ee Note B4)						
	NOTE: S informati knowled provided informati	Supplier makes no in contained in this ge available at the shere is approximation.	representations, guass document. All info- time of completion, te and provided for i	arantees, assurances or rmation provided by sup and supplier shall have in informational purposes of	plier in this document on obligation to uponly. See a Lenovo	ent is provided bas date such informat Account Represe	sed on sup	plier's forma	3
P9				let Computers for the l			0		

Note B4: Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B

Reference	Declaration item
2002/95/EC (ROHS Directive)	P1.1, P4.1
REACH, Annex XVII	P1.6, P1.8, P4.2
REACH, Annex XVII	P1.4
REACH, Annex XVII	P1.2
REACH, Annex XVII	P1.7
REACH, Annex XVII	P1.9
Regulation (EC) No. 2037/2000, 2038/2000, 2039/2000	P1.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
2006/66/EC (Battery and accumulators Directive)	P2.1, P2.2, P2,3, P3.4, P8.1
2006/95/EC (Low Voltage Directive)	P3.1, 3.4
2004/108/EEC (New EMC Directive)	P3.2, 3.4
1999/5/EC (R&TTE Directive)	P3.3, 3.4
"REACH" Regulation (1907/2006), annex VII	P1.10
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P4.3
REACH article 31, annex II	P4.3
2004/12/EC (Directive on packaging and packaging waste)	P5.1
(97/129/EC) (Commission Decision on Identification System for Packaging Materials	P5.2
2037/2000/EC Regulation on Substances that Deplete the Ozone Layer	P5.3
2002/96/EC (WEEE directive)	P3.4, P6.1
(EC) No.1272/2008 regulation on classification, labeling and packaging (CLP)	P7.19