



ECMA/TC38-TG3/2015/026 (Rev. 1 – 15 April 2015)

Annex B2 - Product environmental attributes Computer monitors

The declaration may be published only when all rows and/or fields marked with * are filled-in (n.a. for not applicable). Additional information regarding each item may be found under P15.

Brand *	Lenovo	Logo					
Company name *	Lenovo						
Contact information *	Lenovo Global Environmental Affairs		Lenovo				
e-mail address	Alvin L Carter		LEIIOVO				
	alcarter@lenovo.com						
Internet site *	http://www.lenovo.com/social_responsibility/us/en/environment.html						
Additional information	The latest version of this document can be found at:						
	http://www.lenovo.com/ecodeclaration						

The company declares (based on product specification or test results based obtained from sample testing), that the product conforms to the statements given in this declaration.						
Type of product * Monitor						
Commercial name *	ThinkVision L27q					
Model number *	65CE					
Issue date *	2016/12/12					
Intended market *	☐ Global ☐ Europe ☐ Asia, Pacific & Japan ☐ Americas ☐ Other					
Additional information						

This is an uncontrolled copy when in printed form. Please refer to the contact information for the latest version.

About Annex B2

Annex B2 reflects Product environmental attributes relevant for Computers and Computer Monitors. The following items from the ECMA-370 Main body are not shown in the template:

P4.1 – P4.3 Consumable materials

P9.1 TEC and Print speed

P10.2 - P10.3 Chemical emissions from printing products

P11.1 - P11.3 Consumable materials for printing products

Model nu	mber *	65CE Logo	Lon					
Issue dat	e *	2016/12/12	Len		J _{TM}			
Product	environ	mental attributes - Legal requirements	Require	men	met			
Item			Yes	No	n.a.			
P1	Hazardo	ous substances and preparations						
P1.1*	Products	s do comply with current European RoHS Directive. (See legal reference and NOTE B1)						
P1.2*	Comment: Legal reference has no maximum concentration value.							
P1.3*	P1.3* Products do not contain Ozone Depleting Substances: Chlorofluorocarbons (CFC), hydrobromofluorocarbons (HBFC), hydrochlorofluorcarbons (HCFC), Halons, carbontetrachloride, 1,1,1- trichloroethane, methyl bromide (see legal reference). Comment: Legal reference has no maximum concentration values.							
P1.4*	terpheny	s do not contain more than; 0,005% polychlorinated biphenyl (PCB), 0,005% polychlorinated // (PCT) in preparations (see legal reference).						
P1.5*	chain co	s do not contain more than 0,1% short chain chloroparaffins (SCCP) with 10-13 carbon atoms in the entaining at least 48% per mass of chlorine in the SCCP (see legal reference).						
P1.6*	(see lega	th direct and prolonged skin contact do not release nickel in concentrations above 0,5 μg/cm²/week al reference). nt: Max limit in legal reference when tested according to EN1811:2011-5.						
P1.7*	REACH	Article 33 information about substances in articles is available at (add URL or mail contact): www.lenovo.com/social_responsibility/us/en/environment.html						
P2	Batterie							
P2.1*		oduct contains a battery or an accumulator, the battery/accumulator is labeled with the disposal Information on proper disposal is provided in user manual. (See legal reference)						
P2.2*	Batteries reference	s or accumulators do not contain more than 0,0005% of mercury or 0,002% of cadmium. (See legal e)			\boxtimes			
P2.3*	Batteries	s and accumulators are readily removable. (See legal reference)			\boxtimes			
P3	Conforn	nity verification & Eco design (ErP)						
P3.1*		duct is CE-marked to show conformance with applicable legal requirements (see legal reference). claration of Conformity can be requested at (add link or e-mail address):						
P3.2*		duct complies with the Eco design requirements for energy-related products,	\square	$\overline{}$				
1 3.2		al reference).		Ш	Ш			
	Required	d information is; given in item P15 or added to this document, available at (add URL):						
P5	Product	packaging						
P5.1*	Packagii	ng and packaging components do not contain more than 0,01% lead, mercury, cadmium an ent chromium by weight of these together.	d 🔀					
P5.2*	The pac	kaging materials are marked with abbreviations and numbers indicating the nature of the material(see legal reference).	s) 🔀					
P5.3*	(see lega	duct packaging material is free from ozone depleting substances as specified in the Montreal Protoco al reference). nt: Legal reference has no maximum concentration values.	ol 🔀					
P6		nt information						
P6.1*	Informati	ion for recyclers/treatment facilities is available (see legal reference).	X					

NOTE B1 Restriction applies to the homogeneous material, unless other specified and expressed in weight %. Stating "Yes" means that the product is compliant with the mandatory requirements.

Model number *	65CE	Logo	Lanava
Issue date *	2016/12/12		LEI IOVO"

Environmental conscious design Requirement met tell memorated by the fill in Additional information regarding each item may be found under P14. Yes No n.a. P7. Design Disassembly, recycling P7.1° Parts that have to be treated separately are easily separable	Product	t environmental attributes - Market requirements (See General NOTE GN below)			
P7.1 Parts that have to be treated separately are easily separable P7.2 Plastic materials in covers/housing have no surface coating. P7.3 Plastic materials in covers/housing have no surface coating. P7.4 Plastic materials in covers/housing have no surface coating. P7.5 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7 Upgrading can be done e.g. with processor, memory, cards or drives P7.8 Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for: 5 years Upgrading can be done using commonly available tools P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11 Particulation materials of external electrical cables are PVC free. Material type: ABS Material type: ABS Material type: PC Insulation materials of internal electrical cables are PVC free. P7.11 Sexternal plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated filame retardants, chlorinated filame retarded man adopty/vinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC of 1249-2-21. (See INOTE B2) P7.16 Particulation advision of filame retardants in printed circuit boards (without components): P7.17 Particulation of filame retardants in printed circuit boards (without components): P7.18 Alt. 1; Chemical specifications of flame retardants in printed circuit boards (without components): P7.18 A		- Environmental conscious design	Require	ment	met
Pr.1			Yes	No	n.a.
P7.1' Parts that have to be treated separately are easily separable P7.2' Plastic materials in covers/housing have no surface coating. P7.3' Plastic parts > 100 g consist of one material or of easily separable materials. P7.4' Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6' Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7' Upgrading can be done e.g. with processor, memory, cards or drives P7.8' Upgrading can be done e.g. with processor, memory, cards or drives P7.9' Spare parts are available after end of production for. 5 years P7.10 Service is available after end of production for. 5 years P7.11 Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.11 Insulation materials of external electrical cables are PVC free. P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of external electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) bromine and 0.4% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.18 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components) > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations in concentrations above 0.1%: 1. Chemical name: , CAS #	P7				
P7.2* Plastic materials in covers/housing have no surface coating. P7.3* Plastic parts > 100 g consist of one material or of easily separable materials. P7.4* Plastic parts > 25 g have material codes according to ISO 11468 referring ISO 1043-4. P7.5 Plastic parts > 25 g have material codes according to ISO 11468 referring ISO 1043-4. P7.6* Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9* Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: PC Material type: PC Material type: PC Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants. chlorinated flame retard on, 1% weight (1000 ppm) chlorine attributable to brominated flame retardants. PCBs (without components) as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substance	P7.1*				
P7.3° Plastic parts > 100 g consist of one material or of easily separable materials.					
P7.4° Plastic parts > 25 g have material codes according to ISO 11469 referring ISO 1043-4. P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6° Labels are easily separable. (This requirement does not apply to safety/regulatory labels). P7.6° Upgrading can be done e.g. with processor, memory, cards or drives P7.78° Upgrading can be done e.g. with processor, memory, cards or drives P7.8° Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11' Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: PC Material type: Material type: Material type: ABS Material type: PC Material type: PC Material type: Description (available of the tool) Material type: ABS Material type: PC Material type: Description (available of the tool) Material type: ABS Material type: PC Material type: Description (available tool) P7.12 Insulation materials of internal electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) bromine and 0.3% weight (3000 ppm) bromine and 0.3% weight (3		<u>`</u>			
P7.5 Plastic parts are free from metal inlays or have inlays that can be removed with commonly available tools. P7.6 Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7 Upgrading can be done e.g. with processor, memory, cards or drives Upgrading can be done e.g. with processor, memory, cards or drives Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11 Service is available after end of production for: 5 years Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyviny chlorider or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) pomp chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all ☑PCBs > 25 g ☐ are low halogen ☐ as defined in IEC 61249-2:21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Math. 1: Flame retarded plastic parts > 25 g contain in printed circuit boards > 25 g (without components): □ T8BPA (additive). ☐ T8BPA (reactive) (See NOTE B3). ☐ Other: chemical name. CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ In plastic parts > 25 g, flame retardant substances/preparations above 0.1% according ISO 1043-4: □ In plastic parts > 25 g, flame retardant substances/prepar				\dashv	H
P7.6' Labels are easily separable. (This requirement does not apply to safety/regulatory labels). Product lifetime P7.7' Upgrading can be done e.g. with processor, memory, cards or drives P7.8' Upgrading can be done e.g. with processor, memory, cards or drives P7.9' Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11' Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0.1% weight (1000 ppm) bromine and 0.1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0.3% weight (3000 ppm) bromine and 0.3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all \(\times \)PCBs > 25 g \(\times \) are low halogen: as defined in IEC 614249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: \[Mat.1: Chemical specifications of flame retardants in printed circuit boards (without components): \text{Mat.1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: \[\text{Mat.1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: \[\text{Mat.1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: \[\text{Mat.1: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: \[\text{Mat.1: Chemical specifications of flame re				$\overline{}$	
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done using commonly available tools P7.9* Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years P7.11				H	Ħ
P7.7* Upgrading can be done e.g. with processor, memory, cards or drives P7.8* Upgrading can be done e.g. with processor, memory, cards or drives P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material and substance requirements P7.12* Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1; Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): ■ TBBPA (additive), ■ TBBPA (reactive) (See NOTE B3), ■ Other: chemical name, CAS #: Alt. 2; Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1; Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #:					
P7.8° Upgrading can be done using commonly available tools P7.9 Spare parts are available after end of production for: 5 years P7.10 Service is available after end of production for: 5 years Material and substance requirements P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: PC Material type: P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all ☑PCBs > 25 g ☐ are low halogen as defined in IEC 61249-2-21. (See INOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): □TBBPA (additive). □TBBPA (reactive) (See NOTE B3). □Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: □ Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: □ Chemical name: , CAS #:	P7.7*			П	П
P7.10 Service is available after end of production for: 5 years Material and substance requirements	P7.8*	Upgrading can be done using commonly available tools		$\overline{\Box}$	$\overline{\Box}$
P7.11* Material and substance requirements P7.12* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: PC Material type: No. Material type: No. P7.12* Insulation materials of external electrical cables are PVC free.	P7.9	Spare parts are available after end of production for: 5 years			Ī
P7.11* Material and substance requirements P7.12* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS Material type: PC Material type: No. Material type: No. P7.12* Insulation materials of external electrical cables are PVC free.	P7.10				Ħ
P7.11* Product cover/housing material type (e.g. plastics, metal, aluminum): Material type: ABS		· · · · · · · · · · · · · · · · · · ·			
P7.12 Insulation materials of external electrical cables are PVC free. P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all ☑PCBs > 25 g ☐ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards, PCBs (without components): ☐TBBPA (additive), ☐TBBPA (reactive) (See NOTE B3), ☐ Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardants substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): ☐ FYES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.11*				
P7.13 Insulation materials of internal electrical cables are PVC free. P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all \(\text{PCBs} > 25 \text{ g}\) are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #:	··				
P7.14 External plastic casing/cover parts > 25 g contain no more than 0,1% weight (1000 ppm) bromine and 0,1% weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #:			<u> </u>		Ц_
weight (1000 ppm) chlorine attributable to brominated flame retardants, chlorinated flame retardants, and polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " 4lt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as					Ц_
polyvinyl chloride or 0,3% weight (3000 ppm) bromine and 0,3% weight (3000 ppm) chlorine in parts containing more than 25% post-consumer recycled content. P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.14			Ш	Ш
P7.15 Printed circuit boards, PCBs (without components) are low halogen: all PCBs > 25 g are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as					
as defined in IEC 61249-2-21. (See 1NOTE B2) P7.16 Flame retarded plastic parts > 25 g in covers / housings are marked according ISO 1043-4: Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:					
Marking: P7.17 Alt. 1: Chemical specifications of flame retardants in printed circuit boards > 25 g (without components): TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: chemical name, CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.15	Printed circuit boards, PCBs (without components) are low halogen: all ⊠PCBs > 25 g ☐ are low halogen as defined in IEC 61249-2-21. (See 1NOTE B2)	า 📙		
TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>chemical name</i> , CAS #: Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.16				
Alt. 2: Chemical specifications of flame retardants in printed circuit boards (without components) > 25 g according ISO 1043-4: P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.17]
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:		TBBPA (additive), TBBPA (reactive) (See NOTE B3), Other: <i>chemical name</i> , CAS #:	\boxtimes		
P7.18 Alt. 1: Flame retarded plastic parts > 25 g contain the following flame retardant substances/preparations in concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:					
concentrations above 0,1%: 1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:		according ISO 1043-4:		\boxtimes	
1. Chemical name: , CAS #: (See NOTE B4) 2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:	P7.18		n		
2. Chemical name: , CAS #: " 3. Chemical name: , CAS #: " Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as				\boxtimes	
3. Chemical name: , CAS #: Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4: P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as					
P7.19 In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as					
assigned the following Risk phrases; and Hazard statements: The source(s) for these classifications is/are found at (add URL(s)): Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as		Alt. 2: Chemical specifications of flame retardants in plastic parts > 25 g according ISO 1043-4:		\boxtimes	
The source(s) for these classifications is/are found at (add URL(s)): , (See note B5) P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.19	In plastic parts > 25 g, flame retardant substances/preparations above 0,1% are used which have been			
P7.20* Postconsumer recycled plastic material content is used in the product (See Note B6): If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as		assigned the following Risk phrases; and Hazard statements:			
If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as					
a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as	P7.20*	Postconsumer recycled plastic material content is used in the product (See Note B6):	\boxtimes		
a) Of total plastic parts' weight > 25 g, the postconsumer recycled plastic material content (calculated as		If YES; at least one of the two alternatives below shall be answered:			
a percentage of total plastic by weight) is 33%					
		a percentage of total plastic by weight) is 33%.			
or b) The weight of recycled material is 4775.6 g.					

GENERAL NOTE Standard references should direct to the latest version of a standard. If an older version of a standard is used, section P15 shall be used for explanation.

NOTE B2 IEC 61249-2-21 defines maximum limits of 900 ppm for each of the substances chlorine and bromine and a maximum limit of 1500ppm of these substances combined. The standard does not address fluorine, iodine and astatine which are included in the group of halogens.

NOTE B3 and B4 A Guidance document on Chemical substances is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B5 If a certain substance has been assigned a certain risk phrases / hazard statement in the referenced source, this does not necessarily mean the substance has been tested for all of the hazards referred to by a certain customer.

NOTE B6 Applies to a product containing plastic parts whose combined weight exceeds 100 g with the exception of printed circuit boards, cables, connectors and electronic components and bio-based plastic material.

Model number *	65CE	Logo	Lanava
Issue date *	2016/12/12		LEI IOVO"

Product environmental attributes - Market requirements (continued)	Requi	remer	nt met
Item	Yes	No	n.a.

	Material and substance requirements (continued)						
P7.21*	Biobased plastic m	naterial content is used	I in the product (See N	OTE B7):			
	 If YES; at least one of the two alternatives below shall be answered; a) Of total plastic parts' weight > 25 g, the biobased plastic material content (calculated as a percentage of total plastic by weight) is %. or 						
		the biobased plastic r	naterial is g.				
P7.22*	Light sources are f	ree from mercury, i.e.	less than 0,1 mg/lamp.				
Do		specify: Number of lan	nps: and maxim	num mercury content pe	er lamp: mg		
P8.1*	Batteries Battery chemical c	omposition:					
P9		tion (See NOTE B8)					
P9.1			s or energy consumpti	ons are reported:			
Energy mo		Power level at 100 V AC	Power level at 115 V AC	Power level at 230 V AC	Reference/Standard for energy modes and test method *		
Peak (On-	max)	21.2 W	19.3 W	21.3 W	Full load		
Categor	<u>y</u>						
Short Idle Enabled	State - WOL	21.3 W	19.3 W	21.3 W	Use for ENERGY STAR V6 registration (P _{idle})		
Long Idle Enabled	State - WOL	21.3 W	19.3 W	21.3 W	Use for ENERGY STAR V6 registration (P _{idle})		
Sleep (S3)	- WOL Enabled	0.3 W	0.3 W	0.3 W	Use for ENERGY STAR V6 registration(P _{sleep})		
Sleep (S3)	- WOL Disabled	0.3 W	0.3 W	0.3 W	Reference		
Off (S5) - I	WOL Enabled	0.19 W	0.19 W	0.22 W	Use for ENERGY STAR V6 registration(P _{off})		
Off (S5) - 1	WOL Disabled	0.19 W	0.19 W	0.22 W	Use for ErP		
		W	W	W	Reference		
Catagor							
Categor	<u>y</u>						
Short Idle Enabled	State - WOL	W	W	W	Reference		
Long Idle Enabled	State - WOL	W	W	W	Reference		
Sleep (S3)	- WOL Enabled	W	W	W	Reference		
Sleep (S3)	- WOL Disabled	W	W	W	Reference		
Off (S5) - I	WOL Enabled	W	W	W	Reference		
Off (S5) - I	WOL Disabled	W	W	W	Reference		
		W	W	W	Reference		
Categor	<u>y</u>						
Short Idle Enabled	State - WOL	W	W	W	Reference		

NOTE B7 The following is to be excluded from the calculation of percentage: printed circuit boards, labels, cables, connectors and electronic components and postconsumer recycled plastic

NOTE B8 A Guidance document on Energy Efficiency is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

NOTE B9 A Guidance document on Acoustic Noise is available; see http://www.ecma-international.org/publications/standards/Ecma-370.htm

Long Idle Enabled	e State - WOL	W	W	W	Reference		
Sleep (S3	B) - WOL Enabled	W	W	W	Reference		
Sleep (S3) - WOL Disabled W W		W	W	Reference			
Off (S5) - WOL Enabled		W	W	W	Reference		
Off (S5) -	WOL Disabled	W	W	W	Reference		
		W	W	W	Reference		
EPS No-le		W	W	W			
(External powe wall outlet but d	r supply / charger plugged in the lisconnected from the product.)						
PTEC *		28.7 W	28.05 W	28.33 W			
ETEC *	nergy Consumption	67 kWh/year	60.7 kWh/year	67.1 kWh/year			
	nergy Consumption	07 KVVII/yeai	00.7 KVVII/yeai	07.7 KVVII/yeai			
		I ncy Level (Internation	onal Efficiency Marking	Protocol) * : V/			
Display re	esolution * : 2560*14	140 megapixels	<u> </u>	<u> </u>			
Default tir	me to enter energy s	ave mode: 0.25 min	utes				
P9.2*			nction is provided with the	he product.			
P9.3	Energy efficiency	class (monitors onl	y): EPA7.0				
P10	Emissions	,	· <i>,</i>				
	Noise emission	 Declared according 	g to ISO 9296 (See NO	TE B9)			
P10.1	Mode	Mode description		Statistical upper	limit A-weighted sound power level, L _{WA,c} (B)		
	Idle	* HDD: Idle		*			
		* HDD: Operating		*			
	Other mode	Declared A-weighted s	ound pressure level (dB) $L_{ m p}$	pAm (operator	position desktop – idle)		
	Other mode $\frac{Declared A-weighted sound pressure level (dB)}{L_{pAm}}$ (operator position desktop – operating)						
	Measured according to: Signature ISO 7779 ECMA-74 Other (only if not covered by ECMA-74)						

Model number *		65CE	Logo	Lenovo.				
Issue date *		2016/12/12				Lelio	VO.	м
Product	environn	nental attribute	s - Market requiren	nents (continued)		Require	ment	met
Item			-			Yes	No	n.a.
		nagnetic emissio						
P10.4	program	(s):		requency electromagnetic fields of t	the following voluntar	у 🗌		
P12		mics for computir						
P12.1*			•	f ISO 9241-307 for visual display ted	chnologies.			
P12.2*	The physical input device meets the requirements of ISO 9995 and ISO 9241-410.							
P13		ing and document						
P13.1*	Product Product	packaging materia packaging materia packaging materia packaging materia	l type(s): PE Bag l type(s): Paper	weight (kg): 0.40 weight (kg): 0.03 weight (kg): 0.03 weight (kg): 1.13				
P13.2*			ckaging is free from PV	C.		\boxtimes		
P13.3*								
P13.4*			product documentatio Other	n (tick box):				
P13.5	Ùser and		item if paper documen ntation on paper media					
	Totally c	hlorine-free						
	Element	al chlorine-free						
	Processe	ed chlorine-free						
P14	Volunta	ry programs						
P14.1	The prod	duct meets the requ	uirements of the follow	ing voluntary program(s):				
	ENERG'	Y STAR®	Criteria version:	Date: Pro	oduct category:			
	Eco-labe		Criteria version:		oduct category:			
	Eco-labe		Criteria version:	Date: Pro	oduct category:			
P15		nal information (S						
P9				may vary; description of the test			- 41	
	informati knowled	ion contained in thi ge available at the I here is approxima	is document. All inform time of completion, an	intees, assurances or warranties whation provided by supplier in this do d supplier shall have no obligation to ormational purposes only. See a Le	ocument is provided be to update such inform	pased on supp nation. The inf	olier's formati	ion
P9				omputers for the latest information: find_a_product.showProductGroup	&pgw_code=CO			

NOTE B10 Additional lines may be inserted to declare further items, by positioning the cursor at the far right of the row and hitting the <Enter> key.

Legal references Europe Annex B2

Reference	Declaration item
Directive 2011/65/EU (RoHS Directive) * * Specific exemptions apply for certain products and applications.	P1.1
Regulation (EC) 1907/2006(REACH, Annex XVII	P1.2, P1.4, P1.6, P1.7
Regulation (EC) 2037/2000, 2038/2000, 2039/2000 (Marketing and use of Ozone layer depleting substances)	P1.3, P5.3
Norwegian regulation relating to restrictions on the use of certain dangerous chemicals 20.12.2002	P1.5
Directive 2013/56/EC (Battery and accumulators Directive) * * These provisions shall not apply where, for safety, performance, medical or data integrity reasons, continuity of power supply is necessary and requires a permanent connection between the appliance and the battery or accumulator.	P2.1, P2.2, P2,3, P8.1
Directive 2006/95/EC (Low Voltage Directive)	P3.1
Directive 2004/108/EC (EMC Directive)	P3.1
Directive 1999/5/EC (R&TTE Directive)	P3.1
Regulation (EC) 801/2013 amending Regulation (EC) No 1275/2008 with regard to ecodesign requirements for standby, off mode electric power consumption of electrical and electronic household and office equipment, and amending Regulation (EC) No 642/2009 with regard to ecodesign requirements for televisions	P3.1, P3.2
Regulation (EC) No 1272/2008 (CLP Regulation)	P7.19
Directive 2004/12/EC (Packaging Directive)	P5.1
Decision 97/129/EC (Secondary packaging legislation)	P5.2
Directive 2012/19/EU (WEEE directive)	P6.1